



HD 17/14-4 S Plus

The HD 17/14-4 S Plus, an upright cold water high-pressure cleaner, is equipped with an EASY!Force high-pressure gun and Servo Control for pressure and water flow regulation.

















- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Effortless operation at last: the EASY!Force high-pressure gun.
- EASY!Lock quick-release couplings: durable and robust. And five times faster than screws.

Proven Kärcher quality

- 4-pole water-cooled electric motor.
- Robust brass cylinder head and ceramic piston.

3 For increased safety

- Integrated electronics system for machine monitoring.
- Automatic switch-off in case of low voltage range or overvoltage.

Outstanding mobility

- Large rubber wheels for negotiating uneven surfaces, stairs and lan-
- Proven sack truck principle for easy, ergonomic transport.

TECHNICAL DATA AND EQUIPMENT





HD 17/14-4 S Plus

- Save time and effort: EASY!Force high-pressure gun and EASY!Lock quick-release couplings.
- Water-cooled three-phase motor
- Outstanding flushing action

Technical data		
Order no.		1.286-915.0
EAN code		4054278162959
Supply voltage	Ph/V/Hz	3 / 400 / 50
Flow rate	I/h	650 - 1700
Inlet temperature	°C	60
Working pressure	bar / MPa	30 - 140 / 3 - 14
Max. pressure	bar / MPa	154 / 15.4
Connection load	kW	9.4
Weight	kg	72.2
Dimensions (L x W x H)	mm	560 × 500 × 1090
Cleaning agent function		6 I tank
Number of simultaneous users		1/2
Portability		cart

Equipment				
Spray gun		EASY!Force Advanced	Oil level indicator	
Spray gun with soft grip padding			Servo control	
High-pressure hose	m	10	Brass water inlet	
Spray lance	mm	1050		
Power nozzle				
Dirt Blaster				
ANTI!Twist				
4-pole, three-phase motor with air and water cooling		•		
Pressure switch-off				
Large water fine filter				
Electronic motor protection with LED display		•		

■ Included in the scope of supply.

















		Order no.	Flow rate		Price	Description
Spray guns						
EASY!Force Advanced	1	4.118-005.0				Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0				For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!Force high-pressure gun, spray lance and all adapters through to the nozzle.
EASY!Force conversion kit 2 - from machine	3	4.111-051.0				Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0				Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.
Servo control						
Servo Control	5	4.118-009.0	1100 l/h			Water quantity and pressure regulated directly from the hand spray gun.
Quick connect						
Quick coupling	6	2.115-000.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Male coupling	7	2.115-001.0				Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

[■] Included in the scope of supply.

Available accessories.































		1					_
	Order no.	Max. working pressure	Length		Price	Description	
						'	
1	4.112-000.0	300 bar	1050 mm			1050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° I under pressure.	•
2	2.680-002.0					Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in unfavourable lighting conditions for up to 5 working hours.	
3	4.112-027.0	300 bar	250 mm			Spray lance, 250 mm, rotatable, ergonomic	
4	4.112-024.0	300 bar	400 mm			Spray lance, 400 mm, rotatable, ergonomic	
5	4.112-007.0	300 bar	600 mm			under pressure.	
6		300 bar	840 mm			nomic handle for ease of use and protection. Rotatable 360° l under pressure.	
7	4.112-018.0	300 bar	1550 mm			1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° l under pressure.	
8	4.112-021.0	300 bar	2050 mm			nomic handle for ease of use and protection. Rotatable 360° l under pressure.	
9	4.112-048.0	300 bar	1000 mm			Spray lance extension with EASY!Lock connection. Length 1000 mm.	
		,	1				
10	2.112-016.0	310 bar	960 mm			960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (le.g. stable cleaning).	
			1				
11	4.112-029.0						
		1	ı				
			1050 mm			140°, ideal for cleaning difficult to reach areas, e.g. gutters.	
13	4.112-057.0	300 bar					
14	2.112-015.0		960 mm			The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter and be cleaned without removing the cover plates.	
		1	1				
15	4.112-032.0		700 mm			Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.	
			1			,	
16	4.321-380.0					Comfortable in every situation – the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working for greater flexibility.	
	2 3 4 5 6 7 8 9 10 11 12 13 14	1 4.112-000.0 2 2.680-002.0 3 4.112-027.0 4 4.112-024.0 5 4.112-006.0 7 4.112-018.0 8 4.112-021.0 9 4.112-048.0 10 2.112-016.0 11 4.112-029.0 12 4.112-035.0 13 4.112-057.0 14 2.112-015.0	Order no. pressure 1 4.112-000.0 300 bar 2 2.680-002.0 300 bar 3 4.112-027.0 300 bar 4 4.112-024.0 300 bar 5 4.112-007.0 300 bar 6 4.112-018.0 300 bar 7 4.112-018.0 300 bar 8 4.112-021.0 300 bar 9 4.112-048.0 300 bar 10 2.112-016.0 310 bar 11 4.112-029.0 12 4.112-035.0 210 bar 13 4.112-057.0 300 bar 14 2.112-015.0 15 4.112-032.0	Order no. pressure Length 1 4.112-000.0 300 bar 1050 mm 2 2.680-002.0 250 mm 3 4.112-027.0 300 bar 250 mm 4 4.112-024.0 300 bar 400 mm 5 4.112-007.0 300 bar 600 mm 6 4.112-018.0 300 bar 1550 mm 8 4.112-021.0 300 bar 2050 mm 9 4.112-048.0 300 bar 1000 mm 10 2.112-016.0 310 bar 960 mm 11 4.112-029.0 1050 mm 12 4.112-035.0 210 bar 1050 mm 13 4.112-015.0 960 mm 14 2.112-015.0 960 mm	Order no. pressure Length 1 4.112-000.0 300 bar 1050 mm 2 2.680-002.0 250 mm 3 4.112-027.0 300 bar 250 mm 4 4.112-024.0 300 bar 400 mm 5 4.112-007.0 300 bar 600 mm 6 4.112-018.0 300 bar 1550 mm 8 4.112-021.0 300 bar 2050 mm 9 4.112-048.0 300 bar 1000 mm 10 2.112-016.0 310 bar 960 mm 11 4.112-029.0 1050 mm 12 4.112-035.0 210 bar 1050 mm 13 4.112-057.0 300 bar 960 mm 14 2.112-015.0 960 mm 700 mm	Order no. pressure Length Price 1 4.112-000.0 300 bar 1050 mm 1050 mm 2 2.680-002.0 300 bar 250 mm 250 mm 4 4.112-024.0 300 bar 400 mm 400 mm 5 4.112-007.0 300 bar 600 mm 600 mm 7 4.112-018.0 300 bar 1550 mm 1550 mm 8 4.112-021.0 300 bar 2050 mm 2050 mm 9 4.112-048.0 300 bar 1000 mm 1000 mm 10 2.112-016.0 310 bar 960 mm 11 11 4.112-035.0 210 bar 1050 mm 1050 mm 12 4.112-057.0 300 bar 1050 mm 1050 mm 14 2.112-015.0 960 mm 1050 mm	Order no. Dressure Length Price Description

[■] Included in the scope of supply.

□ Available accessories.





			Max. working					
		Order no.	pressure	Nozzle size		Price	Description	
Dirt blaster, large								
Dirt blaster	1	4.114-044.0	300 bar	120			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

[■] Included in the scope of supply.

Available accessories.





		Order no.	Nozzle size		Price	Description
Power nozzle spray angle 25°						
Power nozzle	1	2.113-060.0	115			Fan jet nozzle for large-area coverage and stubborn dirt and
						stains.

[■] Included in the scope of supply.

□ Available accessories.









Standard with unions on both side		Order no.	ID	Max. working pressure	Length	Price	Description	
High-pressure hose	1	6.110-041.0	DN 10	220 bar	10 m		Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	•
	2	6.110-042.0	DN 10	220 bar	15 m		Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10).	
	3	6.110-043.0	DN 10	220 bar	20 m		20 m in length and the extremely time-saving and comfortable EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
	4	6.110-044.0	DN 10	220 bar	25 m		Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
	5	6.110-045.0	DN 10	220 bar	40 m		40 m long high-pressure hose with EASY!Lock system for the time-saving manual screw connection (both sides). Nominal size (DN) 10, working pressure up to 220 bar.	
	6	6.110-059.0	DN 12	210 bar	15 m		Designed for working pressures up to 250 bar: High-pressure hose (DN 12) with a length of 15 m. Has the comfortable EASY!Lock manual screw fitting on both sides.	
	7	6.110-060.0	DN 12	210 bar	40 m		With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	

[■] Included in the scope of supply.

Available accessories.































			1	1	1		T	$\overline{}$
		Order no.				Price	Description	⊥
Nozzle union			ı					
Nozzle screws	1	4.112-011.0					Nozzle screws with protectors for high-pressure and power nozzles	r c
Cleaning agent injector							11022165	+
Dosing valve for stainless steel	2	6.500-000.0					Retrofittable dosing valve for stainless steel injectors. For	
injector							easy, convenient and precise cleaning agent dosing adjustment via a control knob.	
Cleaning agent injector for high	3	4.637-032.0					Detergent injector for independent high and low pressure	
and low pressure (without nozzles)							dosage. Maximum dosage about 15%.	┵
Cleaning agent injector for high pressure (without nozzle)	4	4.637-033.0					Cleaning agent dosage at high pressure 3 - 5 %	
Nozzle insert with order no. 4.637-	032.0							+
Nozzle insert from 1,100 l/h - HD	5	4.769-002.0					For high pressure with machines above 1.100 l/h	10
Nozzle insert from 1,100 l/h - ND	6	4.769-006.0					For low pressure with machines above 1.100 l/h	
Rotary coupling								
Rotary coupling	7	4.111-021.0					Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector								
Screw socket for surface cleaners and Servo Control controllers	8	4.111-022.0					For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - 1 x M 22 x 1.5/1 M 18 x 1.5.	
Y distributor	9	4.111-024.0					Offers the option to connect two spray units to the machine Installation on the high pressure outlet.	e. [
Short spray unit	10	4.111-038.0					For attaching high-pressure nozzles and accessory parts to HP trigger gun (with nozzle screws). Not compatible with triple nozzles.	
EASY!Lock adapter			I.	'				
Adapter 1 M22AG-TR22AG	11	4.111-029.0					Adapter 1 to connect the old hose with the new hose	[
Adapter 2 M22IG-TR22AG	12	4.111-030.0					Adapter 2 to connect the old device with the new hose and the old gun with the new hose	
Adapter 3 M22IG-TR22AG	13	4.111-031.0					Adapter 3 to connect the old gun with the new spray lance and new servo regulator	
Adapter 4 TR22IG-D11	14	4.111-032.0					Adapter 4 to connect the new gun with the old swivel hose	. [
Adapter 5 TR22IG-M22AG	15	4.111-033.0					Adapter 5 to connect the new gun with the old spray lance and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	16	4.111-034.0					Adapter 6 to connect the new device with the old hose and the old hose with the new gun	1 [
Adapter 7 M18IG-TR20AG	17	4.111-035.0					Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	18	4.111-036.0					Adapter 8 to connect the new spray lance with the old nozzle	[
Adapter hose extension 9 TR	19	4.111-037.0					Adapter 9 to connect the new hose with the new hose	[
Adapter 12 rotary coupling EASY!Lock 22 IG - M22 x 1.8 AG	20	4.111-046.0					Rotatable adapter for connecting EASY!Force high-pressure gun and high-pressure hoses with M 22x1.5 connection	; [

[■] Included in the scope of supply.

Available accessories.



















		1		T	1		I	_
			Max. working		Diame-			
		Order no.	pressure	Nozzle size	ter	Price	Description	
Pipe cleaning hose, ID 6		<u>'</u>	·					
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	2	6.110-008.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pressure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle			_					
Pipe cleaning dirt blaster D21/060	4	4.765-002.0		60	21 mm		The forward-tilted rotating pencil jet removes the most	
Pipe cleaning dirt blaster D30/060	5	4.765-005.0		60	30 mm		stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient handling.	
Pipe cleaning nozzle 120	6	5.763-089.0		120	24 mm		Pipe cleaning nozzle with 24 mm diameter. With 8 nozzles tilted back at a 30° angle.	
Pipe cleaning nozzle	7	5.763-019.0		65	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	
	8	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	9	5.763-021.0		70	30 mm		30 mm pipe cleaning nozzle with internal thread. Various jet directions for environmentally-friendly cleaning of blocked drains and pipes.	1
Rotating pipe cleaning nozzle	10	6.415-440.0		65	16 mm		Rotating pipe cleaning nozzle with internal thread and four rotating jets for environmentally-friendly cleaning of blocked drains and pipes.	
Drum and tank cleaning			,					
Add-on kit mud sucker	11	2.641-798.0					For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	
HKF 50 spray head, brass				1				
HKF 50 M spray head	12	3.631-039.0					Constant rotational speed and lightweight design: The compact interior cleaning head for cleaning vats and tanks with openings of 50 mm or wider.	
	13	3.631-058.0					Compact interior cleaning head for cleaning containers with openings of 50 millimetres or wider. The device stands out from the crowd with its constant rotational speed and lightweight design.	

[■] Included in the scope of supply.

Available accessories.

















		Order no.	Flow rate	Nozzle size	Diame- ter	Price	Description
FR 30 Me surface cleaner							
Hard Surface Cleaner FR 30 Me	1	2.111-013.0			300 mm		Hot water resistant stainless steel surface cleaner with double ceramic bearings, non-marking swivel castors and suction hose connection. Ideal for indoor cleaning, e.g. food industry.
Hard Surface Cleaner FR 50							
Surface Cleaner FR 50 Me	2	2.111-023.0			500 mm		Hot water resistant stainless steel surface cleaner with 500 mm working width. Ideal for large areas.With double ceramic bearings, push handle, non-marking swivel castors and detergent dosing system.
Machine-specific nozzle kits for FR							
Nozzle kit for FR	3	2.640-781.0	1300 - 1800 l/h				Machine-specific nozzle kit Kärcher power nozzle for hard surface cleaners
Machine-specific nozzle kits for FR	V						
Nozzle kit for FRV	4	2.643-769.0		100			Machine-specific nozzle kit Kärcher power nozzles and jet nozzle for FRV 30 and FRV 50.
FRV 30 Me surface cleaner							
Extension hose FRV 30 Me and FRV 50 Me	5	4.441-040.0					$\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ $
FRV 30 Me Surface Cleaner	6	2.111-012.0					Thanks to automatic suction of the dirty water, the stainless steel FRV 30 Me Surface Cleaner makes surface cleaning more efficient in both inside and outside areas. Hot water cleaning up to 85°C.
Surface Cleaner FR 50 Me							
FRV 50 Me surface cleaner	7	2.111-024.0					Surface cleaning with automatic suction of the dirty water for very large surfaces - this means the FRV 50 Me. Hot water cleaning up to 85°C. The FRV 50 Me features a temperature-resistant 10 m polyurethane suction hose. Additional quality features are the non-marking steering rollers and double ceramic bearing. Machine-specific nozzle kit must be ordered separately. Max. 250 bar / 2000 l/h / 85°C.

[■] Included in the scope of supply.

□ Available accessories.





















		Order no.	Flow rate		Price	Description
Cup foam lance						
Cup foam lance Basic 3	1	4.112-055.0	900 - 2500 l/h			High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900–2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality.
1-litre cleaning agent container for cup foam lance basic	2	5.071-414.0				For the quick change of the cleaning agent: Additional 1 litre cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).
Cup foam lance Advanced	3	2.112-018.0				Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.
1-litre cleaning agent container for cup foam lance advanced	4	6.414-050.0				Additional 1-litre cleaning agent container for quick replacement of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).
Cup foam lance Advanced 3	5	4.112-065.0	900 - 2500 l/h			Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kärcher.
Cup foam lance DUO Advanced 3	6	4.112-069.0	900 - 2500 l/h			DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pressure cleaning, spraying angle adjustment and two-litre tank.
Inno Foam Kit						
Inno Foam Set with detergent injector	7	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.
Easy Foam Set						
Easy Foam Set with RM injector	8	2.112-010.0				HP foam system for use with. HD/HDS units for cleaning and disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.
Foam nozzle mounting kit		1				
Foam nozzle attachment kit	9	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sanitary areas and the food industry and wherever long application times are necessary.

[■] Included in the scope of supply.

Available accessories.



















		Order no.	Length		Price	Description	
Manual hose reel attachment kit							
Hose reel attachment kit for HD super class	1	2.110-008.0	20 m			Hose reel attachment kit for installation on the machine. For secure and space-saving storage of the high-pressure hose (with a connection hose for the machine HP output). Rotatable under pressure with connection 22 x 1.5.	П
Automatic, self-winding hose reels	for wa	III mounting					
Automatic plastic hose reel incl. high-pressure hose	2	2.639-257.0	15 m			Spring-mounted and ready-to-use automatic hose reel for wall mounting. Simplifies handling of the high-pressure hose, shortens set-up times and increases occupational safety.	
Automatic hose reel, powder-coated steel / plastic	3	6.392-074.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console is made from powder-coated steel, the drum is made from plastic.	
Automatic stainless steel / syn- thetic material hose drum	4	6.392-083.0	20 m			Automatic hose reel for 20 m high-pressure hose. The console consists of stainless steel, the drum is made from plastic.	
Automatic hose reel, coated	5	6.392-106.0	20 m			Automatic hose reel of durable plastic. Painted steel bracket Suitable for 20 m high-pressure hose.	
Hose reel, automatic, basalt grey-coated	6	6.392-105.0	20 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. For example: order no. 6.110-011.0 (ID 8, 20 m, 315 bar) or order no. 6.110-028.0 (ID 8, 20 m, 400 bar Longlife).	П
Automatic hose reel, stainless steel, includes swivel holder	7	6.392-076.0	20 m			Automatic stainless steel hose reel. With swivel holder. Suitable for 20 m high-pressure hose.	
Automatic stainless steel hose reel	8	6.392-442.0	40 m			Automatic hose reels provide the highest level of safety and convenience for winding and unwinding HP hoses. Compatible high-pressure hose, e.g. order no. 6.110-076.0 (ID 8, 40 m, 400 bar, 1x hose reel connection attachment kit).	
Powder-coated swivel holder	9	2.639-931.0				Swivel holder for automatic hose reel wall mounting. For maximum action radius and flexibility of high-pressure hose Rotatable 120°. Galvanised steel.	. 🗆
Stainless steel swivel holder	10	2.641-867.0				Swivelling wall bracket made of high-grade steel (for 2.641- 866). This makes maximum flexibility and convenience possible when working with the HP hose.	

[■] Included in the scope of supply.

□ Available accessories.



		Order no.	Flow rate	Length of the product	Length	Price	De- scrip- tion		
Telescopic lances	Telescopic lances								

[■] Included in the scope of supply.

□ Available accessories.

















		Order no.	Nozzle size		Price	Description
Nozzle kits for wet jet unit						
Nozzle kit for wet jet unit 100	1	2.112-030.0	100			Consisting of wet jet nozzle and nozzle insert - only for use
						in combination with wet jet unit 4.115-000.0 4.115-006.0.
Boron carbide nozzle						
Boron carbide, for machines from	2	6.415-083.0	8 mm			In addition to nozzle packs. Very wear-resistant nozzle with
1,000 l/h						boron carbide chuck for continuous-duty operation.

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.





















		Order no.				Price	Description	
Geka coupling		·			 			
Geka connector with hose barb, R 1"	1	6.388-465.0					with hose barb	
Geka connector with internal thread, R 1"	2	6.388-458.0					with female thread	
Suction filter								
Water suction filter	3	6.414-956.0					Suitable for ponds, storage tanks or similar, polyamide filte casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve	
Suction filter with check valve	4	4.730-012.0					Brass suction filter suitable for ponds, storage tanks, etc. With check valve.	
Water fine filter								
Universal water fine filter, 25 μm	5	2.637-020.0					Water fine filter, mesh size 25 µm, max. temperature 50 °C. Protects the machine from small dirt particles in the water. Water volume up to 1200 l/h. 3/4" connection, with 1" adapter.	
Water fine filter, with adapter	6	4.730-102.0					Fine-mesh water filter, 125 µm, max. temperature 50°C. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1".	;- C
Water fine filter, 100 µm, R 1"	7	2.638-270.0					Fine-mesh water filter, 100 µm, max. temperature 60°C. Connects to high-pressure cleaner. Protects the high-pressure cleaner from dirt particles contained in the water. Water flow rate up to 1200 l/h. Connector 1".	
Water supply hose				,				
Water supply hose	8	4.440-207.0					NW 19 R1" / R 3/4", up to 85 °C, for pick-up	
	9	4.440-270.0					NW 19 R1" / R1", up to 85 °C	
Backflow check valve	٠	l · · · · -	1	1		1	I=	
Backflow preventer	10	2.641-374.0					To prevent detergent getting into the drinking water cycle i case of inlet at low-pressure hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakag protection	۱
Other HP Accessories								
Jet gun	11	2.869-067.0					Short set-up time, easy transport, instant switch off - the je gun is the affordable cleaning method for all kinds of small to medium-sized areas. Adjustable pressure/water volume.	

[■] Included in the scope of supply.

Available accessories.









		Order no.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.113-001.0				For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 x 1.5 $\hfill\Box$
Rotating washing brush						
Rotating wash brush for > 800 l/h machines, nylon bristles	2	4.113-002.0	800 - 1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to
Rotating wash brush for > 800 l/h machines, natural bristles	3	4.113-005.0	800 - 1300 l/h			60°C, M 18 x 1.5 (replaceable brush insert).

 $[\]blacksquare$ Included in the scope of supply. \qed Available accessories.