



HDS 1000 De Weed

HDS 1000 De Weed hot water high-pressure cleaner for consistently high temperatures of up to 98 $^{\circ}$ C – ideal for mobile weed removal and a demonstrable reduction of viruses on surfaces.









1 Maximum performance

- High-output burner with upright heating coil and detonation-free continuous ignition.
- Automatic burner cut-out in case of water shortage and overheating.

2 Economical, diesel-powered combustion engine

- Complies with the requirements of exhaust emissions standard EU STAGE V.
- Electro start for effortless starting.



3 User-friendly operation

- The speed is automatically reduced in standby mode. This protects the engine and saves energy.
- Crane loading possible thanks to the sturdy tubular steel frame.

TECHNICAL DATA AND EQUIPMENT

KARCHER



HDS 1000 De Weed

Independent high-pressure cleaning irrespective of external power

sources

- Economical diesel engine with convenient electro start
- Professional high-performance hot water machine

Technical data		
Order no.		1.811-947.0
EAN code		4054278772493
Pressure	bar / MPa	40 - 200 / 4 - 20
Flow rate	l/h	450 - 900
Temperature (for supply 12 °C)	°C	max. 98
Consumption of heating oil or gas at full load	kg/h	5.6
Drive type		Diesel
Motor manufacturer		Yanmar
Motor type		L 100 V
Engine rating	kW / hp	6.8 / 9.3
Number of simultaneous users		1
Portability		cart
Weight	kg	199.16

Equipment		
Spray gun		EASY!Force Advanced
High-pressure hose	m	15 / Premium quality / ID 8, 315 bar
Spray lance	mm	1050
Cage protective frame		1
Anti-twist system		-
Electro start		1
Power nozzle		1
Servo control		1
Sturdy tubular steel frame for crane loading		•

Included in the scope of supply.

KARCHER



		Order no.	Flow rate		Price	Description
Spray guns			1 1	1		
EASY!Force Advanced	1	4.118-005.0				Effortless, not energy-sapping: the EASY!Force high-pres- sure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero.
EASY!Force conversion kit 1 - from high-pressure hose	2	4.111-050.0				For retrofitting Kärcher high-pressure cleaners with existing high-pressure hose: EASY!Force conversion kit 1 with EASY!- Force high-pressure gun, spray lance and all adapters through to the nozzle.
EASY!Force conversion kit 2 - from machine	3	4.111-051.0				Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters.
EASY!Force conversion kit 3 - high-pressure gun	4	4.111-052.0				Compatible with existing high-pressure hose and spray lance: EASY!Force conversion kit 3, incl. EASY!Force trigger gun and all necessary adapters for upgrading your high-pressure cleaner.
Servo control						
Servo Control	5	4.118-008.0	750 - 1100 l/h			Water quantity and pressure regulated directly from the hand spray gun.
Quick connect						
Quick coupling	6	2.115-000.0				For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread.
Male coupling	7	2.115-001.0				Hardened stainless steel male coupling for quick coupling 2.115-000. With M 22 x 1.5 external thread.

		3			 5	
		Order no.	Max. working pressure	Length	Price	Description
Rotating spray lances Spray lance	1	4.112-000.0	300 bar	1050 mm		1050 mm stainless steel lance (manual coupling) with ergo-
Spray lance		4.112 000.0	500 bui	1050 1111		nomic handle for ease of use and protection. Rotatable 360° under pressure.
LED nozzle light	2	2.680-002.0				Bright, lightweight LED work light for direct mounting on spray lance of EASY!Force high-pressure gun. Better view in [unfavourable lighting conditions for up to 5 working hours.
Spray lance	3	4.112-027.0	300 bar	250 mm		Spray lance, 250 mm, rotatable, ergonomic
	5	4.112-024.0 4.112-007.0	300 bar 300 bar	400 mm 600 mm		Spray lance, 400 mm, rotatable, ergonomic [600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° [under pressure. [
	6	4.112-006.0	300 bar	840 mm		850 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° [under pressure.
	7	4.112-018.0	300 bar	1550 mm		1550 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° [under pressure.
	8	4.112-021.0	300 bar	2050 mm		2050 mm stainless steel lance (manual coupling) with ergo- nomic handle for ease of use and protection. Rotatable 360° [under pressure.
Spray lance extender	9	4.112-048.0	300 bar	1000 mm		Spray lance extension with EASY!Lock connection. Length 1000 mm.
Double lance Double lance	10	2.112-016.0	310 bar	960 mm		960 mm double lance for variable pressure adjustment on handle at full water flow rate. Suitable for agricultural use (e.g. stable cleaning).
Angular spray lance Spray lance for toilets and rain gutters	11	4.112-029.0				Stainless steel lance WC and gutter with nozzle insert. Spe- cially shaped for effective and hygienic cleaning of gutters and toilets.
Flexible spray lance Flexible lance	12	4.112-035.0	210 bar	1050 mm		1050 mm flexible lance with variable bend from 20° to
High pressure articulated joint	13	4.112-057.0	300 bar			140°, ideal for cleaning difficult to reach areas, e.g. gutters. For hard-to-reach areas: High-pressure articulated joint with infinite angle adjustment up to 120°. Simply attach directly to the spray lance of the pressure washer.
Gutter cleaner Gutter cleaning lance	14	2.112-015.0		960 mm		The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates.
Undercarriage spray lance Underbody lance	15	4.112-032.0		700 mm		Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle.
Additional handle Additional handle for EASY!Lock spray lances	16	4.321-380.0				Comfortable in every situation - the additional handle is easy to attach to the spray lance of our new EASY!Lock generation and makes work easier by allowing you to adjust your posture to suit the particular task. Regularly changing your posture relieves the strain on your body, making work more relaxed. Thanks to the 360°-rotatable spray lance, the additional handle can simply be fully rotated whilst working

■ Included in the scope of supply. □ Available accessories.

additional handle can simply be fully rotated whilst working

for greater flexibility.



		Order no.	Nozzle size		Price	Description
Power nozzle spray angle 25	,°					
Power nozzle	1	2.113-063.0	33			Fan jet nozzle for large-area coverage and stubborn dirt and stains.
	2	2.113-023.0	50			Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains.
HP nozzle spray angle 0°						
Power nozzle	3	2.113-034.0	50			High-pressure nozzle with powerful jet for extremely stub- born dirt.
Power nozzle spray angle 15	i°					
Power nozzle	4	2.113-047.0	55			Fan jet nozzle with 15° spray angle suitable for stubborn dirt. $\hfill \square$
Power nozzle spray angle 40)°					
Power nozzle	5	2.113-054.0	50			Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. $\hfill \square$

KARCHER





		Order no.	ID	Max. working pressure	Length	Price	Description	
Standard with unions on both sid High-pressure hose		6.110-030.0	DN 8	315 bar	15 m		15 m long high-pressure hose, DN 8, with ANTI!Twist and time-saving EASY!Lock manual screw fitting on both sides.	
	2	6.110-031.0	DN 8	315 bar	10 m		High-pressure hose (DN 8) suitable up to 315 bar pressure. With innovative EASY!Lock manual screw fitting on both sides, ANTI!Twist and 10 m long.	
	3	6.110-032.0	DN 8	315 bar	20 m		20 m long high-pressure hose (DN 8) equipped with the time-saving and robust EASY!Lock manual screw fitting on both sides. Approved for pressures up to 315 bar.	
	4	6.110-014.0	DN 8	315 bar	30 m		Comfortable length (30 m) and innovative EASY!Lock manu- al screw fitting: High-pressure hose (DN 8) with ANTI!Twist for pressures up to 315 bar.	
	5	6.110-042.0	DN 10	220 bar	15 m		Equipped with innovative EASY!Lock manual screw fitting and suitable for pressures up to 220 bar: 15 m long high-pressure hose (DN 10).	
	6	6.110-043.0	DN 10	220 bar	20 m		20 m in length and the extremely time-saving and comforta ble EASY!Lock manual screw fitting on both sides are some of the main features of this high-pressure hose (DN 10).	
	7	6.110-044.0	DN 10	220 bar	25 m		Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
	8	6.110-059.0	DN 12	210 bar	15 m		Designed for working pressures up to 250 bar: High-pres- sure hose (DN 12) with a length of 15 m. Has the comforta- ble EASY!Lock manual screw fitting on both sides.	
	9	6.110-060.0	DN 12	210 bar	40 m		With EASY!Lock manual screw fitting and lots of room for manoeuvre thanks to 40 m in length: High-pressure hose (DN 12) with EASY!Lock manual screw fitting on both sides. Suitable for working pressures up to 250 bar.	
	10	6.110-041.0	DN 10	220 bar	10 m		Impressive values and basic equipment: 25 m long high-pressure hose (DN 10) developed for pressures up to 220 bar.	
onglife 400 with unions on both	sides							
High-pressure hose Longlife	11	6.110-024.0	DN 8	400 bar	1.5 m		 1.5 m short high-pressure hose (DN 8). Comfortable EASY!Lock manual screw fitting on both sides for robust and quick connections. Durable and designed for up to 400 bar pressure. 	d
	12	6.110-069.0	DN 8	400 bar	1.5 m		 1.5 m long high-pressure hose (DN 8) suitable for up to 400 bar pressure with double steel core. Connections: M 22 × 1.5, as well as the comfortable and quick EASY!Lock manual screw fitting. 	
	13	6.110-038.0	DN 8	400 bar	10 m		Durable, 10 m long high-pressure hose (DN 8) with double steel core and EASY!Lock manual screw fitting on both side: and ANTI!Twist. Approved for 400 bar pressure.	5
	14	6.110-023.0	DN 8	400 bar	30 m		Robust high-pressure hose with double steel core, AN- TI!Twist and EASY!Lock manual screw fitting on both sides. Nominal size DN 8, 30 m long, for up to 400 bar pressure.	-
	15	6.110-027.0	DN 8	400 bar	20 m		High-pressure hose with ANTI!Twist, EASY!Lock manual screw fittings and double steel core. 20 m long, nominal size DN 8, EASY!Lock manual screw fitting on both sides.	9
	16	6.110-029.0	DN 8	400 bar	15 m		The double steel core ensures a particularly long life of this 15 m long high-pressure hose (DN 8), which is approved for pressures up to 400 bar.	

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories.

KARCHER

HDS 1000 DE WEED 1.811-947.0



		Order no.	ID	Max. working pressure	Length	Price	Description	
Longlife food design with screw co	nnecti	ons at both ends						
High-pressure hose food grade Longlife	17	6.110-053.0	DN 8	400 bar	10 m		With blue, non-marking and animal fat resistant outer cov- ering: durable high-pressure hose (ID 8), 10 m long, AN- TI!Twist and EASY!Lock hand screw connection at both ends.	
Special hoses								
High-pressure hose curved	18	6.110-068.0	DN 8	400 bar	1.5 m		For connection to hose reels: high-pressure hose, with M 22 × 1.5 connection and curved EASY!Lock hand screw connec- tion. 1.5 m long, suitable for up to 400 bar working pres- sure.	



		Order no.		Price	Description	
Weed control						
WR 50	1	2.114-013.0			In combination with a hot water high-pressure cleaner from Kärcher, the 50 cm wide weed remover WR 50 is ideal for removing weeds. It comes with an adaptive chassis and nozzle adapter.	
WR 20	2	2.114-014.0			For thorough weed removal: The WR 20 weed remover for use with a hot water high-pressure cleaner from Kärcher. Equipped with a 20 cm wide nozzle bar and nozzle adapter.	
WR 100	3	2.114-015.0			Comfortable and fast weed removal: WR 100 weed remover with chassis, 100 cm wide nozzle bar and integrated nozzle adapter for use with hot water high-pressure cleaners.	
WR 10	4	2.114-016.0			In combination with hot water high-pressure cleaners our WR 10 weed remover enables fast and thorough weed removal. With 10 cm spray head and nozzle adapter.	



		Order no.	Max. working pressure	Nozzle size		Price	Description	
Dirt blaster, large								
Dirt blaster	1	4.114-027.0	300 bar	50			The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C.	

KARCHER

2 2 9 10		3		4		5		$ \begin{array}{c} $	
		Order no.					Price	Description	
Nozzle union									
Nozzle screws	1	4.112-011.0						Nozzle screws with protectors for high-pressure and power nozzles	
Cleaning agent injector									
Cleaning agent injector for high	2	4.637-032.0						Detergent injector for independent high and low pressure	
and low pressure (without nozzles) Cleaning agent injector for high	3	4.637-033.0						dosage. Maximum dosage about 15%.	_
pressure (without nozzle)		4.007 000.0							
Machine-specific nozzle kit with or		1 1			1 1		1		
Nozzle kit 750-1000 l/h Nozzle kit 750-1000 l/h	4								
Nozzle insert with order no. 4.637-		4.769-047.0					<u> </u>		믝
Nozzle insert up to 1,100 l/h - high pressure	6	4.769-003.0						Nozzle insert for detergent injector 3.637-001 for high-pressure detergent application. For high-pressure cleaners with a water flow rate up to 1100 l/h.	
Nozzle insert up to 1,100 l/h - low	7	4.769-001.0						For low pressure with machines up to 1.100 l/h	
pressure Rotary coupling					<u> </u>			<u> </u>	
Rotary coupling	8	4.111-021.0						Reliably prevents twisting of HP hoses. Connection Easy!Lock. Handle protection	
Connector									
Screw socket for surface cleaners and Servo Control controllers	9							For attaching high-pressure nozzles and accessory parts to the HD trigger gun (with nozzle screws) - $1 \times M 22 \times 1.5/1 \times M 18 \times 1.5$.	
Y distributor	10	4.111-024.0						Offers the option to connect two spray units to the machine. Installation on the high pressure outlet.	
Short spray unit	11	4.111-038.0						For attaching high-pressure nozzles and accessory parts to	
EASY!Lock adapter	12	4 111 030 0	1					Adapter 1 to connect the old base with the serve base	
Adapter 1 M22AG-TR22AG Adapter 2 M22IG-TR22AG	12	4.111-029.0 4.111-030.0						Adapter 2 to connect the old device with the new bece and	
Adapter 3 M22IG-TR22AG	14	4.111-031.0						Adapter 2 to connect the old gup with the new spray lance	
Adapter 4 TR22IG-D11	15	4.111-032.0							
Adapter 5 TR22IG-M22AG	16	4.111-033.0						and new servo regulator with the old spray lance	
Adapter 6 TR22IG-M22AG	17	4.111-034.0						the old hose with the new gun	
Adapter 7 M18IG-TR20AG	18	4.111-035.0						Adapter 7 to connect the old spray lance with the new nozzle	
Adapter 8 TR20IG-M18AG	19	4.111-036.0						Adapter 8 to connect the new spray lance with the old nozzle	
Adapter hose extension 9 TR		4 4 4 4 0 2 7 0				-		A deaters O to account the second base with the second base	
Adapter 12 rotary coupling	20 21							Adapter 9 to connect the new hose with the new hose Rotatable adapter for connecting EASY!Force high-pressure	븨

 EASY!Lock 22 IG - M22 x 1.8 AG

 Included in the scope of supply.

KARCHER



		Order no.	Max. working pressure	Nozzle size	Diame- ter	Price	Description	
Pipe cleaning hose, ID 6							1	-
Pipe cleaning hose, ID 6, 10 m, max. 250 bar	1	6.110-046.0	250 bar				The 10 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 20 m, max. 250 bar	2	6.110-008.0	250 bar				The 20 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning hose, ID 6, 30 m, max. 250 bar	3	6.110-047.0	250 bar				The 30 m pipe cleaning hose is a highly flexible high pres- sure hose for pipe interior cleaning (threaded connection for nozzle R 1/8).	
Pipe cleaning nozzle								
Pipe cleaning dirt blaster D21/060	4	4.765-002.0		60	21 mm		The forward-tilted rotating pencil jet removes the most	Ľ
Pipe cleaning dirt blaster D30/060	5	4.765-005.0		60	30 mm		stubborn dirt. The three backwards-tilted jets ensure the necessary forward movement, as well as convenient han- dling.	
Pipe cleaning nozzle	6	5.763-015.0		55	16 mm		16 mm pipe cleaning nozzle with internal thread. Various jet	Ε
	7	5.763-016.0		60	16 mm		directions for environmentally-friendly cleaning of blocked drains and pipes.	
	8	5.763-017.0		50	30 mm		Pipe cleaning nozzle with inner thread. Different spray directions. The hose moves freely through the pipe. (R $1/8"$ connection, 3 x 30° backwards, diameter 30 mm.)	
Rotating pipe cleaning nozzle	9	6.415-428.0		50	16 mm		Pipe cleaning nozzle with four rotating jets and inner thread. Different spray directions. The hose moves freely through the pipe. With R 1/8" connection.	
Drum and tank cleaning								
Add-on kit mud sucker	10	2.641-798.0					For connection to the high-pressure hose of Kärcher high-pressure cleaners: Powerful sludge suction cleaner for the retrofitting of high-pressure cleaners to dirt pumps.	

KÄRCHER



 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories.

KARCHER



8





6





0











		Order no.	Flow rate		Price	Description	
Cup foam lance				<u> </u>		1	
Cup foam lance Basic 3	1	4.112-055.0	900 - 2500 l/h			High-quality, simple and durable: Basic 3 cup foam lance for high-pressure cleaners with a flow rate of 900-2500 l/h. Halves the cleaning agent consumption while maintaining optimum foam quality.	
1-litre cleaning agent container for cup foam lance basic	2	5.071-414.0				For the quick change of the cleaning agent: Additional 1 litric cleaning agent container for basic foam lance (2.112-053.0, 2.112-054.0 and 2.112-055.0).	
Cup foam lance Advanced	3	2.112-017.0	max. 1300 l/h			Short, handy foam lance with adjustable spray angle with 1 litre detergent tank. Ideal for cleaning cars due to its compact design.	
1-litre cleaning agent container for cup foam lance advanced	4	6.414-050.0				Additional 1-litre cleaning agent container for quick replace ment of the cleaning agent (for foam lance 2.112-017.0 and 2.112-018.0).	
Cup foam lance Advanced 3	5	4.112-065.0	900 - 2500 l/h			Specially designed for use with aggressive cleaning agents: High-quality cup foam lance Advanced 3 with spray angle adjustment and Ecobrass for high-pressure cleaners from Kårcher.	
Cup foam lance DUO Advanced 3	6	4.112-069.0	900 - 2500 l/h			DUO Advanced 3 cup foam lance, designed for use with aggressive detergents. With instant switching to high-pres- sure cleaning, spraying angle adjustment and two-litre tank.	
Inno Foam Kit							
Inno Foam Set with detergent injector	7	2.112-000.0				High-pressure foam system with double lance (foam nozzle and high-pressure jet for rinsing). For use with mobile and	
Inno Foam Set	8	2.112-008.0				stationary high-pressure and HDS pressure cleaners for cleaning or disinfection.	
Easy Foam Set							
Easy Foam Set with RM injector	9			 	 	HP foam system for use with. HD/HDS units for cleaning and	d 🗆
Easy Foam Set	10	2.112-011.0				disinfecting. Foam nozzle for connection to lance and HP chemical injector with precision 0-5% metering valve. The machine specific nozzle kit has to be ordered separately.	
Nozzle kits for Inno/Easy Foam Set				-		· · ·	
Nozzle kit 090 for Inno / Easy Set 700-1,000 l/h	11	2.111-019.0	700 - 1000 l/h			Nozzle kit contains Kärcher power nozzles and nozzle in- serts. For Inno/Easy-Foam set 700-1000 I/h. For optimal foam system performance.	
Foam nozzle mounting kit							
Foam nozzle attachment kit	12	2.112-013.0				Foaming agent kit. The foam nozzle is ideal for use in sani- tary areas and the food industry and wherever long applica tion times are necessary.	


KÄRCHER



Length of the	De- scrip- tion	scrip-	
---------------	-----------------------	--------	--

Telescopic lances







		Order no.	Flow rate	Length of the product	Length	Price	De- scrip- tion	
Hoses								
iSolar HP hose 7	1	6.392-978.0			8.5 m			
iSolar HP hose 10	2	6.392-977.0			11.5 m			
iSolar HP hose 14	3	6.392-976.0			15 m			



		Order no.	Nozzle size			Price	Description	
Wet blasting attachment (without n	ozzle)							
Wet blasting attachment with flow control (without nozzles)	1	4.115-000.0					Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet.	
Wet blasting attachment without flow control (nozzles not included)	2	4.115-006.0					Paint, rust and scale removal made easy: Kärcher wet blast- ing attachment with flow control for adding blasting abra- sive to the high-pressure jet. Without flow control.	
Nozzle kits for wet jet unit								
Nozzle kit for wet jet unit 050	3	2.112-023.0	50				Nozzle kit with wet blasting nozzle and nozzle insert (type specific). For optimal Kärcher wet blasting attachment per- formance. Only in combination with wet blasting attachment	
Boron carbide nozzle				-			•	
Boron carbide nozzle, for ma- chines up to 1,000 l/h	4	6.415-084.0	6 mm				In addition to nozzle packs. Very wear-resistant nozzle with boron carbide chuck for continuous-duty operation.	



		Order no.			Price	Description
Wheel mounting kit						
Wheel attachment kit for HDS 1000 Be/De	1	2.637-820.0				Practical kit with pneumatic tyres for HDS 1000 BE and HDS 1000 DE high-pressure cleaners. For improved manoeuvra- bility.

 \blacksquare Included in the scope of supply. $\hfill\square$ Available accessories.

2 3 Order no. Price Description Geka coupling Geka connector with hose barb, R 6.388-465.0 1 with hose barb 1' 6.388-473.0 with female thread Geka connector with inner thread, 2 R 3/4" Suction filter Water suction filter 6.414-956.0 Suitable for ponds, storage tanks or similar, polyamide filter 3 casing, stainless steel strainer, 800 µm mesh, R 3/4" and R 1" connection, without non-return valve Suction filter with check valve 4 4.730-012.0 Brass suction filter suitable for ponds, storage tanks, etc. With check valve. Water fine filter Universal water fine filter, 25 µm 5 2.637-020.0 Water fine filter, mesh size 25 um, max, temperature 50 °C. Protects the machine from small dirt particles in the water. П Water volume up to 1200 l/h. 3/4" connection, with 1" adapter. 6 2.637-691.0 Water fine filter, 100 um, R 3/4" Fine-mesh water filter, 100 μ m, max. temperature 60°C. Protects the high-pressure cleaner from dirt particles con-Г tained in the water. Transparent filter cup. Water flow rate up to 1200 l/h. Connector 3/4". Water fine filter, with adapter 7 4.730-102.0 Fine-mesh water filter, 125 μm , max. temperature 50°C. Protects the high-pressure cleaner from dirt particles con-Г tained in the water. Water flow rate up to 1200 l/h. Connection 3/4", with adapter, 1" Backflow check valve 8 2.641-374.0 Backflow preventer To prevent detergent getting into the drinking water cycle in case of inlet at low-pressure. - hot water resistant up to 80 °C - tested according to IEC 60335-2-79 - integrated leakage protection **Other HP Accessories** 9 2.869-067.0 Jet gun Short set-up time, easy transport, instant switch off - the jet gun is the affordable cleaning method for all kinds of small

■ Included in the scope of supply. Available accessories.

HDS 1000 De Weed, 1.811-947.0, 2022-07-27

KARCHER





to medium-sized areas. Adjustable pressure/water volume.





		Order no.	Flow rate		Price	Description
Push-on washing brush						
Push-on wash brush	1	4.113-001.0				For general-purpose cleaning of all surfaces. Clamps directly onto the spray lance. Connection M 18 x 1.5
Rotating washing brush						
Rotating wash brush for > 800 l/h machines, nylon bristles	2	4.113-002.0	800 - 1300 l/h			Driven by water stream. Gently removes fine dust and traffic film from any surface. Temperature resistant up to
Rotating wash brush for > 800 l/h machines, natural bristles	3	4.113-005.0	800 - 1300 l/h			60°C, M 18 x 1.5 (replaceable brush insert).