

Reference	FT INDE Inglés
Date	02/10/13
Revision	3
Page	1 of 6
Codes	INCO, INSI, INPISANIN, INPINZANI,

Denomination: Hollow Wall Anchor

INCOHollow wall anchor with
screw**INSI**Hollow wall anchor
without screw**INPISANIN**

Hollow wall anchor gun

**INPINZANI**

Hollow wall anchor pliers

**1.- CHARACTERISTICS**

- Anchor for hollow elements as airbrick, pladur, dry wall, plaster wall, etc.
- Max load in thin walls due to its design.
- With and without screw versions.
- Easy, fast and controlled installation. Requires a special gun.
- Previous installation or thought out.
- Available special pliers to use in difficult accessibility places.
- After Installation screw can be replaced with other with same metrical.

	<h1>TECHNICAL DATA SHEET</h1>	Reference	FT INDE Inglés
		Date	02/10/13
		Revision	3
		Page	2 of 6
Denomination: Hollow Wall Anchor		Codes	INCO, INSI, INPISANIN, INPINZANI,

2.- DIMENSIONS

CODE		Screw diameter M [mm]	Body diameter H [mm]	Screw length * L [mm]	Body length C [mm]
With screw	Without screw				
INCO421	INSI421	M4	6.9	28	21
INCO432	INSI432			41	33.5
INCO438	INSI438			47	39.5
INCO446	INSI446			54	46.5
INCO459	INSI459			67	60
INCO537	INSI537	M5	8.9	43.5	37
INCO552	INSI552			60	53
INCO565	INSI565			74	65.5
INCO580	INSI580			89	81
INCO637	INSI637	M6	10.1	45	37
INCO652	INSI652			60	53
INCO665	INSI665			74	66
INCO680	INSI680			89	81
---	INSI865	M8	12.2	-	67

(*) Screw no provided with INSI version

