

<b>MODENA ROUND SURFACE LED PANEL FAMILY DATASHEET</b>	<b>IP44</b>	<b>IK03</b>	
------------------------------------------------------------	-------------	-------------	-------------------------------------------------------------------------------------

**MODENA PRO**

Surface/suspended edge lit LED luminaire with a slim 27mm profile. Electronic, fixed output gear. IP44 protection degree. IK03. Body: sheet aluminium white (RAL9016). Diffuser: UV-stabilised, PRO-LINE prismatic optic. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.

Dimensions: Ø87x27mm  
 Luminaire efficiency: 68-84 lm/W  
 Weight: 4,8 kg

Light source: LED  
 Color rendering index: >80  
 Correlated colour temperature: 4000 Kelvin  
 Rated median useful life: 50000 L80 25°C  
 Rated output: Fixed output



**TECHNICAL DATA**

Article	Model	Product description	
6004000017	MODENA80_R_8W_LED_570	TOPE LED PANEL LIGHT 8W, Ø87x27mm	
Nominal wattage	8.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	461lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	Ø87x27mm	Weight	0.4kg

Article	Model	Product description	
6004000019	MODENA80_R_16W_LED_1140	TOPE LED PANEL LIGHT 16W, Ø145x27mm	
Nominal wattage	16.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1168lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	Ø145x27mm	Weight	1,0kg

Article	Model	Product description	
6004000020	MODENA80_R_22W_LED_1570	TOPE LED PANEL LIGHT 22W, Ø170x27mm	
Nominal wattage	22.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1772lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	Ø170x27mm	Weight	1,1kg

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© TopE Lighting

<b>MODENA ROUND SURFACE LED PANEL FAMILY DATASHEET</b>	IP44	IK03	□	<b>TOPE</b> 
------------------------------------------------------------	------	------	---	-------------------------------------------------------------------------------------------------

Article	Model	Product description	
6004000021	MODENA80_R_30W_LED_2150	TOPE LED PANEL LIGHT 30W, Ø220x27mm	
Nominal wattage	30.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	2147lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	ØØ220x27mm	Weight	1,3kg

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© TopE Lighting