

MODENA SQUARE SURFACE LED PANEL FAMILY DATASHEET	IP44	IK03	□	TOPE 
---	------	------	---	---

MODENA PRO

Surface/suspended edge lit LED luminaire with a slim 27mm profile. Electronic, fixed output gear. IP44 protection degree. IK03. Body: sheet aluminium white (RAL9016). Diffuser: UV-stabilised, PRO-LINE prismatic optic. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.

Dimensions: 87x87x27mm

Luminaire efficiency: 68-84 lm/W

Weight: 0,46 kg


Light source: LED

Color rendering index: >80

Correlated colour temperature: 4000 Kelvin

Rated median useful life: 50000 L80 25°C

Rated output: Fixed output



TECHNICAL DATA

Article	Model	Product description	
6004000022	MODENA80_S_8W_LED_570	TOPE LED PANEL LIGHT 8W, Ø87x87mm	
Nominal wattage	8.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	461lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	87x87x27mm	Weight	0,46kg

Article	Model	Product description	
6004000024	MODENA80_S_16W_LED_1140	TOPE LED PANEL LIGHT 16W, Ø145x145mm	
Nominal wattage	16.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1168lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	145x145x27mm	Weight	1,0kg

Article	Model	Product description	
6004000025	MODENA80_S_22W_LED_1570	TOPE LED PANEL LIGHT 22W, Ø170x170mm	
Nominal wattage	22.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1772lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimensions	170x170x27mm	Weight	1,1kg

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© TopE Lighting

MODENA SQUARE SURFACE LED PANEL FAMILY DATASHEET	IP44	IK03	□	TOPE 
---	------	------	---	---

Article	Model	Product description	
6004000026	MODENA80_S_30W_LED_2150	TOPE LED PANEL LIGHT 30W, Ø220x220mm	
Nominal wattage	30.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	2147lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	220x220x27mm	Weight	1,3kg