

**SPLIT ROUND LED PANEL FAMILY DATASHEET**

IP44

IK03

**TOPE** **SPLIT PRO**

A recessed/surface/suspended edge lit LED luminaire with a slim 7mm profile. Electronic, fixed output gear. IP44 protection degree. IK03. Body: sheet aluminium white (RAL9016). Diffuser: UV-stabilised, PRO-LINE prismatic optic. Electrical connection via push wire terminal blocks. Complete with 4000K LED. With integrated driver.

Dimencions: 597x597x9

Luminaire efficiency: 68-76 lm/W

Weight: 4,8 kg

Light source: LED

Color rendering index: >80

Correlated colour temperature: 4000 Kelvin

Rated median usefull life: 50000 L80 25°C

Rated output: Fixed.

**TECHNICAL DATA**

Article	Model	Product description	
6003000017	SPLIT80_R_5W_LED_355	TOPE LED PANEL LIGHT 5W, Ø75x7mm	
Nominal wattage	5.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	325lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	Ø75x7mm	Weight	0.4kg

Article	Model	Product description	
6003000018	SPLIT80_R_8W_LED_570	TOPE LED PANEL LIGHT 8W, Ø87x7mm	
Nominal wattage	8.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	461lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	Ø87x7mm	Weight	0,44kg

Article	Model	Product description	
6003000020	SPLIT80_R_16W_LED_1140	TOPE LED PANEL LIGHT 16W, Ø145x7mm	
Nominal wattage	16.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1168lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	Ø145x7mm	Weight	0,87kg

TopE Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement.

© TopE Lighting

<b>SPLIT ROUND LED PANEL FAMILY DATASHEET</b>	IP44	IK03	<input type="checkbox"/>	
-----------------------------------------------	------	------	--------------------------	-------------------------------------------------------------------------------------

Article	Model	Product description	
60032000020	SPLIT80_R_16W_LED_1140EME	TOPE LED PANEL LIGHT 16W, Ø145x7mm, Emergency	
Nominal wattage	16.0W	Luminous flux	1168lm
Nominal Voltage	220-240V	CRI	80
Power factor	0.90	Dimming	Emergency
Frequency	50/60Hz	Emergency luminous flux	720lm
Color temperature	4000K	Emergency working time	3 Hours
Dimencions	Ø145x7mm	Weight	0,87kg

Article	Model	Product description	
6003000021	SPLIT80_R_22W_LED_1570	TOPE LED PANEL LIGHT 22W, Ø170x7mm	
Nominal wattage	22.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	1772lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	Ø170x7mm	Weight	0,98kg

Article	Model	Product description	
60032000021	SPLIT80_R_22W_LED_1570EME	TOPE LED PANEL LIGHT 22W, Ø170x7mm, Emergency	
Nominal wattage	22.0W	Luminous flux	1772lm
Nominal Voltage	220-240V	CRI	80
Power factor	0.90	Dimming	Emergency
Frequency	50/60Hz	Emergency luminous flux	720lm
Color temperature	4000K	Emergency working time	3 Hours
Dimencions	Ø170x7mm	Weight	0,98kg

Article	Model	Product description	
6003000022	SPLIT80_R_30W_LED_2150	TOPE LED PANEL LIGHT 30W, Ø220x7mm	
Nominal wattage	30.0W	Color temperature	4000K
Nominal Voltage	220-240V	Luminous flux	2147lm
Power factor	0.90	CRI	80
Frequency	50/60Hz	Dimming	Not dimmable
Dimencions	Ø220x7mm	Weight	1,27kg

Article	Model	Product description	
60032000022	SPLIT80_R_30W_LED_2150EME	TOPE LED PANEL LIGHT 30W, Ø220x7mm, Emergency	
Nominal wattage	30.0W	Luminous flux	2147lm
Nominal Voltage	220-240V	CRI	80
Power factor	0.90	Dimming	Emergency
Frequency	50/60Hz	Emergency luminous flux	720lm
Color temperature	4000K	Emergency working time	3 Hours
Dimencions	Ø220x7mm	Weight	1,27kg