



PRODUCT FEATURES

WALL-HUNG TOILET NAUTIC 1522 - WITH CISTERN, HYGIENIC FLUSH

Dual flush 2/4L, without seat

- Easy-to-clean and minimalistic design
- Space between tank and wall for easier cleaning
- With open, glazed flush edge for simplified cleaning

ARTICLE NUMBER: GB111522201205

EAN-NUMBER 7391530067346




- The product follows AMA recommendations, SS-EN 33 dimensioning and SS-EN 997 function
- Complies with Safe Water installation requirements
- CE approved

ASSEMBLING & CARE

Mounted with bolts directly on the wall. Washers, bushings and nuts included (M12) but not bolts. Bolt projection from finished wall must be $60 \pm 2\text{mm}$. Rubber bellows for waste pipe connection included. See supplied installation instructions and mounting kit for each toilet. Triomont fixture for wall hung toilet and bidet RSK 382 57 56, is recommended for installation on weak walls. According to the AMA the seat height should be 450 mm which corresponds to 270 mm distance (centre-centre) between the existing floor and the centre of the drain.

DRAWING



A MEMBER OF THE
VILLEROY & BOCH GROUP

Villeroy & Boch Gustavsberg AB
Box 400, 134 29 Gustavsberg, Sweden
Tel: +46 (0) 8-570 391 00 | Fax +46 8 570 320 36
gustavsberg.com | e-post: info@gustavsberg.com