

SOPOT_48W_LED_3840	IP20	IK03	<input type="checkbox"/>	CE	
--------------------	------	------	--------------------------	----	--

TopE article 6004000058

Data Sheet

A round ultra thin LED luminaire. Electronic, Infrared wireless dimmable and CCT adjustable output control gear. Body and bezel: white finish, spun White painted Steel. Diffuser: opal Polycarbonate (PC).
Class I electrical, IP20.
3000 to 6500K CCT adjustable
Remote included to the set.



Dimencions: Ø600x75mm

Total power: 48-96W

Luminaire luminous flux: 6500lm max

Luminaire efficiancy: 80 lm/W

Weight: 1,95 kg

Light source: LED

Color rendering index min.: >80

Correlated colour temperature: 3000 – 6500 Kelvin

Rated median usefull life: 30000 L70 25°C

Ballast: 1xB

Luminaire input power: 48-96W

Dimming: Dimmable to 1%

All values are rated values. TopE Lighting uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at ±10%. Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of 25°C. In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint

