






# ENSTO

## AVH11.2

### Saunavalgusti

|           |   |
|-----------|---|
| Tüüp      | AVH11.2   |
| GTIN      | 6410041171449   |
| Nimi      | Saunavalgusti Ensto<br>1x40/60W A60/E27 IP44, ta125 °C  |
| Kirjeldus | Saunavalgusti männipuust restiga. Sobib kasutamiseks ka muudes ruumides, kus on vaja pidevat püsivalgustust. Korpus kuumakindlast polüestrist, kuppel klaasist.   |
| Müüja     | Ensto Lighting Oy   |
|           |      |



## Spetsifikatsioon

### Dimensions

|                    |             |
|--------------------|-------------|
| Kaal:              | 2.05 kg     |
| Pikkus:            | 250 mm      |
| Mõõtmed p x l x k: | 250x250x135 |

### Temperatures

|                 |                |
|-----------------|----------------|
| Töötemperatuur: | -25 ... 125 °C |
|-----------------|----------------|

### Materials

|           |           |
|-----------|-----------|
| Materjal: | Polüester |
|-----------|-----------|

### Features

|                |               |
|----------------|---------------|
| Valgusallikas: | 1xA60 60W/E27 |
|----------------|---------------|

### Mechanical

|               |   |
|---------------|---|
| Löögitaluvus: | - |
|---------------|---|

### Certificates

|               |    |
|---------------|----|
| Certificates: | FI |
|---------------|----|

### Ratings

|             |       |
|-------------|-------|
| Nimipinge:  | 230 V |
| Kaitseaste: | IP44  |

|             |                                  |
|-------------|----------------------------------|
| Kaitseaste: | II                               |
| ETIM 7:     | EC002892 Ceiling-/wall luminaire |

## Valgustusinfo

---

### Valgustus tehline info

|                                       |               |
|---------------------------------------|---------------|
| Dimmerdatavus:                        | -             |
| Sokkel:                               | E27           |
| Materjali kuumusindeks:               | 650 °C        |
| Valgusallikate arv ja võimsus (W):    | 1x40/60       |
| Valgusallikas (ILCOS):                | IA            |
| Valgusallikas:                        | A60           |
| Konstruksioon/muud tehnilised andmed: |               |
| Optics:                               | Wood diffuser |
| Paigaldus:                            | Pindpaigaldus |
| Ühendamine vooluvõrku:                | Lõppühendus   |
| Ühendamine vooluvõrku:                | 2x1,5         |
| Ühendamine vooluvõrku:                | Kruviklemm    |

## ETIM

---

### ETIM

|  |                   |
|--|-------------------|
| Height/depth:                          | 135 mm            |
| With air slots:                        | false             |
| Nominal voltage:                       | 230 V             |
| Suitable for surface mounting:         | true              |
| Colour housing:                        | Other             |
| Protection class:                      | II                |
| Suitable for light line configuration: | false             |
| With movement sensor:                  | false             |
| Voltage type:                          | AC                |
| Dimming DSI:                           | false             |
| Control gear included:                 | true              |
| Suitable for ceiling mounting:         | false             |
| Dimming depending on control gear:     | false             |
| Light sharing:                         | Symmetric         |
| Light outlet:                          | Direct            |
| Suitable for wall mounting:            | true              |
| Length:                                | 250 mm            |
| Suitable for built-in mounting:        | false             |
| Material cover:                        | Glass transparent |
| Dimming Zigbee:                        | false             |
| Dimming Touch and Dim:                 | false             |
| Dimming 1-10 V:                        | false             |
| Dimming 0-10 V:                        | false             |
| Dimming DMX:                           | false             |

|  |                   |
|--|-------------------|
| Dimming DALI:  | false             |
| Dimming Sine Wave Reduction:   | false             |
| Dimming RF:  | false             |
| Dimming manufacturer's proprietary system:                             | false             |
| Dimming LineSwitch:  | false             |
| Dimming phase cut-off:   | false             |
| Dimming mains voltage modulation:                                      | false             |
| Dimming GPRS:  | false             |
| Beam angle:  | Open beam/diffuse |
| Lamp holder:   | E27               |
| With light source:   | false             |
| Covering of the luminaire with thermally insulating material possible: | true              |
| Luminaire with limited surface temperature, sign "D":                  | false             |
| Material housing:  | Plastic           |
| Suitable for number of lamps:  | 1                 |
| Dimming potentiometer (integrated):                                    | false             |
| Width:   | 250 mm            |
| Dimming programmable:  | false             |
| Type of control gear:  | Not required      |
| No dim function:   | true              |
| Dimming with push-button:  | false             |
| Degree of protection (IP):   | IP44              |
| Fit for monitor workplace acc. EN 12464-1:                             | false             |
| Suitable for suspended mounting:                                       | false             |
| Type of grid:  | None              |
| Dimming phase cut-on:  | false             |
| Suitable for emergency lighting:                                       | false             |
| With light sensor:   | false             |

## Pakkeinfo

---

### Default package

|               |         |
|---------------|---------|
| Unit:         | PCS     |
| Size:         | 1       |
| Length:       | 252 mm  |
| Width:        | 252 mm  |
| Height:       | 137 mm  |
| Weight (net): | 2.05 kg |
| Weight (brt): | 2.27 kg |
| Volume:       | 8.7     |

### Pallet package

|       |     |
|-------|-----|
| Unit: | PCS |
| Size: | 81  |

|               |           |
|---------------|-----------|
| Length:       | 1200 mm   |
| Width:        | 800 mm    |
| Height:       | 990 mm    |
| Weight (brt): | 220.02 kg |
| Volume:       | 950       |

