






# ENSTO

## AVH11

### Saunavalgusti

Tüüp	AVH11
GTIN	6410041171388
Nimi	Saunavalgusti Ensto 1x60W A60/E27 IP44, ta125 °C
Kirjeldus	Saunavalgusti sobib kasutamiseks ka muudes ruumides, kus on vaja pidevat püsivalgustust. Korpus kuumakindlast polüestrist, kuppel klaasist.
Müüja	Ensto Lighting Oy
	    



## Spetsifikatsioon

### Dimensions

Kaal:	1.19 kg
Pikkus:	194 mm
Läbimõõt:	205 mm

### Temperatures

Töötemperatuur:	-25 ... 125 °C
-----------------	----------------

### Materials

Materjal:	Polüester
-----------	-----------

### Colors

Värv:	Valge
-------	-------

### Features

Valgusallikas:	1xA60 60W/E27
----------------	---------------

### Mechanical

Löögitaluvus:	-
---------------	---

### Certificates

Certificates:	FI
---------------	----

## Ratings

Nimipinge:	230 V
Kaitseaste:	IP44
Kaitseaste:	II
ETIM 7:	EC002892 Ceiling-/wall luminaire

## Valgustusinfo

### Valgustus tehlinine info

Dimmerdatavus:	-
Sokkel:	E27
Materjali kuumusindeks:	650 °C
Valgusallikate arv ja võimsus (W):	1x60
Valgusallikas (ILCOS):	IA
Valgusallikas:	A60
Konstruksioon/muud tehnilised andmed:	
Optics:	Ribbed diffuser, clear
Paigaldus:	Pindpaigaldus
Ühendamine vooluvõrku:	Lõppühendus
Ühendamine vooluvõrku:	2x1,5
Ühendamine vooluvõrku:	Kruviklemm

## ETIM

### ETIM

Height/depth:	105 mm
With air slots:	false
Nominal voltage:	230 V
Suitable for surface mounting:	true
Colour housing:	White
Protection class:	II
Suitable for light line configuration:	false
With movement sensor:	false
Voltage type:	AC
Dimming DSI:	false
Control gear included:	true
Suitable for ceiling mounting:	false
Dimming depending on control gear:	false
Light sharing:	Symmetric
Light outlet:	Direct
Suitable for wall mounting:	true
Length:	194 mm
Suitable for built-in mounting:	false
Material cover:	Glass transparent
Dimming Zigbee:	false
Dimming Touch and Dim:	false

Dimming 1-10 V:	false
Dimming 0-10 V:	false
Dimming DMX:	false
Dimming DALI:	false
Dimming Sine Wave Reduction:	false
Dimming RF:	false
Dimming manufacturer's proprietary system:	false
Dimming LineSwitch:	false
Dimming phase cut-off:	false
Dimming mains voltage modulation:	false
Dimming GPRS:	false
Beam angle:	Open beam/diffuse
Lamp holder:	E27
With light source:	false
Covering of the luminaire with thermally insulating material possible:	true
Luminaire with limited surface temperature, sign "D":	false
Material housing:	Plastic
Suitable for number of lamps:	1
Dimming potentiometer (integrated):	false
Width:	205 mm
Dimming programmable:	false
Type of control gear:	Not required
No dim function:	true
Dimming with push-button:	false
Degree of protection (IP):	IP44
Fit for monitor workplace acc. EN 12464-1:	false
Suitable for suspended mounting:	false
Type of grid:	None
Dimming phase cut-on:	false
Suitable for emergency lighting:	false
With light sensor:	false

## Pakkeinfo

---

### Default package

Unit:	PCS
Size:	1
Length:	195 mm
Width:	195 mm
Height:	106 mm
Weight (net):	1.191 kg
Weight (brt):	1.31 kg
Volume:	4.03

## Pallet package

Unit:	PCS
Size:	160
Length:	1200 mm
Width:	800 mm

