

# TYPE APPROVAL CERTIFICATE

**This is to certify:****That the Electric Power Cable**with type designation(s)  
**RADOX 125 Switchboard wire**

Issued to

**Huber+Suhner AG**  
**Pfäffikon, ZH, Switzerland**is found to comply with  
**DNV GL rules for classification – Ships, offshore units, and high speed and light craft****Application :****Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV GL.****Rated voltage (kV) 0,6/1**  
**Temp. class (°C) 90**Issued at **Hamburg** on **2019-04-11**This Certificate is valid until **2024-04-10**.DNV GL local station: **Augsburg**Approval Engineer: **Carsten Hunsalz**for **DNV GL**

---

**Arne Schaarmann**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



## Product description

Type: RADOX 125 0,6/1 kV Switchboard wire

Construction:

Conductor: Tinned, stranded copper class 5

Core insulation: Radox 125 (HF90)

Conductor cross-section	Overall diameter
mm <sup>2</sup>	mm
1,0	2,6±0,1
1,5	2,85,1±0,1
2,5	3,35±0,1
4	3,95±0,1
6	4,65±0,15
10	5,6±0,15

Conductor cross-section	Overall diameter
mm <sup>2</sup>	mm
16	6,75±0,15
25	8,5±0,2
35	9,7±0,2
50	11,4±0,2
70	13,8±0,25
95	15,3±0,25

Conductor cross-section	Overall diameter
mm <sup>2</sup>	mm
120	17,2±0,3
150	19,1±0,3
185	21,3±0,3
240	24,5±0,3
300	27,1±0,4

## Application/Limitation

The requirements of SOLAS Amendments Chapter II-1, Part D, Reg. 45, 5.2 (provision to be taken to limit Fire Propagation along Bunches of Cables or Wires) are fulfilled without any additional measures.

Switchboard wire for power and instrumentation circuits inside cabinets.  
 Flame retardant in bunch Cat. A. Halogen free. Low smoke.

## Type Approval documentation

### Tests carried out

Standard	Release	General description	Limitation
IEC 60092-350	2014-08	General construction and test methods of power, control and instrumentation cables for shipboard and offshore applications	
IEC 60092-353	2016-09	Electrical installations in ships - Part 353: Power cables for rated voltages 1 kV and 3 kV	
IEC 60092-360	2014-04	Electrical installations in ships - Part 360: Insulating and sheathing materials for shipboard and offshore units, power, control, instrumentation and telecommunication cables.	
IEC 60332-1-2	2015-07	Tests on electric and optical fibre cables under fire conditions - Part 1-2: Test for vertical flame propagation for a single insulated wire or cable - Procedure for 1 kW pre-mixed flame	
IEC 60332-3-22	2018-07	Tests on electric and optical fibre cables under fire conditions - Part 3-22: Test for vertical flame spread of vertically-mounted bunched wires or cables - Category A	Charred portion of sample does not exceed 2,5m above bottom edge of burner.

Job Id: **262.1-030546-1**  
Certificate No: **TAE00003GH**

<b>Standard</b>	<b>Release</b>	<b>General description</b>	<b>Limitation</b>
IEC 60754-1	2011-11	Test on gases evolved during combustion of materials from cables - Part 1: Determination of the halogen acid gas content	Low Halogen: <0,5% Halogen
IEC 60754-2	2011-11	Test on gases evolved during combustion of materials from cables - Part 2: Determination of acidity (by pH measurement) and conductivity	Halogen free: pH > 4,3 Conductivity < 10µS/mm
IEC 60684-2	2011-08	Clause 45.2 Methods of determination of low levels of fluorine	HF max 0,1%
IEC 61034-1/2	2013-06	Measurement of smoke density of cables burning under defined conditions – Test apparatus, procedure and requirements	Low smoke Light transmittance >60%

## Marking of product

<Huber+Suhner RADOX 125 1X[*cross section*] [*prod. place*]> 0.6/1 kV HF90 IEC 60332-3-22

## Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the Type approval are complied with and that no alterations are made to the product design or choice of materials.

The main elements of the assessment are:

- Inspection on factory samples, selected at random from the production line (where practicable)
- Results from Routine Tests (RT) checked (if not available tests according to RT to be carried out)
- Review of type approval documentation
- Review of possible change in design, materials and performance
- Ensuring traceability between manufacturer's product type marking and Type Approval Certificate.

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE