

Data Sheet

Item Code:	KM Turbo
Description:	grip type coupler
Properties:	for waterproof and tight connection of pliable conduits, especially for use in concrete installation, extraction resistance >250 N
Colour:	light grey, similar to RAL 7035
Relevant Standard:	EN 61386 chlorine free



Material	IP	Temperature Range	UV Stabilisation
PE	40	-25 °C/+90 °C	none

Package Quantity [ps]:

Item Code	Small Package	Large Package
KM Turbo 16	100	1,200
KM Turbo 20	100	800
KM Turbo 25	50	600
KM Turbo 32	25	300
KM Turbo 40	25	200
KM Turbo 50	15	120
KM Turbo 63	8	64

Measurements [mm]:

Item Code	O.D.	I.D.	L	I
KM Turbo 16	20.0	16.2	51.5	25.0
KM Turbo 20	24.2	20.2	56.0	27.2
KM Turbo 25	29.4	25.2	56.0	27.2
KM Turbo 32	36.7	32.2	62.0	30.2
KM Turbo 40	43.3	39.5	66.0	32.8
KM Turbo 50	53.4	49.4	86.0	42.8
KM Turbo 63	66.5	62.3	102.0	50.8

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice.