

M12 FIWF12-O | M12 FUEL™ sub compact 1/2 impact wrench



- More power, more compact, more control.
- Up to 339Nm of maximum torque.
- 1/2" anvil with friction ring for quick and easy socket changes.
- Milwaukee® designed and built brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	M12 FIWF12-O
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	1100/2100/3200
Max. bolt diameter	M16
Max. fastening torque (Nm)	339
Max. torque (Nm)	339
No load speed (rpm)	1200/1800/2700/2700
No. of batteries supplied	0
Nut-busting torque (Nm)	339
Sound power level measured (dB(A))	107.82
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	96.69
Sound pressure level uncertainty (dB(A))	3
Supplied in	-
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s ²]	10.26
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s ²]	1.5
Voltage (V)	12
Weight with battery pack (kg)	-