

M28 CHPX-502C | M28 FUEL™ 4-mode SDS-plus hammer with FIXTEC chuck



- Milwaukee® designed and built brushless POWERSTATE™ motor.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- High powered motor gives corded tool performance.
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism: delivers 4.1 J of impact energy at low 8.1 m/s² vibrations thanks to the new dual rail anti-vibration system.
- All metal gear case - optimum seating of the gears for enhanced service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.

M28 CHPX-502C	
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Blow energy (EPTA)(J)	4.1
Charger supplied	90 min
Max. drilling concrete (mm)	28
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. percussion rate (bpm)	0 - 5000
No load speed (rpm)	0 - 1350
No. of batteries supplied	2
Optimised drilling capacity in concrete (mm)	ø 7 - 24
Sound power level measured (dB(A))	103.7
Sound power level measured uncertainty (dB(A))	3.0
Sound pressure level (dB(A))	92.7
Sound pressure level uncertainty (dB(A))	3.0
Standard equipment	Side handle, depth gauge, grease, FIXTEC 13 mm full metal chuck
Supplied in	Kitbox
Vibration chiseling (m/s ²)	8.1
Vibration chiselling uncertainty (m/s ²)	1,5
Vibration drilling (m/s ²)	8.1
Vibration drilling into concrete [m/s ²]	8.1
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Voltage (V)	28