

HD18 HIWF-0 | M18™ impact wrench with friction ring



- Engineered for heavy use, the M18™ impact wrench with friction ring delivers maximum cordless power on the jobsite.
- With its Milwaukee® 4-pole frameless motor it delivers a staggering 610 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- ½" square friction ring.
- Ideal for heavy applications such as steel fabrication, mechanical fastening, industrial construction and automotive work.
- Light weight and ergonomically designed.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	HD18 HIWF-0
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	0 - 2200
Max. torque (Nm)	610
No load speed (rpm)	0 - 1900
No. of batteries supplied	0
Sound power level (dB(A))	91
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	80
Sound pressure level uncertainty (dB(A))	3
Supplied in	-
Vibration screw driving (m/s ²)	11.3
Vibration screw driving uncertainty (m/s ²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	-