

## HD28 AG125-0X | M28™ 125 mm angle grinder



- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear case delivers heavy duty durability.
- Reduced height of gear box and slim girth design deliver optimum ergonomics.
- Fast and easy wheel change with patented FIXTEC nut.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.
- AVS side handle for most compatible work and less strain to the user.

	HD28 AG125-0X
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	36
No load speed (rpm)	9000
No. of batteries supplied	0
Sound power level (dB(A))	90
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	79
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Safety guard, additional AVS handle, FIXTEC flange nut
Supplied in	HD Box
Vibration grinding (m/s <sup>2</sup> )	5.5
Vibration grinding uncertainty (m/s <sup>2</sup> )	1.5
Vibration sanding (m/s <sup>2</sup> )	2.5
Vibration sanding uncertainty (m/s <sup>2</sup> )	1.5
Voltage (V)	28
Weight (kg)	1.9
Weight with battery pack (kg)	—