

HD28 IW-502X | M28™ 1/2 drive impact wrench with pin detent



- With its Milwaukee® 4-pole frameless motor it delivers a staggering 440 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Durable, lightweight magnesium gear case for extended life and comfort.
- Variable speed trigger for enhanced control and accuracy.
- 1/2" square drive with detent pin for secure socket retention.
- Non-slip gripping surfaces for maximum comfort and control.
- Exclusive reversible battery pack design for optimal tool balance.

HD28 IW-502X	
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	90 min
Impact rate (ipm)	0 - 2450
Max. torque (Nm)	440
No load speed (rpm)	0 - 1450
No. of batteries supplied	2
Sound power level (dB(A))	91
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	80
Sound pressure level uncertainty (dB(A))	3
Supplied in	HD Box
Vibration screw driving (m/s ²)	11.3
Vibration screw driving uncertainty (m/s ²)	1.5
Voltage (V)	28
Weight with battery pack (kg)	4.1