

HD28 SX-0 | M28™ SAWZALL®



- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Milwaukee® patented FIXTEC clamp for fast and easy keyless blade change.
- Gear protection clutch - protects the gearbox in case of blade lock ups.
- Counter balance mechanism to reduce vibrations.
- 28.6 mm stroke length, 3000 spm for extremely fast cutting.
- Tool free, adjustable shoe quickly adjusts blade depth.

	HD28 SX-0
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
Max. cutting depth in aluminium (mm)	25
Max. cutting depth in metal pipe (mm)	150
Max. cutting depth in non-ferrous metal (mm)	25
Max. cutting depth in soft-wood (mm)	300
Max. cutting depth in steel (mm)	25
No load stroke rate (spm)	0-2000/0-3000
No. of batteries supplied	0
Sound power level (dB(A))	94
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83
Sound pressure level uncertainty (dB(A))	3
Stroke length (mm)	28.6
Supplied in	—
Vibration cutting (m/s ²)	16.8
Vibration cutting uncertainty (m/s ²)	1.5
Voltage (V)	28
Weight (kg)	3.2
Weight with battery pack (kg)	—