

M18 FID-0 | M18 FUEL™ 1/4" Hex impact driver



- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 20% more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- The Milwaukee® DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.

	M18 FID-0
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Impact rate (ipm)	1800/2900/3700/0-3700
Max. fastening torque (Nm)	203
Max. torque (Nm)	26/80/203/0-203
No load speed (rpm)	850/2100/3000/0-3000
No. of batteries supplied	0
Sound power level measured (dB(A))	105
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	94
Sound pressure level uncertainty (dB(A))	3
Supplied in	-
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s ²]	11.4
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s ²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	-