

M18 ONEID-502X | ONE-KEY™ FUEL™ 1/4" Hex impact driver



- M18 FID but with ONE-KEY™ technology.
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app.
- Complete tool customisation via ONE-KEY™ app to tune the tool to your needs.
- Control speed, torque, start and end speeds and LED control.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Program/save profiles for unmatched control.
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull.

M18 ONEID-502X	
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	1450/2400/2900/3700
Max. fastening torque (Nm)	203
Max. torque (Nm)	26/80/150/203
No load speed (rpm)	850/1500/2100/3000
No. of batteries supplied	2
Sound power level measured (dB(A))	105
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	94
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Belt Clip
Supplied in	HD Box
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s ²]	11.4
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s ²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	1.7