

## M12 FID-0 | M12 FUEL™ sub compact 1/4 Hex impact driver



- Milwaukee® designed and built brushless POWERSTATE™ motor with faster speed in a more compact size of 130 mm.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- The Milwaukee® DRIVE CONTROL™ allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 1/4" Hex chuck for quick and easy bit change.
- On board fuel gauge and LED light.

	M12 FID-0
Battery pack capacity (Ah)	—
Battery type	Li-ion
Charger supplied	—
Impact rate (ipm)	0 - 4000
Max. bolt diameter	M14
Max. torque (Nm)	147
No load speed (rpm)	0-1300 / 0-2400 / 0-3300 / 0-3300
No. of batteries supplied	0
Sound power level measured (dB(A))	99.1
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	88.1
Sound pressure level uncertainty (dB(A))	3
Supplied in	—
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m/s <sup>2</sup> ]	12.2
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	12
Weight with battery pack (kg)	—