

M18 FHIWP12-502X | M18 FUEL™ 1/2 high torque impact wrench with pin detent



- The M18 FUEL™ high torque impact wrench delivers 1017 Nm fastening torque in a compact size of 206 mm, which gives more access in tight spaces.
- 4-Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides maximum nut-busting of 1491 Nm then shifts to 750 rpm for unmatched control when removing fasteners.
- 1/2" pin detent for maximum socket retention.
- New LED light is 40 percent brighter than previous model.
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.

	M18 FHIWP12-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	0-1150/0-2100/0-2400/0-2400
Max. bolt diameter	M24
Max. fastening torque (Nm)	190/400/1017/1017
No load speed (rpm)	0-950/0-1500/0-1800/0-1800
No. of batteries supplied	2
Nut-busting torque (Nm)	1491
Supplied in	HD Box
Voltage (V)	18
Weight with battery pack (kg)	3.2