

M12 H-402C | M12™ sub compact SDS-plus hammer



- Ergonomically designed, compact and light weight allows for work in tight spaces and reduces fatigue during all day use.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- L-shape, 2 mode hammer drill for hammer & rotary drilling for maximum versatility.
- Low vibration at 6.7 m/s².
- Optimised hammer drilling up to 4 - 8 mm (max 13 mm).
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.

	M12 H-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	0.9
Charger supplied	80 min
Max. drilling concrete (mm)	13
Max. drilling steel (mm)	8
Max. drilling wood (mm)	10
No load speed (rpm)	0 - 800
No. of batteries supplied	2
Optimised drilling capacity in concrete (mm)	ø 5.5 - 10
Sound power level (dB(A))	92.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	81.5
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration drilling (m/s ²)	6.7
Vibration drilling into concrete [m/s ²]	6.7
Vibration drilling into concrete uncertainty [m/s ²]	1.5
Voltage (V)	12
Weight with battery pack (kg)	1.8