

HD18 AG-125-0 | M18™ 125 mm angle grinder with paddle switch



- Milwaukee®'s high performance 4-pole motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear case delivers heavy duty durability.
- Reduced height of gear box and slim girth design deliver optimum ergonomics.
- Non-lockable switch for best user protection and preventing automatic start up.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.
- Multi position side handle for ease of use.

HD18 AG-125-0	
Battery pack capacity (Ah)	-
Battery type	Li-ion
Charger supplied	-
Disc diameter (mm)	125
Line lock out function	No
Max. cutting depth (mm)	33
No load speed (rpm)	9000
No. of batteries supplied	0
Sound power level (dB(A))	85.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	74.5
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Safety guard, side handle
Supplied in	-
Switch type	Paddle switch
Vibration grinding (m/s ²)	7.3
Vibration grinding uncertainty (m/s ²)	1.5
Vibration sanding (m/s ²)	6.1
Vibration sanding uncertainty (m/s ²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	-