M12 BD-202C | M12™ sub compact driver



- Milwaukee® high performance sub compact screw driver measures 175 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 1/4" Hex chuck for quick easy one handed bit change.
- o Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light added user convenience and illumination in low lit working conditions.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

| | M12 BD-202C |
|--|-------------|
| Battery pack capacity (Ah) | 2.0 |
| Battery type | Li-ion |
| Charger supplied | 40 min |
| Max. drilling steel (mm) | 10 |
| Max. drilling wood (mm) | 22 |
| Max. torque (Nm) | 30 |
| No load speed gear 1 (rpm) | 0 - 400 |
| No load speed gear 2 (rpm) | 0 - 1500 |
| No. of batteries supplied | 2 |
| Sound power level (dB(A)) | 96 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 85 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Supplied in | Kitbox |
| Vibration drilling into Metal [m s²] | 1.5 |
| Vibration drilling into metal uncertainty [m s²] | 1.5 |
| Vibration screw driving (m/s²) | 0.4 |
| Vibration screw driving uncertainty (m/s²) | 1.5 |
| Voltage (V) | 12 |
| Weight with battery pack (kg) | 1.0 |
| Wood screws to (mm) | 6 |
| | |

Milwaukee