


## WCHP-SB 30 mm 1/2" G - 1 pc | Wet diamond drilling cores WCHP-SB up to 50 mm



- Standard 1/2" G reception.
- Engraving of diameter and type on the core reception for longterm visibility.
- Laser welded segments guarantee against break off.
- 10 mm segment height for superior life time.
- Extra thin 2 mm segment for fast and aggressive drilling in reinforced concrete.
- Closed ring segment for outstanding performance in tough applications.

| WCHP-SB 30 mm 1/2" G - 1 pc                 |                     |
|---|---------------------|
| Aerated and breeze concrete blocks          | Most suitable       |
| Artificial stone                            | Not suitable        |
| Asphalt                                     | Not suitable        |
| Diameter (mm)                               | 30                  |
| Fits DCM2-250C & DCM2-350C                  | ♦                   |
| Fits DD3-152                                |                     |
| Granite                                     | Not suitable        |
| Lime and sandstone blocks medium to hard    | Limited suitability |
| Lime and sandstone blocks soft and abrasive | Limited suitability |
| Lime and sandstone blocks very hard         | Not suitable        |
| Marble                                      | Limited suitability |
| Pack quantity                               | 1                   |
| Porphyry                                    | Not suitable        |
| Screed                                      | Most suitable       |
| Slate                                       | Limited suitability |
| Stoneware and clay pipes                    | Limited suitability |
| Total length (mm)                           | 365                 |
| Working length (mm)                         | 300                 |