

WCHP-SB 12 mm 1/2" G - 1 pc | Wet diamond drilling cores WCHP-SB up to 50 mm



- Standard 1/2" G reception.
- Engraving of diameter and type on the core reception for longterm visibility.
- Laser welded segments guarantee against break off.
- 10 mm segment height for superior life time.
- Extra thin 2 mm segment for fast and aggressive drilling in reinforced concrete.
- Closed ring segment for outstanding performance in tough applications.

| WCHP-SB 12 mm 1/2" G - 1 pc | |
|---|---------------------|
| Aerated and breeze concrete blocks | Most suitable |
| Artificial stone | Not suitable |
| Asphalt | Not suitable |
| Diameter (mm) | 12 |
| Fits DCM2-250C & DCM2-350C | ♦ |
| Fits DD3-152 | |
| Granite | Not suitable |
| Lime and sandstone blocks medium to hard | Limited suitability |
| Lime and sandstone blocks soft and abrasive | Limited suitability |
| Lime and sandstone blocks very hard | Not suitable |
| Marble | Limited suitability |
| Pack quantity | 1 |
| Porphyry | Not suitable |
| Screed | Most suitable |
| Slate | Limited suitability |
| Stoneware and clay pipes | Limited suitability |
| Total length (mm) | 265 |
| Working length (mm) | 200 |