

## M18 CCS66-502X | M18 FUEL™ 66mm circular saw for wood and plastics



- Milwaukee® designed and built brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 190 mm blade which gives a 66 mm depth of cut enables the saw to cut three stacked OSB boards.
- The saw blade is mounted on the right of the saw keeping the extracted dust away from the user.
- 50° bevel capacity.

M18 CCS66-502X	
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Blade diameter (mm)	190
Bore size (mm)	30
Charger supplied	59 min
Max. cutting depth 45° (mm)	48
Max. cutting depth 90° (mm)	66
No load speed (rpm)	5000
No. of batteries supplied	2
Sound power level (dB(A))	94.2
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	83.2
Sound pressure level uncertainty (dB(A))	1.5
Standard equipment	Saw blade, side fence, dust extraction chute, blade wrench
Supplied in	HD Box
Vibration sawing of wood [m/s <sup>2</sup> ]	2.0
Vibration sawing of wood uncertainty [m/s <sup>2</sup> ]	1.5
Voltage (V)	18
Weight with battery pack (kg)	4.2