

# Conex | Bänninger

# Series 8000

A range of Yellow Brass threaded fittings.



### Features and Benefits:

- Yellow brass threaded fittings.
- Available in sizes 1/8-2".
- Manufactured to BSEN 1254-4.
- The threads are manufactured to ISO 228-1.
- Suitable to material with EN12165, CW617N, EN12164 and CW617N.

- Hydraulic working temperatures and pressures:

Size (inches)	Working pressure (bar)	
	-20°C to 120°C	> 120 to 225°C
1/4" to 3/4"	25	16
1 to 2	16	10
2 to 4	10	6



# Conex | Bänninger

## Series 8000

### 8000 Range

Brass Plug  
Male Thread (Parallel)



**8595**  
From: 1/4"  
To: 2"

Female Elbow  
Female x Female Thread



**8090**  
From: 1/4"  
To: 3/4"

Male x Female Elbow  
Male x Female Thread



**8092**  
From: 3/8"  
To: 1"

Tee - Equal  
Female Thread All Ends



**8130**  
From: 1/4"  
To: 1"

Reduced Bush  
Male x Female Thread



**8241**  
From: 3/8" x 1/4"  
To: 2" x 1.1/2"

Straight Coupler  
Female x Female Thread



**8270**  
From: 1/4"  
To: 2"

Hexagon Nipple  
Male x Male Thread



**8280**  
From: 1/8"  
To: 2"

Flanged Backnut



**8310**  
From: 1/2"  
To: 2"

Barrel Nipple  
Male Thread x Length(mm)



**8530**  
From: 3/8" x 40mm  
To: 2" x 100mm

Running Nipple  
Male (Parallel)



**8531**  
From: 1/4"  
To: 3/4"

Blank Cap  
Female Thread



**8599**  
From: 1/4"  
To: 2.1/2"



\*Conex|Bänninger products are approved by numerous Standards Authorities and Certification Bodies. For more details on this product range, please email our technical team at: [technical@ibpgroup.com](mailto:technical@ibpgroup.com).

**Conex Universal Limited:** Global House, 95 Vantage Point, The Pensnett Estate, Kingswinford, West Midlands DY6 7FT, UNITED KINGDOM.  
Tel: +44 (0)121 557 2831 | Fax: +44 (0)121 520 8778 | Email: [salesuk@ibpgroup.co.uk](mailto:salesuk@ibpgroup.co.uk) | Website: [www.ibpgroup.com](http://www.ibpgroup.com)