

Sliding grease TOPSLIP- UW 28.4.5

TOPSLIP-UW 28.4.5 is a mineral oil free, non-polluting sliding grease for rubber seals on concrete pipes. Especially suitable for wet surfaces and temperature below freezing point.

- ▶ TOPSLIP-UW 28.4.5 can be used within an outside temperature range of – 18 °C to + 40 °C. Within this temperature range the product properties will not be influenced. The grease also can be used on wet surfaces.
- ▶ TOPSLIP-UW 28.4.5 is designed for optimal protection of seals when sliding on rough and wet concrete surfaces.



Special benefits

- ▶ **optimal protection of seals when sliding on rough and wet concrete surfaces**
- ▶ **to be used at a wide temperature range and in wet surroundings**
- ▶ **mineral oil free, no environmental influences, biological exploitable**

Property of material

TOPSLIP-UW 28.4.5 is based on bentonite, plant oils and admixtures. It is not environmental and not water pollutant. The product is biological exploitable and will not cause any disturbances in sewage plants when proper used.

Handling

Sliding grease TOPSLIP-UW 28.4.5 to put on rubber seal and concrete surface with brush or applicable tool.

Processing

TOPSLIP-UW 28.4.5 will be delivered in 5 kg pails, other delivery containments on request.

Storage

TOPSLIP-UW 28.4.5 to be stored in original containments not below -18°C and not over 40°C, storage time under specified conditions minimum 12 month.

All information's are based on our presently available knowledge and experience and no assurance of quality or legally contractual relationship. Changes will be reserved without prior notice. Errors and misprints to be reserved.

Stand: 08/20Rev.: 01

F & B GmbH * Braunsfelde 16 * D-39114 Magdeburg * Tel.: +49 (0) 160 96 22 19 33 * info@fundb-gmbh.de