

ES Air/Water monobloc heat pumps



AWT-R32-M 6, 9 and 12 kW

Economic and effective air-to-water heat pump, designed for a Nordic climate

- User-friendly touch display
- Built in Wi-Fi enables controlling and monitoring of the heat pump from computer or Smart Device
- Two different temperature zone setting
- Automatic restart in case of power failure
- 6, 9 and 12 kW heating capacity
- Operates in conditions down to -25°C
- Low investment – short payback time
- Low noise outdoor unit
- New eco-friendly refrigerant R32 enables A+++
- Anti-freeze protection device
- Inbuild el. heater for DHW and heating



User-friendly touch screen interface

The interface enables quick adjustment of all temperature settings directly from the front page. The software also supports variable temperature settings (curve) for both heating and cooling.



ES Air/Water heat pumps monobloc

AWT-R32-M 6, 9, and 12 kW



Converts energy from the outdoor air to heat and domestic hot water

By utilising the energy from outdoor air, you can reduce your energy bills in an eco-friendly way, and at the same time creating the perfect level of comfort for your home. AWT-R32-M is designed to replace or supplement an existing heat source or for new installations.

The indoor unit has a stylish design to fit into a modern home. All connections are easily accessible at the top of the unit.

Designed to provide maximum energy savings and quiet operation

By using components from leading suppliers (see table) and smart control, great energy savings and quiet operation are made possible. All AW-R32-M series are rated A+++.

Simple and cost-effective installation

In a monobloc system the outdoor unit has a

closed refrigerant circuit and a heat exchanger. The outdoor unit can be connected directly to the heating system, which means that no refrigeration technicians are needed during installation. The automatic and self-learning defrost function, combined with the nanocoated evaporator, reduces defrosting time to a minimum and increases the efficiency.

Control your heating system

AWT-R32-M can be controlled locally or remotely thru smartphone or computer. Make all the necessary settings for an efficient, trouble-free operation with the new user-friendly touch display. Even when you are not at home you have full control of your heating system thru your smartphone or computer.

Two heating curves

AWT-R32-M uses a heat curve to provide a constant indoor temperature, regardless of

the outdoor temperature. When the outdoor temperature drops, the heat pump raises the temperature of the water to the heating system and vice versa when the outdoor temperature rises. Different heating systems require different temperatures, e.g. floor heating and radiators. AWT-R32-M have the possibility to set two heating curves if you have two different heating systems in your home. With two heating curves the possibilities to save even more energy is possible and, in some cases, costs on components that would otherwise have to be installed in the system.

250 liters hot water tank

The integrated tank for domestic hot water heating is 250 liters and heated by the heat pump. If the temperature drops, the heat pump changes the operating status and starts the production of hot water. If additional power is required, the integrated electric heaters will be used as back-up.

		AWT6-R32-M	AWT9-R32-M	AWT12-R32-M	
Min/max heating capacity (1)	kW	3,50 / 6,50	4,30 / 9,20	5,50 / 11,60	
El. Heating power input min/max (1)	W	758 / 1410	927 / 2097	1107 / 2683	
C.O.P min/max (1)	WW	4,5 / 4,7	4,38 / 4,71	4,30 / 4,90	
Min/max heating capacity (2)	kW	3,15 / 6,00	3,90 / 8,60	4,90 / 11,20	
El. Heating power input min/max (2)	W	943 / 1732	1162 / 2550	1401 / 3263	
C.O.P min/max (2)	WW	3,34 / 3,56	3,37 / 3,58	3,30 / 3,50	
SCOP - Average climate, low temperature	WW	4,74	4,73	4,71	
Min/max cooling capacity (3)	kW	3,50 / 4,50	4,90 / 7,20	4,90 / 9,50	
El. cooling power input min/max (3)	W	1330 / 1680	1451 / 2366	1358 / 2444	
E.E.R. min/max (3)	WW	2,50 / 2,74	2,80 / 3,10	2,60 / 3,50	
Energy class		A+++	A+++	A+++	
Defrost upon demand		Yes	Yes	Yes	
Heating cable for defrosting/Anti-freeze protection		Yes / Yes	Yes / Yes	Yes / Yes	
Compressor pre-heat		Yes	Yes	Yes	
Electronic expansion valve		Yes	Yes	Yes	
ErP Circulating pump / flow switch		Yes / Yes (outdoor)	Yes / Yes (outdoor)	Yes / Yes (outdoor)	
Compressor		Mitsubishi			
Fan	Manufacturer	Yibisi	Shunwei	Shunwei	
	Quantity	pcs	1	1	
	Airflow	m³/h	2500	3150	3150
	Rated power	W	34	45	45
Sound pressure level*	Outdoor 0m / 5m	dB (A)	52 / 30	53 / 31	52 / 30
	Manufacturer		SWEP		
Plate heat exchanger	Water press. drop	kPa	26	26	26
	Piping connection	Inch	G1"	G1"	G1"
Allowable water flow	Min / Nominal	l/s	0,21 / 0,28	0,26 / 0,43	0,40 / 0,56
Residual current device and overvoltage protection		Required			
Power supply, grounded	V / Hz / A	400V/3N/3PH/50Hz or 230V/3PH/50Hz			
Electric heater heating, domestic hot water	kW	9 (3X3) / 0,5	9 (3X3) / 0,5	9 (3X3) / 0,5	
Refrigerant		R32			
Dimensions (W x H x D)	Outdoor unit	mm	1010 x 735 x 370	1165 x 885 x 370	1165 x 885 x 370
	Indoor unit	mm	600 x 1780 x 680		
Net weight	Outdoor unit	kg	67	80	85
	Indoor unit	kg	125		
Article number indoor/outdoor		120296 / 120290	120296 / 120291	120296 / 120292	

(1) Heating condition: water inlet/outlet temperature: 30°C/35°C, Ambient temperature: DB 7°C /WB 6°C
 (2) Heating condition: water inlet/outlet temperature: 40°C/45°C, Ambient temperature: DB 7°C /WB 6°C
 (3) Cooling condition: water inlet/outlet temperature: 12°C/7°C, Ambient temperature: DB 35°C /WB 34°C

ES ENERGY SAVE AB

Nitgatan 2, 441 38 Alingsås · Sweden

0046 322-790 50 · info@energysave.se · www.energysave.se

