



ALPHA product series is a great choice for commercial and business premises. DALI-controlled luminaire is a stylish choice that delivers low glare (UGR<19).

Flush-mounted luminaire can be installed to T-bar ceilings (595 x 595 mm) in new and renovated buildings. Serie is available in three different power categories and DALI-compatible options. Luminaire has a power efficiency of 135 lm/W and opening angle of 110 degrees.



LIGHTING INFORMATION

Power	25/30/36W
Luminous efficacy	135 lm/W
Total lumens	3375/4050/4860 lm
Glare index	<19
MacAdam	3
Service life	L80B50
Light control	DALI
Colour temperatures	4000 K, 5000 K

DIMENSIONS

Length	595 mm
Width	595 mm
Height	35 mm

LIGHT DISTRIBUTION



Opening angle: 110°

ALPHA

ELECTRICAL NO. (F)	PRODUCT CODE	TYPE	VOLTAGE	POWER INPUT	LIGHT SOURCE	IP CLASS	MOUNTING
4129507	ALPHA-25DA-600X600	Modular luminaire	230V	25W	LED	20	FLUSH/T-LIST
4129508	ALPHA-30DA-600X600	Modular luminaire	230V	30W	LED	20	FLUSH/T-LIST
4129509	ALPHA-36DA-600X600	Modular luminaire	230V	36W	LED	20	FLUSH/T-LIST