



TECHNICAL DATA SHEET

part number cable family

25969 O.R. FRX®

FORMATION: 4G10

4GAWG08

INSTALLATION TYPE: CABLE FOR DYNAMIC INSTALLATION ON DRAG CHAIN

CATEGORY: MULTI CORE

STANDARD/APPROVAL: CE/UL/CSA

SHIELDING: UNSHIELDED



GROUP // 4G10

CONDUCTOR

| | |
|--------------------|---|
| MATERIAL | Bare copper |
| CAPILLARY DIAMETER | - Extra-flexible (DIN VDE 0295, IEC 60228 or CEI 20-29) |
| CONDUCTORS NUMBER | 4 |
| RATED SECTION | 10 mm ² |

INTERNAL TAPING

| | |
|------------|---|
| ON MAKE-UP | Between conductor and insulation (optional) |
| MATERIAL | Transparent tape or Non-woven tape |

INSULATION

| | |
|----------|--|
| MATERIAL | PVC |
| COLOUR | Black conductors marked U/L1, V/L2, W/L3 + Green/Yellow |

TOTAL ASSEMBLY MAKE-UP

TE.CO. reserves the right to make some modifications to the products notwithstanding the basic technical characteristics. Unless otherwise stated, all indicated data are nominal. RAL colour is stated only as reference. TE.CO. Tecnologia Commerciale S.p.A. - Via Achille Grandi, 1 - 40013 Castel Maggiore (Bologna - Italia) - Tel +39 051 6047311 Web: www.tecoit.com - E-mail: sales@tecoit.com - Reg. Impr. Bologna e Codice Fiscale 03163100377 - P.IVA IT 01636081208. Subject to management and coordination activities handled by Pronos S.r.l.. All rights are reserved. The reproduction of any part of this document is not allowed without the written authorization of TE.CO. Tecnologia Commerciale S.p.A..

TOTAL TAPING

ON MAKE-UP AROUND the total assembly

MATERIAL Non-woven tape

TOTAL SHEATH

MATERIAL PVC

COLOUR Matte black RAL 9005

DIAMETER (MM) 17.9±0.4

MARKING

METRIC MARKING P/N 25969 TE.CO. E244280 - Fxx cRUus - AWM STYLE
2570 80°C 1000V VW-1 - AWM I/II A/B 80°C 1000V FT1 -
4GAWG08 - O.R. FRX® 4G10 - IEC 60332-1-2 - year/week -
CE meter indication

ELECTRICAL FEATURES

WORKING VOLTAGE 1000 V

TEST VOLTAGE 4000 V

DYNAMIC FEATURES

MINIMUM BENDING RADIUS STATIC INSTALLATION 4 times \varnothing cable

MINIMUM BENDING RADIUS DYNAMIC INSTALLATION 7.5 times \varnothing cable

WORKING TEMPERATURE STATIC INSTALLATION -40°C / +80°C

WORKING TEMPERATURE DYNAMIC INSTALLATION -5°C / +80°C

TRAVEL SPEED Up to 180 m/min

ACCELERATION/DECELERATION Up to 10 m/sec²

CABLE LENGTH INSIDE CHAIN Up to 10 m

CHAIN LENGTH NOTES (horizontal only)

GUARANTEED CYCLES Up to 5 Mio

NOTES The given data are meant to be restricted to the type of
reference installation. For fixed installation is meant to
be without any mechanical stress. For application in
dynamic installation with very low temperatures,
contact our technical department.

APPROVALS AND STANDARDS

| | |
|---------------------------|--|
| REFERENCE STANDARDS | 1581, UL 758(UL); C22.2 n° 210(CSA) |
| UL CSA APPROVALS | RU E244280 AWM STYLE 2570 80°C 1000V CSA E244280 AWM I/II A/B 80°C 1000V |
| FIRE BEHAVIOUR | VW-1(UL); FT1(CSA); IEC 60332-1-2(EU) |
| INDUSTRIAL OIL RESISTANCE | 1581(UL); IEC 60811-404(EU); CEI EN 50363-4-1(EU); IRM 902 |
| HALOGEN FREE | NO |
| UV RESISTANCE | UV RESISTANT |

CUSTOMS CODE

| | |
|-----------------------|----------|
| CUSTOMS-TARIFF NUMBER | 85444999 |
| MADE IN | IT |

REVISION

| | |
|--------|----------|
| DATE | 12042019 |
| NUMBER | 004 |

TE.CO. reserves the right to make some modifications to the products notwithstanding the basic technical characteristics. Unless otherwise stated, all indicated data are nominal. RAL colour is stated only as reference. TE.CO. Tecnologia Commerciale S.p.A. - Via Achille Grandi, 1 - 40013 Castel Maggiore (Bologna - Italia) - Tel +39 051 6047311 Web: www.tecoit.com - E-mail: sales@tecoit.com - Reg. Impr. Bologna e Codice Fiscale 03163100377 - P.IVA IT 01636081208. Subject to management and coordination activities handled by Pronos S.r.l.. All rights are reserved. The reproduction of any part of this document is not allowed without the written authorization of TE.CO. Tecnologia Commerciale S.p.A..