

## Start Highbay


START Highbay IP65 1-10V 26000lm 840 WB

0039349



### Product features

- START Highbay, includes 1 m cables, black aluminium housing, 26,000 Lm, 200 W, 130 Lm/W, 4000 K, drive current: 5000 mA, CRI 80, 90° beam angle, 1-10 V dimmable, IP65, IK08, 54,000 hrs (L80/B50), (D x H) 339 x 194 mm, 1 m mains cable, 1 m control cable, 1.2 m chain length including hooks



### NOTES

undefined

### PRODUCT OVERVIEW

Product name	START Highbay IP65 1-10V 26000lm 840 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
ETIM Class	EC001716
E-number FI	4306963
E-number SE	7214417
Warranty	5 years
Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	90
Glare control	< 25
Photobiological Risk Group	RG1
Total power consumption (W)	200
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
Minimum dimming level (%)	1
LED Flickering Rate	Ultra low (5% or less)
Housing colour	Black
IP rating	IP65
IK rating	IK08
Product EAN number	5410288393490

## Start Highbay

START Highbay IP65 1-10V 26000lm 840 WB

0039349

Dimming method	1-10V (Analogue)
----------------	------------------

### DATA TABLE

#### General data

Product name	START Highbay IP65 1-10V 26000lm 840 WB
Technology	LED
Housing	Aluminium
Mount	Suspended
General application	Logistics & Industry
Operating temperature range (°C)	-30°C - 50°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001716
E-number FI	4306963
E-number SE	7214417
Warranty	5 years

#### Optical data

Fixture luminous flux (lm)	26000
Luminaire efficacy (lm/W)	130
Colour temperature (K)	4000
Light colour	Neutral White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	90
Glare control	< 25
Photobiological Risk Group	RG1

#### Electrical data

Total power consumption (W)	200
Mains voltage (V)	220-240V
Lamp power factor	0.95
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	10
Electrical protection	Class I
Control gear type	Other
Dimmable	Yes
Minimum dimming level (%)	1
Drive current (mA)	5000
Inrush Current (A)	60
Inrush Duration (µs)	300
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Ultra low (5% or less)
Max. Luminaires per 10A C Breaker	6
Max. Luminaires per 13A C Breaker	8
Max. Luminaires per 16A C Breaker	9
Max. Luminaires per 20A C Breaker	10

## Start Highbay

START Highbay IP65 1-10V 26000lm 840 WB

0039349

Max. Luminaires per 10A B Breaker	3
Max. Luminaires per 13A B Breaker	4
Max. Luminaires per 16A B Breaker	5
Max. Luminaires per 20A B Breaker	7

### Lifetime data

Lifespan L70 B50	54000
Lifespan L70 B20	54000
Lifespan L70 B10	54000
Lifespan L80 B50	54000
Lifespan L80 B20	54000
Lifespan L80 B10	54000
Lifespan L90 B50	54000
Lifespan L90 B20	54000
Lifespan L90 B10	50000

### Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK08
Diffuser finish	Transparent
Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	339
Nominal Product Width (mm)	339
Nominal Product Height (mm)	194
Nominal Product Diameter (mm)	339
Weight (kg)	3.7

### Packaging









Single packaging type	Carton
Product EAN number	5410288393490
Packaging single length / height (cm)	40.0
Packaging single width (cm)	40.0
Packaging single depth (cm)	18.7
DUN14 (outer)	05410288393490
Units per outer package	1
Packaging outer length / height (cm)	40.0
Packaging outer width (cm)	40.0
Packaging outer depth (cm)	18.7

### Safety data

Optimal operating condition (°C)	-30-50
----------------------------------	--------

## PHOTOMETRY

## Start Highbay START Highbay IP65 1-10V 26000lm 840 WB 0039349



## Start Highbay

*START Highbay IP65 1-10V 26000lm 840 WB*

0039349

### TECHNICAL DRAWINGS

---

