

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name

Armaflex 520

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Adhesive for processing all flexible Armaflex insulation materials
For industrial and professional use only

Uses advised against

No data available.

1.3 Details of the supplier of the safety data sheet

Address

Armacell GmbH
Robert-Bosch-Straße 10
48153 Münster

Telephone no. +49 (0) 251 - 7603-200

Fax no. +49 (0) 251 - 7603-561

e-mail info.de@armacell.com

Information provided by / telephone

Dr. Heribert Quante, Tel.: +49 (0) 251 - 7603-227

Advice on Safety Data Sheet

heribert.quante@armacell.com

Address

Armacell UK Ltd
Mars Street
OL9 6LY Oldham
United Kingdom

email: info.armaform@armacell.com

1.4 Emergency telephone number

For medical advice (in German and English):

+49 (0)551 192 40 (Giftinformationszentrum Nord)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification in accordance with Regulation (EC) No 1272/2008 (CLP)

Aquatic Chronic 2; H411

Eye Irrit. 2; H319

Flam. Liq. 2; H225

STOT SE 3; H336

Classification information

This product is assessed and classified using the methods and criteria below referred to in Article 9 of Regulation (EC) n° 1272/2008:

Physical hazards: determined through assessment data based on the methods or standards referred to in part 2 of Annex I to CLP

Health hazards and environmental hazards: determined through toxicological and ecotoxicological assessment data based on the methods or standards referred to in Part 3, 4 and 5 of Annex I to CLP.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 (CLP Regulation)

Hazard pictograms



GHS02



GHS07



GHS09

Signal word

Danger

Hazardous component(s) to be indicated on label:

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
ethyl-acetate

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

acetone
butanone

Hazard statement(s)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Hazard statements (EU)

EUH066 Repeated exposure may cause skin dryness or cracking.
EUH208 Contains Rosin; colophony. May produce an allergic reaction.

Precautionary statement(s)

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours/spray.
P273 Avoid release to the environment.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 Call a POISON CENTER/doctor if you feel unwell.
P391 Collect spillage.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to a facility in accordance with local and national regulations.

2.3 Other hazards

Vapours can form an explosive mixture with air.
PBT assessment
The components of this product are not considered to be a PBT.
vPvB assessment
The components of this product are not considered to be a vPvB.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable. The product is not a substance.

3.2 Mixtures

Hazardous ingredients

No	Substance name		Additional information		%
	CAS / EC / Index / REACH no	Classification (EC) 1272/2008 (CLP)	Concentration		
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane				
	64742-49-0 926-605-8 - 01-2119486291-36	Aquatic Chronic 2; H411 Asp. Tox. 1; H304 Flam. Liq. 2; H225 STOT SE 3; H336 EUH066	>	25.00 - < 40.00	wt%
2	ethyl-acetate				
	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	EUH066 Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336		20.00 - < 25.00	wt%
3	acetone				
	67-64-1 200-662-2 606-001-00-8 01-2119471330-49	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		10.00 - < 20.00	wt%
4	butanone				
	78-93-3 201-159-0 606-002-00-3 01-2119457290-43	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066		1.00 - < 5.00	wt%
5	propan-2-ol				
	67-63-0 200-661-7 603-117-00-0 01-2119457558-25	Eye Irrit. 2; H319 Flam. Liq. 2; H225 STOT SE 3; H336		1.00 - < 2.50	wt%
6	Rosin; colophony				
	8050-09-7 232-475-7	Skin Sens. 1; H317		0.10 - < 1.00	wt%

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

650-015-00-7			
01-2119480418-32			

Full Text for all H-phrases and EUH-phrases: pls. see section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

In case of persisting adverse effects, consult a physician. Remove contaminated clothing and shoes immediately, and launder thoroughly before reusing.

After inhalation

When inhaled remove to fresh air and seek medical aid.

After skin contact

When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.

After eye contact

Remove contact lenses. Rinse eye thoroughly under running water keeping eyelids wide open and protecting the unaffected eye (at least 10 to 15 minutes). Get immediate ophthalmic treatment.

After ingestion

Do not induce vomiting. Rinse the mouth thoroughly with water. Never give anything by mouth to an unconscious person. Call a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

Headache; Dizziness; Drowsiness; Nausea; Vomiting; redness

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide; Dry chemical extinguisher; Foam; Water spray jet

Unsuitable extinguishing media

High power water jet

5.2 Special hazards arising from the substance or mixture

In the event of fire, the following can be released: Carbon dioxide (CO₂); Carbon monoxide (CO); Nitrogen oxides (NO_x); Hydrogen chloride (HCl); halogenated compounds

5.3 Advice for firefighters

Use self-contained breathing apparatus. Wear full protective suit. Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations. Containers close to fire should be transferred to a safe place.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Refer to protective measures listed in sections 7 and 8. Exclude sources of ignition and ventilate the area. Do not inhale vapours. Remove persons to safety. Ensure adequate ventilation.

For emergency responders

No data available. Personal protective equipment (PPE) - see Section 8.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater. Do not discharge into the subsoil/soil. In case of entry into waterways, soil or drains, inform the responsible authorities.

6.3 Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in container for disposal according to local regulations (see section 13).

6.4 Reference to other sections

Information regarding safe handling, see section 7. Information regarding personal protective measures, see section 8. Information regarding waste disposal, see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Advice on safe handling

Provide good ventilation at the work area (local exhaust ventilation, if necessary). Risks inherent to handling the product must be minimised by applying the appropriate protective and preventive measures. Working processes should - so far as possible, according to the state of the art - be designed to rule out bodily contact or the release of hazardous substances. If workplace exposure limits are exceeded, respiratory protection approved for this particular job must be worn. For personal protection see section 8.

General protective and hygiene measures

Do not eat, drink or smoke during work time. Keep away from foodstuffs and beverages. Wash hands before breaks and after work. Remove soiled or soaked clothing immediately. Avoid contact with eyes and skin. Do not inhale vapours. Provide eye wash fountain in work area. Have emergency shower available.

Advice on protection against fire and explosion

Keep away from sources of ignition - refrain from smoking. No sparking tools should be used. Vapours can form an explosive mixture with air. Take precautionary measures against electrostatic loading (earthing necessary during loading operations).

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions

Keep container tightly closed in a cool, well-ventilated place. Protect from heat and direct sunlight.

Requirements for storage rooms and vessels

Containers which are opened must be carefully closed and kept upright to prevent leakage. Always keep in containers of same material as the original.

Incompatible products

Substances to be avoided, see section 10.

7.3 Specific end use(s)

No data available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values

No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	2017/164/EU		
	Ethyl acetate		
	WEL short-term (15 min reference period)	1468	mg/m ³ 400 ppm
	WEL long-term (8-hr TWA reference period)	734	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Ethyl acetate		
	WEL short-term (15 min reference period)		400 ppm
	WEL long-term (8-hr TWA reference period)		200 ppm
2	acetone	67-64-1	200-662-2
	2000/39/EC		
	Acetone		
	WEL long-term (8-hr TWA reference period)	1210	mg/m ³ 500 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Acetone		
	WEL short-term (15 min reference period)	3620	mg/m ³ 1500 ppm
	WEL long-term (8-hr TWA reference period)	1210	mg/m ³ 500 ppm
3	butanone	78-93-3	201-159-0
	2000/39/EC		
	Butanone		
	WEL short-term (15 min reference period)	900	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
	List of approved workplace exposure limits (WELs) / EH40		
	Butan-2-one		
	WEL short-term (15 min reference period)	899	mg/m ³ 300 ppm
	WEL long-term (8-hr TWA reference period)	600	mg/m ³ 200 ppm
	Comments	Sk, BMGV	
4	propan-2-ol	67-63-0	200-661-7
	List of approved workplace exposure limits (WELs) / EH40		
	Propan-2-ol		
	WEL short-term (15 min reference period)	1250	mg/m ³ 500 ppm
	WEL long-term (8-hr TWA reference period)	999	mg/m ³ 400 ppm

DNEL, DMEL and PNEC values

DNEL values (worker)

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			64742-49-0 926-605-8	
	dermal	Long term (chronic)	systemic	13964	mg/kg/day
	inhalative	Long term (chronic)	systemic	5306	mg/m ³
2	ethyl-acetate			141-78-6 205-500-4	
	dermal	Long term (chronic)	systemic	63	mg/kg/day
	inhalative	Long term (chronic)	systemic	734	mg/m ³
	inhalative	Short term (acut)	systemic	1468	mg/m ³
	inhalative	Long term (chronic)	local	734	mg/m ³
	inhalative	Short term (acut)	local	1468	mg/m ³
3	acetone			67-64-1 200-662-2	
	dermal	Long term (chronic)	systemic	186	mg/kg/day
	inhalative	Short term (acut)	local	2420	mg/m ³
	inhalative	Short term (acut)	systemic	1210	mg/m ³
4	butanone			78-93-3 201-159-0	
	dermal	Long term (chronic)	systemic	1161	mg/kg/day
	inhalative	Long term (chronic)	systemic	600.00	mg/m ³
5	propan-2-ol			67-63-0 200-661-7	
	dermal	Long term (chronic)	systemic	888	mg/kg/day
	inhalative	Long term (chronic)	systemic	500	mg/m ³

DNEL value (consumer)

No	Substance name			CAS / EC no	
	Route of exposure	Exposure time	Effect	Value	
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			64742-49-0 926-605-8	
	oral	Long term (chronic)	systemic	1301	mg/kg/day
	dermal	Long term (chronic)	systemic	1377	mg/kg/day
	inhalative	Long term (chronic)	systemic	1131	mg/m ³
2	ethyl-acetate			141-78-6 205-500-4	
	oral	Long term (chronic)	systemic	4.5	mg/kg/day
	dermal	Long term (chronic)	systemic	37	mg/kg/day
	inhalative	Long term (chronic)	systemic	367	mg/m ³
	inhalative	Short term (acut)	systemic	734	mg/m ³
	inhalative	Long term (chronic)	local	367	mg/m ³
	inhalative	Short term (acut)	local	734	mg/m ³
3	acetone			67-64-1 200-662-2	
	oral	Long term (chronic)	systemic	62	mg/kg/day
	dermal	Long term (chronic)	systemic	62	mg/kg/day
	inhalative	Long term (chronic)	systemic	200	mg/m ³
4	butanone			78-93-3 201-159-0	
	oral	Long term (chronic)	systemic	31	mg/kg/day
	dermal	Long term (chronic)	systemic	412	mg/kg/day
	inhalative	Long term (chronic)	systemic	106	mg/m ³
5	propan-2-ol			67-63-0 200-661-7	
	oral	Long term (chronic)	systemic	26	mg/kg/day
	dermal	Long term (chronic)	systemic	319	mg/kg/day
	inhalative	Long term (chronic)	systemic	89	mg/m ³

PNEC values

No	Substance name		CAS / EC no	
	ecological compartment	Type	Value	
1	ethyl-acetate		141-78-6 205-500-4	
	water	fresh water	0.24	mg/L
	water	marine water	0.024	mg/L
	water	fresh water sediment	1.15	mg/kg dry weight
	water	marine water sediment	0.115	mg/kg dry weight
	soil	-	0.148	mg/kg dry weight

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

	sewage treatment plant	-	650	mg/L
	secondary poisoning	-	0.2	g/kg
	with reference to: food			
2	acetone		67-64-1 200-662-2	
	water	fresh water	10.6	mg/L
	water	Aqua intermittent	21	mg/L
	water	marine water	1.06	mg/L
	water	fresh water sediment	30.4	mg/kg
	water	marine water sediment	3.04	mg/kg
	soil	-	29.5	mg/kg
	sewage treatment plant	-	100	mg/L
3	butanone		78-93-3 201-159-0	
	water	fresh water	55.8	mg/L
	water	marine water	55.8	mg/L
	water	Aqua intermittent	55.8	mg/L
	water	fresh water sediment	284.74	mg/kg
	with reference to: dry weight			
	water	marine water sediment	284.7	mg/kg
	with reference to: dry weight			
	soil	-	22.5	mg/kg
	with reference to: dry weight			
	sewage treatment plant	-	709	mg/L
	secondary poisoning	-	1000	mg/kg
	with reference to: food			
4	propan-2-ol		67-63-0 200-661-7	
	water	fresh water	140.9	mg/L
	water	Aqua intermittent	140.9	mg/L
	water	marine water	140.9	mg/L
	water	fresh water sediment	552	mg/L
	water	marine water sediment	552	mg/L
	soil	-	28	mg/kg
	sewage treatment plant	-	2251	mg/L
	secondary poisoning	-	160	mg/kg
	with reference to: food			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, local exhaust at the work station if necessary.

Personal protective equipment

Respiratory protection

If workplace exposure limits are exceeded, a respiration protection approved for this particular job must be worn. In case of aerosol and mist formation, take appropriate measures for breathing protection in the event workplace threshold values are not specified.

Respirator AX

Eye / face protection

Tightly fitting safety glasses (EN 166).

Hand protection

Sufficient protection is given wearing suitable protective gloves checked according to i.e. EN 374, in the event of risk of skin contact with the product. Before use, the protective gloves should be tested in any case for its specific work-station suitability (i.e. mechanical resistance, product compatibility and antistatic properties). Adhere to the manufacturer's instructions and information relating to the use, storage, care and replacement of protective gloves. Protective gloves shall be replaced immediately when physically damaged or worn. Design operations thus to avoid permanent use of protective gloves.

Appropriate Material	butyl rubber		
Material thickness	>	0.7	mm
Inappropriate material	nitrile rubber		
Inappropriate material	PVC		
Inappropriate material	viton		
Inappropriate material	Natural rubber, NR		

Other

Fire-resistant antistatic protective clothing.

Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

9.1 Information on basic physical and chemical properties

State of aggregation			
liquid			
Form/Colour			
liquid			
beige			
Odour			
like solvents			
pH value			
No data available			
Boiling point / boiling range			
Value		55	°C
Source	supplier		
Melting point/freezing point			
No data available			
Decomposition temperature			
No data available			
Flash point			
Value		-15	°C
Source	supplier		
Ignition temperature			
No data available			
Auto-ignition temperature			
Value		235	°C
Source	supplier		
Flammability			
Not applicable			
Source	supplier		
Lower explosion limit			
Value		1	% vol
Source	supplier		
Upper explosion limit			
Value		20	% vol
Source	supplier		
Vapour pressure			
No data available			
Relative vapour density			
No data available			
Relative density			
Value		0.85	
Source	supplier		
Density			
No data available			
Solubility in water			
Source	supplier		
Comments	immiscible		
Solubility			
No data available			
Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	log Pow		0.68
	Reference temperature		25 °C
	Source	ECHA	
2	acetone	67-64-1	200-662-2
	log Pow		-0.23
	Method	QSAR	
	Source	ECHA	

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

3	butanone	78-93-3	201-159-0
log Pow		0.3	
Reference temperature		40	°C
Method	OECD 117		
Source	ECHA		
4	propan-2-ol	67-63-0	200-661-7
log Pow		0.05	
Reference temperature		25	°C
Source	ECHA		
Viscosity			
Value	>	1000	mm ² /s
Reference temperature		40	°C
Type	kinematic		
Source	supplier		
Particle characteristics			
No data available			

9.2 Other information

Other information
VOC: 78 %

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available.

10.2 Chemical stability

Stable under recommended storage and handling conditions (See section 7).

10.3 Possibility of hazardous reactions

None, when used as directed.

10.4 Conditions to avoid

Heat, naked flames and other ignition sources.

10.5 Incompatible materials

No data available.

10.6 Hazardous decomposition products

None if stored, handled and transported properly. In case of fire: see section 5.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
LD50		>	5600 mg/kg bodyweight
Species	rat		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50		5800	mg/kg bodyweight
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	butanone	78-93-3	201-159-0
LD50		2054	mg/kg bodyweight
Species	rat		
Method	OECD 423		
Source	ECHA / Read across		
4	propan-2-ol	67-63-0	200-661-7
LD50		5840	mg/kg bodyweight
Species	rat		
Method	OECD 401		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Acute dermal toxicity			
No	Substance name	CAS no.	EC no.

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

1	ethyl-acetate	141-78-6	205-500-4
LD50	>	20000	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
2	acetone	67-64-1	200-662-2
LD50	>	15800	mg/kg bodyweight
Species	rabbit		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Acute inhalational toxicity			
No	Substance name	CAS no.	EC no.
1	acetone	67-64-1	200-662-2
LC50	>	76	mg/l
Duration of exposure		4	h
State of aggregation	Vapour		
Species	rat		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	propan-2-ol	67-63-0	200-661-7
LC50	>	10000	ppmV
Duration of exposure		6	h
State of aggregation	Vapour		
Species	rat		
Method	OECD 403		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Skin corrosion/irritation			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	non-irritant		
2	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 404		
Source	ECHA		
Evaluation	low-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	acetone	67-64-1	200-662-2
Species	guinea pig		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	butanone	78-93-3	201-159-0
Duration of exposure		4	h
Species	rabbit		
Method	OECD 404		
Source	ECHA / Read across		
Evaluation	non-irritant		
5	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Source	ECHA		
Evaluation	non-irritant		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Serious eye damage/irritation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	low-irritant		
2	acetone	67-64-1	200-662-2
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

3	butanone	78-93-3	201-159-0
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
4	propan-2-ol	67-63-0	200-661-7
Species	rabbit		
Method	OECD 405		
Source	ECHA		
Evaluation	irritant		
Evaluation/classification	Based on available data, the classification criteria are met.		
Respiratory or skin sensitisation			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
2	acetone	67-64-1	200-662-2
Route of exposure	Skin		
Species	guinea pig		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	butanone	78-93-3	201-159-0
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
4	propan-2-ol	67-63-0	200-661-7
Route of exposure	Skin		
Species	guinea pig		
Method	OECD 406		
Source	ECHA		
Evaluation	non-sensitizing		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Germ cell mutagenicity			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Source	ECHA / Read across		
Evaluation/classification	Based on available data, the classification criteria are not met.		
2	acetone	67-64-1	200-662-2
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	Chinese hamster Ovary (CHO)		
Method	OECD 473		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	in vitro gene mutation study in mammalian cells		
Species	Mouse lymphoma cells		
Method	OECD 476		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
3	butanone	78-93-3	201-159-0
Type of examination	in vitro gene mutation study in bacteria		
Species	Salmonella typhimurium		
Method	OECD 471		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
Type of examination	In vitro Mammalian Chromosomal Aberration Test		
Species	rat		
Method	OECD 473		

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vitro mammalian cell gene mutation test
Species	Mouse lymphoma cells
Method	OECD 476
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.
Type of examination	In vivo mammalian somatic cell study: cytogenicity / erythrocyte micronucleus
Species	mouse
Method	OECD 474
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

4	propan-2-ol	67-63-0	200-661-7
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		

Reproduction toxicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

2	acetone	67-64-1	200-662-2
----------	----------------	----------------	------------------

Route of exposure	inhalational
NOAEC	2200 ppm
Type of examination	Prenatal Developmental Toxicity Study
Species	rat
Method	OECD 414
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

3	butanone	78-93-3	201-159-0
----------	-----------------	----------------	------------------

Route of exposure	inhalational
Type of examination	Prenatal Developmental Toxicity Study
Species	rat
Method	OECD 414
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Carcinogenicity

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

2	acetone	67-64-1	200-662-2
----------	----------------	----------------	------------------

Route of exposure	dermal
Type of examination	Toxicity study
Species	mouse
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

3	butanone	78-93-3	201-159-0
----------	-----------------	----------------	------------------

Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

STOT - single exposure

No data available

STOT - repeated exposure

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8

Source	ECHA / Read across
Evaluation/classification	Based on available data, the classification criteria are not met.

2	acetone	67-64-1	200-662-2
----------	----------------	----------------	------------------

Route of exposure	oral
NOAEL	10000 ppm
Species	rat
Method	OECD 408
Source	ECHA
Evaluation/classification	Based on available data, the classification criteria are not met.

Route of exposure	inhalational
-------------------	--------------

NOAEC	19000 ppm
Species	rat
Source	ECHA

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Evaluation/classification	Based on available data, the classification criteria are not met.	
3 butanone	78-93-3	201-159-0
Route of exposure	inhalational	
Species	rat	
Method	OECD 413	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	
4 propan-2-ol	67-63-0	200-661-7
Route of exposure	inhalational	
Source	ECHA	
Evaluation/classification	Based on available data, the classification criteria are not met.	

Aspiration hazard
Based on available data, the classification criteria are not met.

11.2 Information on other hazards

Endocrine disrupting properties

No data available.

Other information

No data available.

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish (acute)			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
LL50		12	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Method	OECD 203		
Source	ECHA		
2	ethyl-acetate	141-78-6	205-500-4
LC50		220	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Source	ECHA		
3	acetone	67-64-1	200-662-2
LC50		5540	mg/l
Duration of exposure		96	h
Species	Oncorhynchus mykiss		
Source	ECHA		
Evaluation/classification	Based on available data, the classification criteria are not met.		
4	butanone	78-93-3	201-159-0
LC50		2993	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		
5	propan-2-ol	67-63-0	200-661-7
LC50		9640	mg/l
Duration of exposure		96	h
Species	Pimephales promelas		
Method	OECD 203		
Source	ECHA		

Toxicity to fish (chronic)
No data available

Toxicity to Daphnia (acute)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
EC50		1350	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Source	ECHA		
2	acetone	67-64-1	200-662-2
EC50		8800	mg/l
Duration of exposure		48	h
Species	Daphnia pulex		

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Source Evaluation/classification	ECHA Based on available data, the classification criteria are not met.		
3	butanone	78-93-3	201-159-0
EC50		308	mg/l
Duration of exposure		48	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		
4	propan-2-ol	67-63-0	200-661-7
EC50	>	10000	mg/l
Duration of exposure		24	h
Species	Daphnia magna		
Method	OECD 202		
Source	ECHA		

Toxicity to Daphnia (chronic)

No data available

Toxicity to algae (acute)

No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
EL50		26	mg/l
Duration of exposure		72	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		
2	butanone	78-93-3	201-159-0
EC50		2029	mg/l
Duration of exposure		96	h
Species	Pseudokirchneriella subcapitata		
Method	OECD 201		
Source	ECHA		

Toxicity to algae (chronic)

No data available

Bacteria toxicity

No data available

12.2 Persistence and degradability

Biodegradability			
No	Substance name	CAS no.	EC no.
1	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	64742-49-0	926-605-8
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 F		
Source	ECHA		
Evaluation	readily biodegradable		
2	ethyl-acetate	141-78-6	205-500-4
Type	COD		
Value		1.69	g O2/g
Source	ECHA		
Evaluation	readily biodegradable		
3	acetone	67-64-1	200-662-2
Type	aerobic biodegradation		
Value		90.9	%
Duration		28	day(s)
Method	OECD 301 B		
Source	ECHA		
Evaluation	readily biodegradable		
4	butanone	78-93-3	201-159-0
Type	aerobic biodegradation		
Value		98	%
Duration		28	day(s)
Method	OECD 301 D		
Source	ECHA		
Evaluation	readily biodegradable		
5	propan-2-ol	67-63-0	200-661-7
Type	BOD/COD		
Value		53	%

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Duration	5	day(s)
Source	ECHA	
Evaluation	readily biodegradable	

12.3 Bioaccumulative potential

Partition coefficient n-octanol/water (log value)			
No	Substance name	CAS no.	EC no.
1	ethyl-acetate	141-78-6	205-500-4
	log Pow	0.68	
	Reference temperature	25	°C
	Source	ECHA	
2	acetone	67-64-1	200-662-2
	log Pow	-0.23	
	Method	QSAR	
	Source	ECHA	
3	butanone	78-93-3	201-159-0
	log Pow	0.3	
	Reference temperature	40	°C
	Method	OECD 117	
	Source	ECHA	
4	propan-2-ol	67-63-0	200-661-7
	log Pow	0.05	
	Reference temperature	25	°C
	Source	ECHA	

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

Results of PBT and vPvB assessment	
PBT assessment	The components of this product are not considered to be a PBT.
vPvB assessment	The components of this product are not considered to be a vPvB.

12.6 Endocrine disrupting properties

No data available.

12.7 Other adverse effects

No data available.

12.8 Other information

Other information
Do not discharge into drains or waters and do not dispose of in public landfills.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Waste code 08 04 09* waste adhesives and sealants containing organic solvents or other hazardous substances

Allocation of a waste code number, according to the European Waste Catalogue, should be carried out in agreement with the regional waste disposal company.

dispose of in accordance with local regulation.

Packaging

Waste code 15 01 10* packaging containing residues of or contaminated by hazardous substances

Residues must be removed from packaging and when emptied completely disposed of in accordance with the regulations for waste removal. Incompletely emptied packaging must be disposed of in the form of disposal specified by the regional disposer.

SECTION 14: Transport information

14.1 Transport ADR/RID/ADN

Class	3
Classification code	F1
Packing group	II
Hazard identification no.	33
UN number	UN1133
Proper shipping name	ADHESIVES
Special Provision 640	640D
Tunnel restriction code	D/E
Label	3
Environmentally hazardous	Symbol "fish and tree"

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

substance mark

14.2 Transport IMDG

Class	3
Packing group	II
UN number	UN1133
Proper shipping name	ADHESIVES
Technical name	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
EmS	F-E, S-D
Label	3
Marine pollutant mark	Symbol "fish and tree"

14.3 Transport ICAO-TI / IATA

Class	3
Packing group	II
UN number	UN1133
Proper shipping name	Adhesives
Label	3

14.4 Other information

No data available.

14.5 Environmental hazards

Information on environmental hazards, if relevant, please see 14.1 - 14.3.

14.6 Special precautions for user

To be transported always in closed, upright and safe containers. Make sure that persons handling these containers are aware of the rules of conduct in case of incident or spillage.

14.7 Maritime transport in bulk according to IMO instruments

Not relevant

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No 1907/2006 (REACH) Annex XIV (List of substances subject to authorisation)

According to the data available and/or specifications supplied by upstream suppliers, this product does not contain any substances considered as substances requiring authorisation as listed on Annex XIV of the REACH regulation (EC) 1907/2006.

REACH candidate list of substances of very high concern (SVHC) for authorisation

According to available data and the information provided by preliminary suppliers, the product does not contain substances that are considered substances meeting the criteria for inclusion in annex XIV (List of Substances Subject to Authorisation) as laid down in Article 57 and article 59 of REACH (EC) 1907/2006.

Regulation (EC) No 1907/2006 (REACH) Annex XVII: RESTRICTIONS ON THE MANUFACTURE, PLACING ON THE MARKET AND USE OF CERTAIN DANGEROUS SUBSTANCES, MIXTURES AND ARTICLES

The product is considered being subject to REACH regulation (EC) 1907/2006 annex XVII. No 3, 40

The product contains following substance(s) that are considered being subject to REACH regulation (EC) 1907/2006 annex XVII.

No	Substance name	CAS no.	EC no.	No
1	acetone	67-64-1	200-662-2	75
2	butanone	78-93-3	201-159-0	75
3	ethyl-acetate	141-78-6	205-500-4	75
4	propan-2-ol	67-63-0	200-661-7	75
5	Rosin; colophony	8050-09-7	232-475-7	75
6	Talc	14807-96-6	238-877-9	75

Directive 2012/18/EU on the control of major-accident hazards involving dangerous substances

This product is subject to Part I of Annex I, risk category: E2, P5b

If the properties of the substance/product give rise to more than one classification, for the purposes of 2012/18/UE, the lowest qualifying quantities set out in Part 1 and Part 2 of Annex I shall apply.

Directive 2010/75/EU on industrial emissions (integrated pollution prevention and control)

VOC content 78 %

15.2 Chemical safety assessment

A chemical safety assessment has not been carried out for this mixture.

SECTION 16: Other information

Further information

Trade name: Armaflex 520

Current version : 13.0.0, issued: 31.03.2022

Replaced version: 12.0.0, issued: 27.01.2022

Region: GB

Authors responsible for the compilation of the material safety data sheet: UMCO GmbH - D-21107 Hamburg, Georg-Wilhelm-Strasse 187, Tel.: +49(40)555 546 300, Fax: +49(40)555 546 357, e-mail: umco@umco.de.

The information is based on our current knowledge however it does not represent a guarantee of product properties nor does it create any legal obligation.

Sources of key data used to compile the data sheet:

Regulation (EC) No 1907/2006 (REACH), 1272/2008 (CLP) as amended in each case.

Directives 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164.

National Threshold Limit Values of the corresponding countries as amended in each case.

Transport regulations according to ADR, RID, IMDG, IATA as amended in each case.

The data sources used to determine physical, toxic and ecotoxic data, are indicated directly in the corresponding section.

Full text of the H- and EUH- phrases drawn up in sections 2 and 3 (provided not already drawn up in these sections)

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

Alterations/supplements:

Alterations to the previous edition are marked in the left-hand margin.

Document protected by copyright. Alterations or reproductions require the express written permission of UMCO GmbH.

Prod-ID 636618