

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 03/10/2023 Revision date: 02/10/2023 Supersedes version of: 22/08/2022 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	: SP 400
UFI	: WXWX-F82K-900X-GGRP
Product code	: BDS002387AE
Vaporizer	: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Use of the substance/mixture : Professional use : Anti Corrosion Products

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Supplier

CRC Industries Europe B.V. Touwslagerstraat 1 9240 Zele Belgium T +32(0)52/45.60.11 - F +32(0)52/45.00.34 hse@crcind.com - www.crcind.com

1.4. Emergency telephone number

Emergency number

: +32(0)52/45.60.11 Office hours: 9-17h CET

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Brussels	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1	H222;H229
Skin corrosion/irritation, Category 2	H315
Specific target organ toxicity – Single exposure, Category 3,	H336
Narcosis	
Hazardous to the aquatic environment – Chronic Hazard,	H412
Category 3	
Full text of H- and EUH-statements: see section 16	

Adverse physicochemical, human health and environmental effects

Pressurised container: May burst if heated. Extremely flammable aerosol. May cause drowsiness or dizziness. Causes skin irritation. Harmful to aquatic life with long lasting effects.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]		
Hazard pictograms (CLP)	GHS02 GHS07	
Signal word (CLP)	: Danger	
Contains	 Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; 1-methoxy-2-propanol; monopropylene glycol methyl ether 	
Hazard statements (CLP)	 H222 - Extremely flammable aerosol. H229 - Pressurised container: May burst if heated. H315 - Causes skin irritation. H336 - May cause drowsiness or dizziness. H412 - Harmful to aquatic life with long lasting effects. 	
Precautionary statements (CLP)	 P102 - Keep out of reach of children. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 - Do not spray on an open flame or other ignition source. P251 - Do not pierce or burn, even after use. P261 - Avoid breathing vapours/spray. P271 - Use only outdoors or in a well-ventilated area. P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C. P501 - Dispose of contents/container to a hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. 	

2.3. Other hazards

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	EC-No.: 919-857-5 REACH-no: 01-2119463258- 33	25 – 50	Flam. Liq. 3, H226 STOT SE 3, H336 Asp. Tox. 1, H304 EUH066
propane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
butane (Propellant gas (Aerosol)) substance with national workplace exposure limit(s) (BE)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	10 – 25	Flam. Gas 1, H220 Press. Gas (Liq.), H280
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	EC-No.: 921-024-6 REACH-no: 01-2119475514- 35	5 – 10	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
1-methoxy-2-propanol; monopropylene glycol methyl ether substance with national workplace exposure limit(s) (BE); substance with a Community workplace exposure limit	CAS-No.: 107-98-2 EC-No.: 203-539-1 EC Index-No.: 603-064-00-3 REACH-no: 01-2119457435- 35	1 – 5	Flam. Liq. 3, H226 STOT SE 3, H336

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures		
4.1. Description of first aid measures		
First-aid measures general	: Call a poison center or a doctor if you feel unwell. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If signs/symptoms develop, get medical attention.	
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention. Seek medical attention if irritation develops.	
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Seek medical attention if irritation develops.	
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.	
4.2. Most important symptoms and effects, both acute and delayed		
Symptoms/effects	: May cause drowsiness or dizziness.	
Symptoms/effects after skin contact	: Irritation. Repeated exposure may cause skin dryness or cracking.	
4.3. Indication of any immediate medical attention and special treatment needed		

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media Unsuitable extinguishing media	Water spray. Dry powder. Foam. Carbon dioxide.Do not use a heavy water stream.	
5.2. Special hazards arising from the substance or mixture		
Fire hazard Explosion hazard Hazardous decomposition products in case of fire	 Extremely flammable aerosol. Pressurised container: May burst if heated. During fire, gases hazardous to health may be formed. 	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5.3. Advice for firefighters	
Firefighting instructions	: Move containers from fire area if it can be done without personal risk. Use standard firefighting procedures and consider the hazards of other involved materials.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures		
6.1. Personal precautions, protective equipment and emergency procedures		
6.1.1. For non-emergency personnel		
Protective equipment	: Wear appropriate protective equipment and clothing during clean-up.	
Emergency procedures	 Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. 	
6.1.2. For emergency responders		
Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".	
Emergency procedures	: Evacuate unnecessary personnel. Ventilate area.	

6.2. Environmental precautions

Avoid release to the environment. Avoid the spillage or runoff entering drains, sewers or watercourses.

6.3. Methods and material for containment and cleaning up		
Methods for cleaning up	: Mechanically recover the product. For large spills, confine the spill in a dike and charge it with wet sand or earth for subsequent safe disposal. Following product recovery, flush area with water. Take up small spills with dry chemical absorbent. Clean surface thoroughly to remove residual contamination.	
Other information	: Dispose of materials or solid residues at an authorized site.	

6.4. Reference to other sections

For disposal of contaminated materials refer to section 13 : "Disposal considerations".

SECTION 7: Handling and storage		
7.1. Precautions for safe handling		
Precautions for safe handling	: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid prolonged exposure. Handle in accordance with good industrial hygiene and safety procedures.	
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.	
7.2. Conditions for safe storage, including any incompatibilities		
Storage conditions	: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store locked up. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Keep container closed when not in use.	

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2)		
EU - Indicative Occupational Exposure Limit (IOEL)		
Local name	1-Methoxypropanol-2	
IOEL TWA	375 mg/m³	
IOEL TWA [ppm]	100 ppm	
IOEL STEL	568 mg/m³	
IOEL STEL [ppm]	150 ppm	
Remark	Skin	
Regulatory reference	COMMISSION DIRECTIVE 2000/39/EC	
Belgium - Occupational Exposure Limits		
Local name	1-Méthoxy-2-propanol # 1-Methoxy-2-propanol	
OEL TWA	184 mg/m³	
OEL TWA [ppm]	50 ppm	
OEL STEL	369 mg/m³	
OEL STEL [ppm]	100 ppm	
Remark	D: la mention "D" signifie que la résorption de l'agent, via la peau, les muqueuses ou les yeux, constitue une partie importante de l'exposition totale. Cette résorption peut se faire tant par contact direct que par présence de l'agent dans l'air. # D: de vermelding "D" betekent dat de opname van het agens via de huid, de slijmvliezen of de ogen een belangrijk deel van de totale blootstelling vormt. Deze opname kan het gevolg zijn van zowel direct contact als zijn aanwezigheid in de lucht.	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
propane (74-98-6)		
Belgium - Occupational Exposure Limits		
Local name	Hydrocarbures aliphatiques sous forme gazeuse: (Alcanes C1-C3) # Alifatische koolwaterstoffen in gas-vorm: Alkanen (C1-C3)	
OEL TWA [ppm]	1000 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
isobutane (75-28-5)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: iso-butane # Butaan, alle isomeren: iso-butaan	
OEL STEL	2370 mg/m³	
OEL STEL [ppm]	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
butane (106-97-8)		
Belgium - Occupational Exposure Limits		
Local name	Butane, tous isomères: n-butane # Butaan, alle isomeren: n-butaan	
OEL STEL	2370 mg/m³	
OEL STEL [ppm]	980 ppm	
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021	
8.1.2. Percommanded manitoring procedures		

8.1.2. Recommended monitoring procedures

No additional information available

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Hydrocarbons, C9-C11, n-alkanes, isoalkanes	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	208 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	871 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	125 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	185 mg/m³	
Long-term - systemic effects, dermal	125 mg/kg bodyweight/day	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	cyclics, <5% n-hexane	
DNEL/DMEL (Workers)		
Long-term - systemic effects, dermal	773 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	2035 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	699 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	608 mg/m³	
Long-term - systemic effects, dermal	699 mg/kg bodyweight/day	
1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)	
DNEL/DMEL (Workers)		
Acute - systemic effects, inhalation	553,5 mg/m³	
Acute - local effects, inhalation	553,5 mg/m³	
Long-term - systemic effects, dermal	183 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	369 mg/m³	
DNEL/DMEL (General population)		
Long-term - systemic effects,oral	33 mg/kg bodyweight/day	
Long-term - systemic effects, inhalation	43,9 mg/m³	
Long-term - systemic effects, dermal	78 mg/kg bodyweight/day	
PNEC (Water)		
PNEC aqua (freshwater)	10 mg/l	
PNEC aqua (marine water)	1 mg/l	
PNEC aqua (intermittent, freshwater)	100 mg/l	
PNEC (Sediment)		
PNEC sediment (freshwater)	52,3 mg/kg dwt	
PNEC sediment (marine water)	5,2 mg/kg dwt	
PNEC (Soil)		
PNEC soil	4,59 mg/kg dwt	
PNEC (STP)		
PNEC sewage treatment plant	100 mg/l	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Use eye protection according to EN 166. Safety glasses with side shields.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Wear suitable gloves tested to EN374. The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Nitrile gloves are recommended.

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Approved organic vapour respirator. Filter type: AX

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not expected to present a significant hazard under anticipated conditions of normal use. Wear appropriate thermal protective clothing, when necessary.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: amber.
Appearance	: Propane/butane propelled liquid.
Odour	: characteristic.
Odour threshold	: Not available
Melting point	: Not applicable
Freezing point	: Not available
Boiling point	: 50 – 230 °C
Flammability	: Extremely flammable aerosol.
Explosive properties	: Pressurised container: May burst if heated.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: -35 °C

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Auto-ignition temperature Decomposition temperature pH Viscosity, kinematic	 200 °C Not available Not applicable 57,803 mm²/s
Viscosity, dynamic Solubility Partition coefficient n-octanol/water (Log Kow) Vapour pressure	: 50 mPa⋅s at 20 °C : Not available : Not applicable : Not available
Vapour pressure at 50°C Density Relative density Relative vapour density at 20°C Particle characteristics	 Not available Not available 0,865 g/cm³ at 20 °C 0,865 at 20 °C Not available Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes		
% of flammable ingredients	: 75 – 100 %	
9.2.2. Other safety characteristics		
VOC content	: 530 g/l	
Additional information	: For aerosols data for the product without propellant.	

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable aerosol. Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Strong oxidizing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced. Carbon oxides (CO, CO2).

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) Acute toxicity (dermal) Acute toxicity (inhalation)	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
I D50 oral rat	> 5000 mg/kg

LD50 oral rat	5841 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
LD50 dermal rabbit	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LD50 oral rat	> 5000 mg/kg

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	
LD50 dermal rat	2800 – 3100 mg/kg bodyweight
LC50 Inhalation - Rat	> 25,2 mg/l/4h
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)
LD50 oral rat	4016 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 Inhalation - Rat	> 25,8 mg/l
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	pH: Not applicable : Not classified (Based on available data, the classification criteria are not met) pH: Not applicable
Respiratory or skin sensitisation	: Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity	: Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity Reproductive toxicity	 Not classified (Based on available data, the classification criteria are not met) Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure	: May cause drowsiness or dizziness.
Hydrocarbons, C9-C11, n-alkanes, isoa	Ikanes, cyclics, < 2% aromatics
STOT-single exposure	May cause drowsiness or dizziness.
Hydrocarbons, C6-C7, n-alkanes, isoalk	anes, cyclics, <5% n-hexane
STOT-single exposure	May cause drowsiness or dizziness.
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)
STOT-single exposure	May cause drowsiness or dizziness.
STOT-repeated exposure	: Not classified (Based on available data, the classification criteria are not met)
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)
LOAEL (oral, rat, 90 days)	2757 mg/kg bodyweight
NOAEL (oral, rat, 90 days)	919 mg/kg bodyweight
NOAEL (dermal, rat/rabbit, 90 days)	> 1000 mg/kg bodyweight
Aspiration hazard	: Not classified (Based on available data, the classification criteria are not met)
SP 400	
Vaporizer	Aerosol
Viscosity, kinematic	57,803 mm²/s
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics	
Viscosity, kinematic	1,33 mm²/s
Hydrocarbons, C6-C7, n-alkanes, isoalk	anes, cyclics, <5% n-hexane
Viscosity, kinematic	0,7 mm²/s
1-methoxy-2-propanol; monopropylene	glycol methyl ether (107-98-2)
Viscosity, kinematic	1,848 mm²/s

Safety Data Sheet

11.2. Information on other hazards

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

11.2.1. Endocrine disrupting properties	
Adverse health effects caused by endocrine disrupting properties	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

No additional information available

cology - general tazardous to the aquatic environment, short-term acute) Harmful to aquatic life with long lasting effects. Not classified tazardous to the aquatic environment, long-term schronic) Harmful to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Harmful to aquatic life with long lasting effects. Vior rapidly degradable Harmful to aquatic life with long lasting effects. Hydrocarbons, C9-C11, n-alkanes, isoalkanes-cyclics, < 2% aromatics Harmful to aquatic life with long lasting effects. LC50 - Fish [1] > 1000 mg/l EC50 - Crustacea [1] > 1000 mg/l EC50 - Crustacea [1] > 1000 mg/l Hydrocarbons, C6-C7, n-alkanes, isoalkanes-cyclics, <5% n-hexane Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 11,4 mg/l Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 11,4 mg/l Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 10 mg/l Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 10 mg/l Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 0.32 mg/l Interview of the aquatic life with long lasting effects. LC50 - Fish [1] 10 mg/l Interview of the aquatic life	SECTION 12: Ecological information	SECTION 12: Ecological information		
tazardous to the aquatic environment, ison-term Not classified tazardous to the aquatic environment, isong-term Harmful to aquatic life with long lasting effects. whoreighty degradable Harmful to aquatic life with long lasting effects. Hydrocarbons, C9-C11, n-alkanes, isoalkames, cyclics, < 2% aromatics	12.1. Toxicity			
LCS0 - Fish [1] > 1000 mg/l ECS0 - Crustacea [1] > 1000 mg/l ECS0 - Other aquatic organisms [1] > 1000 mg/l ECS0 72h - Algae [1] > 1000 mg/l Hydrocarbons, C6-C7, n-alkanes, isoalkanes, :solakanes, :solakane, :solakanes, :solaka	Hazardous to the aquatic environment, short-term : (acute)	Not classified		
EC50 - Crustacea [1] > 1000 mg/l EC50 - Other aquatic organisms [1] > 1000 mg/l EC50 72h - Algae [1] > 1000 mg/l Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Hydrocarbons, C9-C11, n-alkanes, isoalkanes	s, cyclics, < 2% aromatics		
EC50 - Other aquatic organisms [1] > 1000 mg/l EC50 72h - Algae [1] > 1000 mg/l Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LC50 - Fish [1]	> 1000 mg/l		
EC50 72h - Algae [1] > 1000 mg/l Hydrocarbons, C6-C7, n-alkanes, isoalkanes, volics, <5% n-hexane	EC50 - Crustacea [1]	> 1000 mg/l		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane LC50 - Fish [1] 11,4 mg/l EC50 - Crustacea [1] 3 mg/l EC50 72h - Algae [1] 10 mg/l LOEC (chronic) 0,32 mg/l NOEC (chronic) 0,17 mg/l NOEC chronic fish 2,04 mg/l NOEC chronic rustacea 1 mg/l EC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	EC50 - Other aquatic organisms [1]	> 1000 mg/l		
LC50 - Fish [1] 11,4 mg/l LC50 - Crustacea [1] 3 mg/l EC50 72h - Algae [1] 10 mg/l LCEC (chronic) 0,32 mg/l LOEC (chronic) 0,17 mg/l NOEC (chronic) 2,04 mg/l NOEC chronic fish 2,04 mg/l NOEC chronic rustacea 1 mg/l Inethoxy-2-propanol; monopropylene glyc wthyl ether (107-98-2) LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Crustacea [1] 2954 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l It-22. Persistence and degradability >1000 mg/l	EC50 72h - Algae [1]	> 1000 mg/l		
EC50 - Crustacea [1] 3 mg/l EC50 72h - Algae [1] 10 mg/l LOEC (chronic) 0,32 mg/l NOEC (chronic) 0,17 mg/l NOEC chronic fish 2,04 mg/l NOEC chronic rustacea 1 mg/l 1 methoxy-2-propanol; monopropylene glycu methyl ether (107-98-2) LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l It 22. Persistence and degradability 1000 mg/l	Hydrocarbons, C6-C7, n-alkanes, isoalkanes,	cyclics, <5% n-hexane		
EC50 72h - Algae [1] 10 mg/l LOEC (chronic) 0,32 mg/l NOEC (chronic) 0,17 mg/l NOEC chronic fish 2,04 mg/l NOEC chronic rustacea 1 mg/l 1 methoxy-2-propanol; monopropylene glycur thyl ether (107-98-2) 6812 mg/l LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l EC50 algae 1000 mg/l	LC50 - Fish [1]	11,4 mg/l		
LOEC (chronic)0,32 mg/lNOEC (chronic)0,17 mg/lNOEC chronic fish2,04 mg/lNOEC chronic crustacea1 mg/l1-methoxy-2-propanol; monopropylene glyctether (107-98-2)LC50 - Fish [1]6812 mg/lLC50 - Fish [2]20800 mg/lEC50 - Crustacea [1]21100 – 25900 mg/lEC50 - Other aquatic organisms [1]954 mg/lEC50 algae1000 mg/l	EC50 - Crustacea [1]	3 mg/l		
NOEC (chronic) 0,17 mg/l NOEC chronic fish 2,04 mg/l NOEC chronic crustacea 1 mg/l 1-methoxy-2-propanol; monopropylene glyc tether (107-98-2) LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l EC50 algae > 1000 mg/l	EC50 72h - Algae [1]	10 mg/l		
NOEC chronic fish 2,04 mg/l NOEC chronic crustacea 1 mg/l 1-methoxy-2-propanol; monopropylene glyco/methyl ether (107-98-2) 6812 mg/l LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l EC50 algae > 1000 mg/l	LOEC (chronic)	0,32 mg/l		
NOEC chronic crustacea 1 mg/l 1-methoxy-2-propanol; monopropylene glyco methyl ether (107-98-2) LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	NOEC (chronic)	0,17 mg/l		
1-methoxy-2-propanol; monopropylene glycol methyl ether (107-98-2) LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	NOEC chronic fish	2,04 mg/l		
LC50 - Fish [1] 6812 mg/l LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	NOEC chronic crustacea	1 mg/l		
LC50 - Fish [2] 20800 mg/l EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	1-methoxy-2-propanol; monopropylene glyco	l methyl ether (107-98-2)		
EC50 - Crustacea [1] 21100 – 25900 mg/l EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	LC50 - Fish [1]	6812 mg/l		
EC50 - Other aquatic organisms [1] 2954 mg/l ErC50 algae > 1000 mg/l	LC50 - Fish [2]	20800 mg/l		
ErC50 algae > 1000 mg/l 12.2. Persistence and degradability	EC50 - Crustacea [1]	21100 – 25900 mg/l		
12.2. Persistence and degradability	EC50 - Other aquatic organisms [1]	2954 mg/l		
	ErC50 algae	> 1000 mg/l		
SP 400	12.2. Persistence and degradability			
	SP 400			

ersistence and degradability	Not established. No data is available on the degradability of this product.
------------------------------	---

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.3. Bioaccumulative potential	12.3. Bioaccumulative potential	
SP 400		
Partition coefficient n-octanol/water (Log Kow)	Not applicable	
1-methoxy-2-propanol; monopropylene glyc	ol methyl ether (107-98-2)	
Bioconcentration factor (BCF REACH)	< 100	
Partition coefficient n-octanol/water (Log Pow)	0,37	
12.4. Mobility in soil		
No additional information available		
12.5. Results of PBT and vPvB assessment		
SP 400		
Results of PBT assessment	Contains no PBT/vPvB substances \geq 0.1% assessed in accordance with REACH Annex XIII	
12.6. Endocrine disrupting properties		
Adverse effects on the environment caused by endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.	
12.7. Other adverse effects		
Additional information Global warming potential (GWP)	 No other effects known 1 (Fluorinated greenhouse gases - (EC) No 517/2014) 	

SECTION 13: Disposal considerations		
13.1. Waste treatment methods		
Waste treatment methods European List of Waste (LoW) code	 Dispose of contents/container in accordance with licensed collector's sorting instructions. According to the European Waste Catalogue (EWC), Waste Codes are not product specific, but application specific Waste codes should be assigned by the user based on the application for which the product was used. 	

SECTION 14: Transpo				
ADR	IMDG	ΙΑΤΑ	ADN	RID
14.1. UN number or ID n	umber			
UN 1950	UN 1950	UN 1950	UN 1950	UN 1950
14.2. UN proper shippin	g name			
AEROSOLS	AEROSOLS	Aerosols, flammable	AEROSOLS	AEROSOLS
Transport document descr	iption			
UN 1950 AEROSOLS, 2.1, (D)	UN 1950 AEROSOLS, 2.1	UN 1950 Aerosols, flammable, 2.1	UN 1950 AEROSOLS, 2.1	UN 1950 AEROSOLS, 2.4
14.3. Transport hazard o	class(es)			
2.1	2.1	2.1	2.1	2.1

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

ADR	IMDG	ΙΑΤΑ	ADN	RID
		2		
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
4.5. Environmental haz	zards			
Dangerous for the environment: No	Dangerous for the environment: No Marine pollutant: No	Dangerous for the environment: No	Dangerous for the environment: No	Dangerous for the environment: No
No supplementary information	on available			

14.6. Special precautions for user

Overland transport	
Classification code (ADR)	: 5F
Special provisions (ADR)	: 190, 327, 344, 625
Limited quantities (ADR)	: 11
Excepted quantities (ADR)	: E0
Packing instructions (ADR)	: P207, LP200
Special packing provisions (ADR)	: PP87, RR6, L2
Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D
	. 0
Transport by sea	
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Stowage and handling (IMDG)	: SW1, SW22
Segregation (IMDG)	: SG69
Air transport	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L
Inland waterway transport	
Classification code (ADN)	: 5F
Special provisions (ADN)	: 190, 327, 344, 625
Limited quantities (ADN)	: 1L
Excepted quantities (ADN)	: E0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Equipment required (ADN)	:	PP, EX, A
Ventilation (ADN)	:	VE01, VE04
Number of blue cones/lights (ADN)	:	1
Rail transport		
Classification code (RID)		5F
Special provisions (RID)		190, 327, 344, 625
Limited quantities (RID)	:	1L
Excepted quantities (RID)	:	E0
Packing instructions (RID)	:	P207, LP200
Special packing provisions (RID)	:	PP87, RR6, L2
Mixed packing provisions (RID)	:	MP9
Transport category (RID)	:	2
Special provisions for carriage – Packages (RID)	:	W14
Special provisions for carriage - Loading, unloading	:	CW9, CW12
and handling (RID)		
Colis express (express parcels) (RID)	:	CE2
Hazard identification number (RID)	:	23

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content

: 530 g/l

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 16: Other information

Abbreviations and acronyms:		
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways	
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road	
ATE	Acute Toxicity Estimate	
BCF	Bioconcentration factor	
BLV	Biological limit value	
BOD	Biochemical oxygen demand (BOD)	
COD	Chemical oxygen demand (COD)	
DMEL	Derived Minimal Effect level	
DNEL	Derived-No Effect Level	
EC-No.	European Community number	
EC50	Median effective concentration	
EN	European Standard	
IARC	International Agency for Research on Cancer	
IATA	International Air Transport Association	
IMDG	International Maritime Dangerous Goods	
LC50	Median lethal concentration	
LD50	Median lethal dose	
LOAEL	Lowest Observed Adverse Effect Level	
NOAEC	No-Observed Adverse Effect Concentration	
NOAEL	No-Observed Adverse Effect Level	
NOEC	No-Observed Effect Concentration	
OECD	Organisation for Economic Co-operation and Development	
OEL	Occupational Exposure Limit	
PBT	Persistent Bioaccumulative Toxic	
PNEC	Predicted No-Effect Concentration	
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail	
SDS	Safety Data Sheet	
STP	Sewage treatment plant	
ThOD	Theoretical oxygen demand (ThOD)	
TLM	Median Tolerance Limit	
VOC	Volatile Organic Compounds	
CAS-No.	Chemical Abstract Service number	
N.O.S.	Not Otherwise Specified	
vPvB	Very Persistent and Very Bioaccumulative	
ED	Endocrine disrupting properties	

Full text of H- and EUH	Full text of H- and EUH-statements:	
Aerosol 1	Aerosol, Category 1	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:Aquatic Chronic 2Hazardous to the aquatic environment - Chronic Hazard, Category 2Aquatic Chronic 3Hazardous to the aquatic environment - Chronic Hazard, Category 3Asp. Tox. 1Aspiration hazard, Category 1EUH066Repeated exposure may cause skin dryness or cracking.Flam. Gas 1Flammable gases, Category 1Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Highly flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2Stort SE 3Specific target organ toxicity – Single exposure, Category 3, Narcosis				
Aquatic Chronic 3Hazardous to the aquatic environment – Chronic Hazard, Category 3Asp. Tox. 1Aspiration hazard, Category 1EUH066Repeated exposure may cause skin dryness or cracking.Flam. Gas 1Flammable gases, Category 1Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gase.H221Extremely flammable gase.H222Extremely flammable gase.H223Extremely flammable aerosol.H224Flammable liquid and vapour.H225Highly flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin crosion/irritation, Category 2	Full text of H- and E	Full text of H- and EUH-statements:		
Asp. Tox. 1Aspiration hazard, Category 1EUH066Repeated exposure may cause skin dryness or cracking.Flam. Gas 1Flammable gases, Category 1Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Skin corrosion/irritation, Category 2	Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2		
EUH066Repeated exposure may cause skin dryness or cracking.Flam. Gas 1Flammable gases, Category 1Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable gas.H222Extremely flammable aerosol.H223Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	Aquatic Chronic 3	Hazardous to the aquatic environment – Chronic Hazard, Category 3		
Flam. Gas 1Flammable gases, Category 1Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable aerosol.H222Extremely flammable aiquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	Asp. Tox. 1	Aspiration hazard, Category 1		
Flam. Liq. 2Flammable liquids, Category 2Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H222Extremely flammable aerosol.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	EUH066	Repeated exposure may cause skin dryness or cracking.		
Flam. Liq. 3Flammable liquids, Category 3H220Extremely flammable gas.H221Extremely flammable aerosol.H222Extremely flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Skin corrosion/irritation, Category 2	Flam. Gas 1	Flammable gases, Category 1		
H220Extremely flammable gas.H222Extremely flammable aerosol.H222Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Skin corrosion/irritation, Category 2	Flam. Liq. 2	Flammable liquids, Category 2		
H222Extremely flammable aerosol.H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	Flam. Liq. 3	Flammable liquids, Category 3		
H225Highly flammable liquid and vapour.H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H220	Extremely flammable gas.		
H226Flammable liquid and vapour.H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H222	Extremely flammable aerosol.		
H229Pressurised container: May burst if heated.H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H225	Highly flammable liquid and vapour.		
H280Contains gas under pressure; may explode if heated.H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H226	Flammable liquid and vapour.		
H304May be fatal if swallowed and enters airways.H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H229	Pressurised container: May burst if heated.		
H315Causes skin irritation.H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H280	Contains gas under pressure; may explode if heated.		
H336May cause drowsiness or dizziness.H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H304	May be fatal if swallowed and enters airways.		
H411Toxic to aquatic life with long lasting effects.H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H315	Causes skin irritation.		
H412Harmful to aquatic life with long lasting effects.Press. Gas (Liq.)Gases under pressure : Liquefied gasSkin Irrit. 2Skin corrosion/irritation, Category 2	H336	May cause drowsiness or dizziness.		
Press. Gas (Liq.) Gases under pressure : Liquefied gas Skin Irrit. 2 Skin corrosion/irritation, Category 2	H411	Toxic to aquatic life with long lasting effects.		
Skin Irrit. 2 Skin corrosion/irritation, Category 2	H412	Harmful to aquatic life with long lasting effects.		
	Press. Gas (Liq.)	Gases under pressure : Liquefied gas		
STOT SE 3 Specific target organ toxicity – Single exposure, Category 3, Narcosis	Skin Irrit. 2	Skin corrosion/irritation, Category 2		
	STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. Apart from any fair dealing for purposes of study, research and review of health, safety and environmental risks, no part of these documents may be reproduced by any process without written permission from CRC. The products are governed by Regulation (EC) No 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP); Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (in each case, as amended and replaced) and other applicable laws. It is an importers or downstream users responsibility to ensure compliance of product they import. An SDS provided in the official language(s) of a country is not a guarantee of compliance in that country.