



Certificate number: 2303774 (2)

Issued 29/03/2023

Expires 27/03/2028

Kiwa Regulation 4 (KUKreg4) Certification

Evaluation Guideline – Kiwa UK – EG004 – Regulation 4(1)(a)

Model number(s) – see Appendix

Zhejiang Mingshi Xingxin Hvac Technology Co.,Ltd.

Kiwa Watertec declares that legitimate confidence exists in the products specified in this certificate and supplied by the above organisation be relied upon to comply with the Kiwa Evaluation Guideline referred above.

Which verifies the requirements of:

Regulation 4(1)a of the Water Supply (Water Fittings) Regulations 1999 England & Wales: 2009 Northern Ireland and 2014 Byelaws Scotland.

This certificate has been issued in accordance with the Kiwa regulations for product certification.

Signed on behalf of Kiwa Watertec

David Jay, Business Unit Manager – Authorised Signatory
Kiwa Watertec

Publication of this certificate is allowed.

Products are intended to be used in the UK only. For other countries, other (National) requirements will apply.

See <https://www.kiwa.com/gb/en/about-kiwa/water-products/> or the QR code below to ensure that the certificate is still valid.

CERTIFICATE

Kiwa Watertec
(A Trading Division of Kiwa Ltd)
26A Rassau Industrial Estate
Ebbw Vale
Gwent
NP23 5SD
United Kingdom
T +44 (0)1495 308185
uk.water@kiwa.com
www.kiwa.co.uk

Certificate Issued to:
Zhejiang Mingshi Xingxin Hvac Technology Co.
Ltd
No. 7-1 Fengye Road
Diankou Town
Zhuji City
Zhejiang Province
China.



KUKreg4

Product Certificate

Appendix to Certificate number: 2303774

The following products belong to this certificate

<p>PRODUCT DESCRIPTION</p> <p>U Profile range of press fittings incorporating EPDM 'O'-rings. For use with PEX-AL-PEX pipe to ISO 21003. ATS3 – Without Production Surveillance.</p>
<p>MODEL(S)</p> <p>M-1-0101-U S1216 M-1-0103-U S1620 M-1-0104-U S2025 M-1-0109-U S2026 M-1-0105-U S2632 M-1-0202-U S20*16 M-1-0204-U S25*16 M-1-0206-U S25*20 M-1-0223-U S26*16 M-1-0225-U S26*20 M-1-0222-U S32*16 M-1-0207-U S32*20 M-1-0208-U S32*25 M-1-0226-U S32*26 M-1-0301-U S16*1/2"M M-1-0302-U S16*3/4"M M-1-0305-U S20*1/2"M M-1-0306-U S20*3/4"M M-1-0307-U S20*1"M M-1-0308-U S25*1/2"M M-1-0309-U S25*3/4"M M-1-0310-U S25*1"M M-1-0326-U S26*1/2"M M-1-0327-U S26*3/4"M M-1-0328-U S26*1"M M-1-0311-U S32*1/2"M M-1-0312-U S32*3/4"M M-1-0313-U S32*1"M M-1-0314-U S32*11/4"M M-1-0401-U S16*1/2"F M-1-0402-U S16*3/4"F M-1-0403-U S16*1"F M-1-0407-U S20*1/2"F M-1-0408-U S20*3/4"F M-1-0409-U S20*1"F M-1-0410-U S25*1/2"F M-1-0411-U S25*3/4"F M-1-0412-U S25*1"F M-1-0422-U S26*1/2"F M-1-0423-U S26*3/4"F M-1-0424-U S26*1"F M-1-0413-U S32*1/2"F M-1-0414-U S32*3/4"F M-1-0415-U S32*1"F M-1-0416-U S32*11/4"F M-1-0501-U L1216 M-1-0503-U L1620 M-1-0504-U L2025</p>

Product Certificate

Appendix to Certificate number: 2303774

M-1-0509-U L2026
M-1-0505-U L2632
M-1-0702-U L20*16
M-1-0704-U L25*16
M-1-0706-U L25*20
M-1-0720-U L26*16
M-1-0722-U L26*20
M-1-0707-U L32*16
M-1-0709-U L32*20
M-1-0710-U L32*25
M-1-0723-U L32*26
M-1-0801-U L16*1/2"M
M-1-0802-U L16*3/4"M
M-1-0805-U L20*1/2"M
M-1-0806-U L20*3/4"M
M-1-0813-U L20*1"M
M-1-0807-U L25*1/2"M
M-1-0808-U L25*3/4"M
M-1-0809-U L25*1"M
M-1-0807-U L26*1/2"M
M-1-0808-U L26*3/4"M
M-1-0809-U L26*1"M
M-1-0810-U L32*1/2"M
M-1-0811-U L32*3/4"M
M-1-0812-U L32*1"M
M-1-0814-U L32*1 1/4"M
M-1-0901-U L16*1/2"F
M-1-0902-U L16*3/4"F
M-1-0905-U L20*1/2"F
M-1-0906-U L20*3/4"F
M-1-0913-U L20*1"F
M-1-0907-U L25*1/2"F
M-1-0908-U L25*3/4"F
M-1-0909-U L25*1"F
M-1-0914-U L26*1/2"F
M-1-0915-U L26*3/4"F
M-1-0916-U L26*1"F
M-1-0910-U L32*1/2"F
M-1-0911-U L32*3/4"F
M-1-0912-U L32*1"F
M-1-0917-U L32*1 1/4"F
M-1-1001-U L16*1/2"F (A)
M-1-1002-U L16*3/4"F (A)
M-1-1004-U L20*1/2"F (A)
M-1-1006-U L20*3/4"F (A)
M-1-1007-U L25*3/4"F (A)
M-1-1008-U L26*3/4"F (A)
M-1-1101-U T1216
M-1-1103-U T1620
M-1-1104-U T2025
M-1-1109-U T2026
M-1-1105-U T2632
M-1-1220-U 16x16x20mm
M-1-1202-U 16x20x16mm
M-1-1203-U 16x25x16mm
M-1-1244-U 16x26x16mm

Product Certificate

Appendix to Certificate number: 2303774

M-1-1207-U 20x16x20mm
M-1-1253-U 20X20X26mm
M-1-1212-U 20x25x20mm
M-1-1213-U 25x16x25mm
M-1-1240-U 25x20x25mm
M-1-1248-U 25x32x20mm
M-1-1241-U 25x32x25mm
M-1-1242-U 20x26x20mm
M-1-1243-U 26X16X26mm
M-1-1215-U 26X20X26mm
M-1-1249-U 26x32x20mm
M-1-1216-U 26x32x26mm
M-1-1217-U 32X16X32mm
M-1-1225-U 32X20X32mm
M-1-1226-U 32X25X32mm
M-1-1247-U 32X26X32mm
M-1-1245-U 25x16x20mm
M-1-1218-U 26X16X20mm
M-1-1246-U 32x20x25mm
M-1-1219-U 32x20x26mm
M-1-1221-U 20x20x16mm
M-1-1223-U 25x25x20mm
M-1-1227-U 25x20x20mm
M-1-1250-U 25x20x16mm
M-1-1252-U 25x16x16mm
M-1-1253-U 25x25x16mm
M-1-1251-U 26x26x20mm
M-1-1254-U 26x20x16mm
M-1-1255-U 26x16x16mm
M-1-1256-U 26x26x16mm
M-1-1257-U 26X26X32mm
M-1-1258-U 32x25x25mm
M-1-1259-U 32x32x16mm
M-1-1260-U 32X32X20mm
M-1-1261-U 32X32X25mm
M-1-1262-U 32X26X20mm
M-1-1263-U 32X26X26mm
M-1-1264-U 32X32X26mm
M-1-2801-U T16*1/2"M*16
M-1-2802-U T16*3/4"M*16
M-1-2803-U T20*1/2"M*20
M-1-2804-U T20*3/4"M*20
M-1-2805-U T25*1/2"M*25
M-1-2806-U T25*3/4"M*25
M-1-2807-U T26*1/2"M*26
M-1-2808-U T26*3/4"M*26
M-1-2809-U T26*1"M*26
M-1-1301-U T16*1/2"F*16
M-1-1302-U T16*3/4"F*16
M-1-1305-U T20*1/2"F*20
M-1-1306-U T20*3/4"F*20
M-1-1307-U T20*1"F*20
M-1-1308-U T25*1/2"F*25
M-1-1309-U T25*3/4"F*25
M-1-1310-U T25*1"F*25
M-1-1329-U T26*1/2"F*26

Product Certificate

Appendix to Certificate number: 2303774

<p>M-1-1330-U T26*3/4"F*26 M-1-1331-U T26*1"F*26 M-1-1311-U T32*1/2"F*32 M-1-1312-U T32*3/4"F*32 M-1-1313-U T32*1"F*32 M-1-2601-U D1216 M-1-2603-U D1620 M-1-2604-U D2025 M-1-2606-U D2026 M-1-2605-U D2632 M-1-2901-U H16*1/2F M-1-2902-U H16*3/4F M-1-2903-U H20*1/2F M-1-2904-U H20*3/4F M-1-2907-U H25*1/2F M-1-2905-U H25*3/4F M-1-2908-U H25*1F M-1-2906-U H32*1F M-1-1801-U H16*1/2M M-1-1802-U H16*3/4M M-1-1803-U H20*1/2M M-1-1804-U H20*3/4M M-1-1805-U H25*1/2M M-1-1806-U H25*3/4M M-1-1807-U H32*1M M-1-2101-U X16 M-1-2102-U X20 M-1-2103-U X25 M-1-2104-U X32 S-1-0509 Tube S-1-0511 Tube S-1-0512 Tube S-1-0517 Tube S-1-0513 Tube</p>
<p>SIZE: See model.</p>
<p>SCOPE: Manufacturer recommended maximum working pressure 10 Bar & maximum operating temperature 95°C. Hygienic Purposes: Non-metallic materials suitable for continuous use up to 85°C. Above ground use only.</p>
<p>MARKING Manufacturers logo and size on fitting. Mingshi, WRAS, size, length and ISO21003 on wall.</p>
<p>MATERIALS Non-metallic materials assessed (BS6920) to point of discharge.</p>
<p>BACKFLOW PROTECTION NOTES N/A.</p>
<p>ADDITIONAL NOTES All water contact & exposed components satisfy opacity requirements.</p>

Extra Notes