



INDICATIVE PHOTO

General features : RS2130

RS range unit coolers have been designed to be installed inside cold rooms suited for fresh and frozen goods storage.

Their shape, being extremely compact, make their installation possible also in cold rooms having very small dimensions

RS range unit coolers are available in two main versions: the one suited for high temperature (differentiated fin spacing 3,5/7mm); the other version suited for medium and low temperature application (differentiated fin spacing 4,5/9mm).

In models for high temperature the version with the fitted defrosting heater is not available; for these models the heaters are optional items and they will be supplied not mounted.

The models for medium and low temperature application are available in the version supplied without defrosting heater (mod. RS...B) and with defrosting heater mounted and wired on the unit cooler's terminal box as well (mod. RS...BED).

The coil is made of aluminium fins and 3/8" copper tube with geometry 25x22
It is tested with nitrogen at a pressure of 25 bar

The fan motor models in use have the following features:

Manufactured following EN 60335-1 laws, with internal thermal protection
Draw through air flow

Fan guard made of plastic and brackets made of steel

Fan diameter 200mm, 34° inclination

Power supply 220-240V/1/50-60Hz

IP42 protection rate

Operating temperature from -40°C to +40°C

B insulation class

It is tested with nitrogen at a pressure of 25 bar

The housing is made of aluminium

The manufacturing solutions used give the housing strength and guarantee the absence of vibrations during the functioning.

Screws, washers and nuts are made of stainless steel

The B and BED models are supplied with fitted drip tray



INDICATIVE PHOTO


Product file : Unit coolers

Code	RS2130
Model	Ceiling
Range	RS
Application	MBP
Net weight	7,3 kg
Inlet connection	9.52 mm
Outlet connection	9.52 mm
Drain connection	1/2" Gas (20mm)
Ped	0
Rows	4
Fin spacing	3,5/7
Circuit volume	0,91 dm ³
Total surface	3,63 m ²

Fan motor

Fans no.	2
Diameter	200 mm
Power supply	220-240/1/50-60
Speed	1300 rpm
Power consumption	86 W
Current consumption	0,5 A
Air flow	337 m ³ /h
Air throw	2,5 m

Technical drawing - RS2130



Refrigerating capacity table (watt) - Gas : R404A

dT \ Tc	-5°C	0°C	2°C	4°C	6°C	8°C	10°C	12°C	15°C
10	916	989	1010	1020	1040	1060	1080	1110	1155
9	829	893	908	921	934	947	978	1000	1033
8	734	791	802	811	821	836	864	886	919
7	626	673	679	685	691	714	733	751	778
6	525	567	571	574	583	605	622	639	665
5	416	450	456	463	470	484	498	513	536