



**AT - Paint remover spray
7330**



SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** AT - Paint remover spray
7330
- Other means of identification:**
- UFI:** 5A9N-E0UM-P00X-JA82
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
- Relevant uses (Consumer use): Cleaner
Relevant uses (Professional users): Cleaner
Relevant uses (Industrial user): Cleaner
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
- AT-Tuote Oy
PL 37
FI-04131 Sipoo - Finland
Phone: +358 9 274 5500
info@attuote.fi
www.attuote.fi
- 1.4 Emergency telephone number:** General emergency number: 112, Poison Information Centre HUS: 09-471977 (Finland)

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
- Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
- Aerosol 1: Flammable aerosols, Category 1, H222
Aerosol 1: Pressurised container: May burst if heated., H229
Eye Irrit. 2: Eye irritation, Category 2, H319
STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
- Danger**
-  
- Hazard statements:**
- Aerosol 1: H222 - Extremely flammable aerosol.
Aerosol 1: H229 - Pressurised container: May burst if heated.
Eye Irrit. 2: H319 - Causes serious eye irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.
- Precautionary statements:**
- P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211: Do not spray on an open flame or other ignition source.
P251: Do not pierce or burn, even after use.
P280: Wear {0}.
P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F
P501: Dispose of contents/container according to the separated collection system used in your municipality.
- Supplementary information:**
- EUH066: Repeated exposure may cause skin dryness or cracking.
- Substances that contribute to the classification**
- acetone; N-butyl acetate; 1-methoxy-2-propanol
- 2.3 Other hazards:**
- Product does not meet PBT/vPvB criteria
Endocrine-disrupting properties: The product does not meet the criteria.

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Aerosol

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification		Concentration
CAS: 115-10-6 EC: 204-065-8 Index: 603-019-00-8 REACH: 01-211947128-37-XXXX	Dimethyl ether⁽¹⁾	ATP CLP00	50 - <75%
	Regulation 1272/2008	Flam. Gas 1A: H220; Press. Gas: H280 - Danger	
CAS: 67-64-1 EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49-XXXX	acetone⁽²⁾	ATP CLP00	25 - <50%
	Regulation 1272/2008	Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	
CAS: 123-86-4 EC: 204-658-1 Index: 607-025-00-1 REACH: 01-2119485493-29-XXXX	N-butyl acetate⁽²⁾	ATP CLP00	10 - <25%
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336; EUH066 - Warning	
CAS: 107-98-2 EC: 203-539-1 Index: 603-064-00-3 REACH: 01-2119457435-35-XXXX	1-methoxy-2-propanol⁽²⁾	ATP ATP01	2.5 - <10%
	Regulation 1272/2008	Flam. Liq. 3: H226; STOT SE 3: H336 - Warning	
CAS: 108-94-1 EC: 203-631-1 Index: 606-010-00-7 REACH: 01-2119453616-35-XXXX	Cyclohexanone⁽²⁾	Self-classified	1 - <2.5%
	Regulation 1272/2008	Acute Tox. 4: H302+H312+H332; Eye Dam. 1: H318; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Danger	
CAS: 69011-36-5 EC: 500-241-6 Index: Not relevant REACH: 01-2119976362-32-XXXX	Isotridecanol, ethoxylated < 2.5 mol EO⁽²⁾	Self-classified	1 - <2.5%
	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 3: H412 - Warning	
CAS: 112-34-5 EC: 203-961-6 Index: 603-096-00-8 REACH: 01-2119475104-44-XXXX	2-(2-butoxyethoxy)ethanol⁽¹⁾	ATP CLP00	<1%
	Regulation 1272/2008	Eye Irrit. 2: H319 - Warning	
CAS: 64-18-6 EC: 200-579-1 Index: 607-001-00-0 REACH: 01-2119491174-37-XXXX	Formic acid⁽²⁾	ATP ATP22	<1%
	Regulation 1272/2008	Acute Tox. 3: H331; Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 3: H226; Met. Corr. 1: H290; Skin Corr. 1A: H314; EUH071 - Danger	

⁽¹⁾ Substance with a Union workplace exposure limit

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification	Specific concentration limit
Formic acid CAS: 64-18-6 EC: 200-579-1	% (w/w) ≥ 90: Skin Corr. 1A - H314 10 ≤ % (w/w) < 90: Skin Corr. 1B - H314 2 ≤ % (w/w) < 10: Skin Irrit. 2 - H315 % (w/w) ≥ 10: Eye Dam. 1 - H318 2 ≤ % (w/w) < 10: Eye Irrit. 2 - H319

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	LD50 oral	1890 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation mist	0,728 mg/L *	
Formic acid CAS: 64-18-6 EC: 200-579-1	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation mist	0,814 mg/L *	

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Acute toxicity	Genus
----------------	----------------	-------

* Equivalent ATE value of the substance applicable to the exposure route of the product. For the ATE value associated with the exposure route of the substance, see section 11.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

- CONTINUED ON NEXT PAGE -

AT - Paint remover spray 7330



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

It is recommended to avoid environmental spillage of both the product and its container.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 6 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification		Occupational exposure limits		
Dimethyl ether CAS: 115-10-6 EC: 204-065-8		IOELV (8h)	1000 ppm	1920 mg/m ³
		IOELV (STEL)		
acetone CAS: 67-64-1 EC: 200-662-2		IOELV (8h)	500 ppm	1210 mg/m ³
		IOELV (STEL)		
N-butyl acetate CAS: 123-86-4 EC: 204-658-1		IOELV (8h)	50 ppm	241 mg/m ³
		IOELV (STEL)	150 ppm	723 mg/m ³
1-methoxy-2-propanol ⁽¹⁾ CAS: 107-98-2 EC: 203-539-1		IOELV (8h)	100 ppm	375 mg/m ³
		IOELV (STEL)	150 ppm	568 mg/m ³
Cyclohexanone ⁽¹⁾ CAS: 108-94-1 EC: 203-631-1		IOELV (8h)	10 ppm	40,8 mg/m ³
		IOELV (STEL)	20 ppm	81,6 mg/m ³
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6		IOELV (8h)	10 ppm	67,5 mg/m ³
		IOELV (STEL)	15 ppm	101,2 mg/m ³
Formic acid CAS: 64-18-6 EC: 200-579-1		IOELV (8h)	5 ppm	9 mg/m ³
		IOELV (STEL)		

⁽¹⁾ Skin

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	1894 mg/m ³	Not relevant
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	186 mg/kg	Not relevant
	Inhalation	Not relevant	2420 mg/m ³	1210 mg/m ³	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	11 mg/kg	Not relevant	11 mg/kg	Not relevant
	Inhalation	600 mg/m ³	600 mg/m ³	300 mg/m ³	300 mg/m ³
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	183 mg/kg	Not relevant
	Inhalation	553,5 mg/m ³	553,5 mg/m ³	369 mg/m ³	Not relevant
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	4 mg/kg	Not relevant	4 mg/kg	Not relevant
	Inhalation	80 mg/m ³	80 mg/m ³	40 mg/m ³	40 mg/m ³
Isotridecanol, ethoxylated < 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	2080 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	294 mg/m ³	Not relevant
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	83 mg/kg	Not relevant
	Inhalation	Not relevant	101,2 mg/m ³	67,5 mg/m ³	67,5 mg/m ³
Formic acid CAS: 64-18-6 EC: 200-579-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	9,5 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	471 mg/m ³	Not relevant

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
acetone CAS: 67-64-1 EC: 200-662-2	Oral	Not relevant	Not relevant	62 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	62 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	200 mg/m ³	Not relevant
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Oral	2 mg/kg	Not relevant	2 mg/kg	Not relevant
	Dermal	6 mg/kg	Not relevant	6 mg/kg	Not relevant
	Inhalation	300 mg/m ³	300 mg/m ³	35,7 mg/m ³	35,7 mg/m ³
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	Oral	Not relevant	Not relevant	33 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	78 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	43,9 mg/m ³	Not relevant
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Oral	1,5 mg/kg	Not relevant	1,5 mg/kg	Not relevant
	Dermal	1 mg/kg	Not relevant	1 mg/kg	Not relevant
	Inhalation	20 mg/m ³	40 mg/m ³	10 mg/m ³	20 mg/m ³
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	Oral	Not relevant	Not relevant	25 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	1250 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	87 mg/m ³	Not relevant
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Oral	Not relevant	Not relevant	5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	50 mg/kg	Not relevant
	Inhalation	Not relevant	60,7 mg/m ³	40,5 mg/m ³	40,5 mg/m ³
Formic acid CAS: 64-18-6 EC: 200-579-1	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	Not relevant	Not relevant	3 mg/m ³

PNEC:

Identification					
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	STP	160 mg/L	Fresh water	0,155 mg/L	
	Soil	0,045 mg/kg	Marine water	0,016 mg/L	
	Intermittent	1,549 mg/L	Sediment (Fresh water)	0,681 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,069 mg/kg	
acetone CAS: 67-64-1 EC: 200-662-2	STP	100 mg/L	Fresh water	10,6 mg/L	
	Soil	29,5 mg/kg	Marine water	1,06 mg/L	
	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	3,04 mg/kg	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	STP	35,6 mg/L	Fresh water	0,18 mg/L	
	Soil	0,09 mg/kg	Marine water	0,018 mg/L	
	Intermittent	0,36 mg/L	Sediment (Fresh water)	0,981 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,098 mg/kg	
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	STP	100 mg/L	Fresh water	10 mg/L	
	Soil	4,59 mg/kg	Marine water	1 mg/L	
	Intermittent	100 mg/L	Sediment (Fresh water)	52,3 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	5,2 mg/kg	
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	STP	10 mg/L	Fresh water	0,033 mg/L	
	Soil	0,03 mg/kg	Marine water	0,003 mg/L	
	Intermittent	0,329 mg/L	Sediment (Fresh water)	0,249 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,025 mg/kg	
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	STP	1,4 mg/L	Fresh water	0,074 mg/L	
	Soil	0,1 mg/kg	Marine water	0,007 mg/L	
	Intermittent	0,015 mg/L	Sediment (Fresh water)	0,604 mg/kg	
	Oral	Not relevant	Sediment (Marine water)	0,06 mg/kg	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	STP	200 mg/L	Fresh water	1,1 mg/L	
	Soil	0,32 mg/kg	Marine water	0,11 mg/L	
	Intermittent	11 mg/L	Sediment (Fresh water)	4,4 mg/kg	
	Oral	0,056 g/kg	Sediment (Marine water)	0,44 mg/kg	

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
Formic acid	STP	7,2 mg/L	Fresh water	2 mg/L
CAS: 64-18-6	Soil	1,5 mg/kg	Marine water	0,2 mg/L
EC: 200-579-1	Intermittent	1 mg/L	Sediment (Fresh water)	13,4 mg/kg
	Oral	Not relevant	Sediment (Marine water)	1,34 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

If the working conditions and/or safety measures adopted do not allow keeping the airborne concentration of the product below the exposure limits (if any) or at acceptable levels (if no exposure limits exist), suitable respiratory protection equipment chosen by a qualified professional should be used.

C.- Specific protection for the hands

Not relevant

D.- Eye and face protection

Not relevant

E.- Body protection

Not relevant

It is advised to implement additional emergency equipments in workplaces that are particularly exposed to the product or in situations where risk assessments highlight the necessity of such equipments.

Environmental exposure controls:

To comply with environmental protection regulations, it is recommended to prevent any spillage of the product and its container. For more detailed information, please refer to subsection 7.1.D.

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	98,25 % weight
V.O.C. density at 20 °C:	Not relevant
Average carbon number:	4,13
Average molecular weight:	80,83 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Aerosol
Appearance:	Fluid
Colour:	 Salmon
Odour:	Characteristic
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	-25 °C (Propellant)
Vapour pressure at 20 °C:	Not relevant *
Vapour pressure at 50 °C:	<300000 Pa (300 kPa)
Evaporation rate at 20 °C:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Product description:

Density at 20 °C:	Not relevant *
Relative density at 20 °C:	Not relevant *
Dynamic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *
Recipient pressure:	Not relevant *

Flammability:

Flash Point:	Not relevant *
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	240 °C (Propellant)
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Not relevant *
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	24,76 kJ/g
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

- CONTINUED ON NEXT PAGE -

AT - Paint remover spray 7330



SECTION 10: STABILITY AND REACTIVITY (continued)

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Precaution	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health.

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
- Contact with the eyes: Causes serious eye irritation.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Cyclohexanone (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

- CONTINUED ON NEXT PAGE -



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation gases	164000 ppm (4 h)	Rat
acetone CAS: 67-64-1 EC: 200-662-2	LD50 oral	5800 mg/kg	Rat
	LD50 dermal	7426 mg/kg	Rabbit
	LC50 inhalation vapour	76 mg/L (4 h)	Rat
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	LD50 oral	1890 mg/kg	Rat
	LD50 dermal	1100 mg/kg	
	LC50 inhalation vapour	6,2 mg/L	Rat
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LD50 oral	12789 mg/kg	Rat
	LD50 dermal	14112 mg/kg	Rabbit
	LC50 inhalation vapour	23,4 mg/L (4 h)	Rat
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	
Formic acid CAS: 64-18-6 EC: 200-579-1	LD50 oral	500 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	7,4 mg/L	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LD50 oral	>2000 mg/kg	
	LD50 dermal	>2000 mg/kg	
	LC50 inhalation vapour	>20 mg/L	

Only the physical form mist can occur during any reasonably expected use of the product, including when the product is used to produce a new product.

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	LC50	Not relevant		
	EC50	Not relevant		
	EC50	675 mg/L (72 h)	Scenedesmus subspicatus	Algae
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	LC50	20800 mg/L (96 h)	Pimephales promelas	Fish
	EC50	23300 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	1000 mg/L (168 h)	Selenastrum capricornutum	Algae
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	LC50	>0.1 - 1 mg/L (96 h)		Fish
	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
	EC50	>0.1 - 1 mg/L (72 h)		Algae
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	LC50	1300 mg/L (96 h)	Lepomis macrochirus	Fish
	EC50	2850 mg/L (24 h)	Daphnia magna	Crustacean
	EC50	53 mg/L (192 h)	Microcystis aeruginosa	Algae
Formic acid CAS: 64-18-6 EC: 200-579-1	LC50	175 mg/L (24 h)	Lepomis macrochirus	Fish
	EC50	120 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	26,9 mg/L (72 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
acetone CAS: 67-64-1 EC: 200-662-2	NOEC	Not relevant		
	NOEC	2212 mg/L	Daphnia magna	Crustacean
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	NOEC	Not relevant		
	NOEC	23,2 mg/L	Daphnia magna	Crustacean
Formic acid CAS: 64-18-6 EC: 200-579-1	NOEC	Not relevant		
	NOEC	100 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification	Degradability		Biodegradability	
acetone CAS: 67-64-1 EC: 200-662-2	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	96 %
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BOD5	Not relevant	Concentration	Not relevant
	COD	Not relevant	Period	5 days
	BOD5/COD	Not relevant	% Biodegradable	84 %
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	28 days
	BOD5/COD	Not relevant	% Biodegradable	90 %
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	87 %
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BOD5	0,25 g O2/g	Concentration	100 mg/L
	COD	2,08 g O2/g	Period	28 days
	BOD5/COD	0,12	% Biodegradable	92 %
Formic acid CAS: 64-18-6 EC: 200-579-1	BOD5	Not relevant	Concentration	100 mg/L
	COD	Not relevant	Period	14 days
	BOD5/COD	Not relevant	% Biodegradable	110 %

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
acetone CAS: 67-64-1 EC: 200-662-2	BCF	1
	Pow Log	-0.24
	Potential	Low

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential	
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	BCF	4
	Pow Log	1.78
	Potential	Low
1-methoxy-2-propanol CAS: 107-98-2 EC: 203-539-1	BCF	3
	Pow Log	-0.44
	Potential	Low
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	BCF	2
	Pow Log	0.86
	Potential	Low
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	BCF	
	Pow Log	4.73
	Potential	
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	BCF	0.46
	Pow Log	0.56
	Potential	Low
Formic acid CAS: 64-18-6 EC: 200-579-1	BCF	3
	Pow Log	-0.54
	Potential	Low

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
Dimethyl ether CAS: 115-10-6 EC: 204-065-8	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1,136E-2 N/m (25 °C)	Moist soil	Not relevant
acetone CAS: 67-64-1 EC: 200-662-2	Koc	1	Henry	2,93 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
N-butyl acetate CAS: 123-86-4 EC: 204-658-1	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	2,478E-2 N/m (25 °C)	Moist soil	Not relevant
Cyclohexanone CAS: 108-94-1 EC: 203-631-1	Koc	39.48	Henry	1,3 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	3,437E-2 N/m (25 °C)	Moist soil	Yes
Isotridecanol, ethoxylated< 2.5 mol EO CAS: 69011-36-5 EC: 500-241-6	Koc	441.7	Henry	Not relevant
	Conclusion	Moderate	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant
2-(2-butoxyethoxy)ethanol CAS: 112-34-5 EC: 203-961-6	Koc	48	Henry	7,2E-9 Pa·m ³ /mol
	Conclusion	Very High	Dry soil	Not relevant
	Surface tension	3,395E-2 N/m (25 °C)	Moist soil	Not relevant
Formic acid CAS: 64-18-6 EC: 200-579-1	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	3,862E-2 N/m (25 °C)	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Code	Description	Waste class (Regulation (EU) No 1357/2014)
16 05 04*	gases in pressure containers (including halons) containing hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2025 and RID 2025:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Special regulations: 190, 327, 344, 625
Tunnel restriction code: D
Physico-Chemical properties: see section 9
Limited quantities: 1 L
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

With regard to IMDG 42-24:



- 14.1 UN number or ID number:** UN1950
- 14.2 UN proper shipping name:** AEROSOLS
- 14.3 Transport hazard class(es):** 2
Labels: 2.1
- 14.4 Packing group:** N/A
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: 63, 959, 190, 277, 327, 344
EmS Codes: F-D, S-U
Physico-Chemical properties: see section 9
Limited quantities: 1 L
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2025:

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number or ID number:** UN1950
14.2 UN proper shipping name: AEROSOLS, flammable
14.3 Transport hazard class(es): 2
Labels: 2.1
14.4 Packing group: N/A
14.5 Environmental hazards: No
14.6 Special precautions for user
 Physico-Chemical properties: see section 9
14.7 Maritime transport in bulk according to IMO instruments: Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains Formic acid.
- Article 95, REGULATION (EU) No 528/2012: *Formic acid (64-18-6) - PT: (2,3,4,5,6)*
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) 2019/1021 on persistent organic pollutants: Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Regulation (EC) No 648/2004 on detergents:

In accordance with this regulation the product complies with the following:

The tensoactives contained in this mixture comply with the biodegradability criteria stipulated in Regulation (EC) n°648/2004 on detergents. The information to prove this is available to the relevant authorities of the Member States and will be shown to them by direct request or the request of a detergent manufacturer.

Labelling for contents:

Component	Concentration interval
Non-ionic surfactants	% (w/w) < 5

Preservation agents: Formic acid (FORMIC ACID).

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation.

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

Regulation (EC) No 1223/2009 of the European Parliament and of the Council of 30 November 2009 on cosmetic products

Regulation (EC) No 648/2004 of the European Parliament and of the Council of 31 March 2004 on detergents

Commission Regulation (EC) No 907/2006 of 20 June 2006 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes III and VII

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330**



SECTION 15: REGULATORY INFORMATION (continued)

Commission Regulation (EC) No 551/2009 of 25 June 2009 amending Regulation (EC) No 648/2004 of the European Parliament and of the Council on detergents, in order to adapt Annexes V and VI thereto (surfactant derogation)
Council Directive 75/324/EEC of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers
Commission Directive 94/1/EC of 6 January 1994 adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of the relating Member States to aerosol dispensers
Commission Directive 2008/47/EC of 8 April 2008 amending, for the purposes of adapting to technical progress, Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers
Commission Directive 2013/10/EU of 19 March 2013 amending Council Directive 75/324/EEC on the approximation of the laws of the Member States relating to aerosol dispensers in order to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures
COMMISSION DIRECTIVE (EU) 2016/2037 of 21 November 2016 amending Council Directive 75/324/EEC as regards the maximum allowable pressure of aerosol dispensers and to adapt its labelling provisions to Regulation (EC) No 1272/2008 of the European Parliament and of the Council on classification, labelling and packaging of substances and mixtures

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.
H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 3: H331 - Toxic if inhaled.
Acute Tox. 4: H302 - Harmful if swallowed.
Acute Tox. 4: H302+H312+H332 - Harmful if swallowed, in contact with skin or if inhaled.
Aquatic Acute 1: H400 - Very toxic to aquatic life.
Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.
Eye Dam. 1: H318 - Causes serious eye damage.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Flam. Gas 1A: H220 - Extremely flammable gas.
Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
Flam. Liq. 3: H226 - Flammable liquid and vapour.
Met. Corr. 1: H290 - May be corrosive to metals.
Press. Gas: H280 - Contains gas under pressure, may explode if heated.
Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.
Skin Irrit. 2: H315 - Causes skin irritation.
STOT SE 3: H335 - May cause respiratory irritation.
STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Eye Irrit. 2: Calculation method
STOT SE 3: Calculation method
Aerosol 1: Calculation method
Aerosol 1: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

- CONTINUED ON NEXT PAGE -

**AT - Paint remover spray
7330****SECTION 16: OTHER INFORMATION (continued)****Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -