

Veiktspējas dati

Āra iekārta

■ PUZ-SWM100VAA PUZ-SWM100YAA

Ūdens izplūdes temperatūra [°C]		25		35		40		45		50		55		60		65		70	
Apkārtnējā temperatūra [°C]		Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP
Max	-25	-	-	7.0	1.84	7.0	1.74	6.9	1.63	6.0	1.36	-	-	-	-	-	-	-	-
	-20	-	-	8.0	2.14	7.8	1.94	7.6	1.74	7.0	1.43	-	-	-	-	-	-	-	-
	-15	-	-	9.0	2.25	8.8	2.09	8.5	1.89	7.9	1.68	7.3	1.58	-	-	-	-	-	-
	-10	11.5	2.75	11.0	2.55	10.6	2.35	10.2	2.09	9.7	1.99	8.8	1.84	7.5	1.77	-	-	-	-
	-7	12.4	2.96	11.9	2.70	11.5	2.50	11.0	2.24	10.0	2.09	9.0	1.89	7.8	1.63	6.3	1.40	-	-
	2	12.4	3.22	12.1	3.05	11.8	2.81	11.5	2.50	11.0	2.30	9.5	1.97	8.7	1.89	7.8	1.71	-	-
	7	11.4	5.59	10.9	4.72	10.5	4.06	10.0	3.40	9.7	3.15	9.2	2.47	8.5	2.32	7.7	2.02	-	-
	12	12.9	6.40	12.2	5.54	12.0	4.83	11.7	4.06	11.1	3.61	10.5	3.04	9.5	2.63	8.7	2.41	-	-
	15	13.4	6.81	13.0	5.74	12.7	5.18	12.4	4.57	11.8	4.23	11.1	3.66	10.0	2.99	9.3	2.60	-	-
	20	14.2	7.72	13.8	6.35	13.5	5.74	13.1	5.08	12.5	4.49	11.4	3.87	10.5	3.66	10.0	3.44	-	-
Daļēja slodze	-25	-	-	7.0	1.84	7.0	1.74	6.9	1.63	6.0	1.36	-	-	-	-	-	-	-	-
	-20	-	-	8.0	2.14	7.8	1.94	7.6	1.74	7.0	1.43	-	-	-	-	-	-	-	-
	-15	-	-	9.0	2.25	8.8	2.09	8.5	1.89	7.9	1.68	7.3	1.58	-	-	-	-	-	-
	-10	10.0	3.32	10.0	2.92	10.0	2.55	10.0	2.19	9.7	1.99	8.8	1.84	7.5	1.77	-	-	-	-
	-7	10.0	3.57	10.0	2.98	10.0	2.70	10.0	2.40	10.0	2.09	9.0	1.89	7.8	1.63	6.3	1.40	-	-
	2	10.0	4.19	10.0	3.47	10.0	3.06	10.0	2.71	10.0	2.40	9.5	1.97	8.7	1.89	7.8	1.71	-	-
	7	8.0	5.99	8.0	5.02	8.0	4.37	8.0	3.66	8.0	3.30	7.0	2.70	7.0	2.37	7.0	1.99	-	-
	12	8.0	7.31	8.0	5.99	8.0	5.18	8.0	4.37	8.0	3.87	7.0	3.20	7.0	2.73	7.0	2.35	-	-
	15	8.0	7.62	8.0	6.30	8.0	5.59	8.0	4.88	8.0	4.38	7.0	3.76	7.0	3.04	7.0	2.71	-	-
	20	8.0	8.79	8.0	7.21	8.0	6.35	8.0	5.49	8.0	4.80	7.0	3.97	7.0	3.87	7.0	3.56	-	-
Daļēja slodze2	-25	-	-	5.6	1.79	5.6	1.74	5.5	1.63	4.8	1.41	-	-	-	-	-	-	-	-
	-20	-	-	6.4	2.40	6.3	2.14	6.1	1.84	5.6	1.53	-	-	-	-	-	-	-	-
	-15	-	-	7.2	2.55	7.0	2.30	6.8	2.04	6.3	1.84	5.8	1.63	-	-	-	-	-	-
	-10	8.0	3.77	8.0	3.16	8.0	2.75	8.0	2.35	7.8	2.09	7.4	1.89	6.0	1.82	-	-	-	-
	-7	8.0	3.83	8.0	3.16	8.0	2.86	8.0	2.50	8.0	2.19	7.6	1.99	6.2	1.68	5.0	1.45	-	-
	2	8.0	4.54	8.0	3.66	8.0	3.32	8.0	2.91	8.0	2.55	8.0	2.20	7.0	1.99	6.2	1.81	-	-
	7	6.4	5.89	6.4	5.07	6.4	4.42	6.4	3.76	6.4	3.35	5.6	2.78	5.6	2.42	5.6	2.07	-	-
	12	6.4	7.37	6.4	5.64	6.4	5.03	6.4	4.37	6.4	3.87	5.6	3.20	5.6	2.78	5.6	2.25	-	-
	15	6.4	7.62	6.4	6.25	6.4	5.54	6.4	4.77	6.4	4.28	5.6	3.71	5.6	3.04	5.6	2.65	-	-
	20	6.4	8.48	6.4	7.16	6.4	6.30	6.4	5.38	6.4	4.74	5.6	3.92	5.6	3.82	5.6	3.64	-	-
Min	-25	-	-	3.6	1.60	3.5	1.50	3.4	1.35	3.0	1.35	-	-	-	-	-	-	-	-
	-20	-	-	4.3	2.35	4.2	2.10	4.1	1.80	3.9	1.50	-	-	-	-	-	-	-	-
	-15	-	-	4.9	2.55	4.8	2.30	4.7	2.00	4.6	1.75	4.5	1.55	-	-	-	-	-	-
	-10	3.8	3.60	3.5	2.85	3.4	2.55	3.3	2.20	3.2	1.90	3.1	1.60	3.0	1.60	-	-	-	-
	-7	3.8	3.70	3.5	2.90	3.4	2.60	3.2	2.25	3.1	2.00	2.9	1.70	2.8	1.67	2.0	1.42	-	-
	2	3.4	4.60	3.2	3.60	2.9	3.20	2.6	2.75	2.4	2.05	2.1	1.80	2.0	1.92	1.9	1.55	-	-
	7	2.7	4.80	2.5	3.50	2.3	3.30	2.2	3.05	2.0	2.50	1.7	2.30	1.6	2.27	1.5	2.07	-	-
	12	3.3	5.35	3.0	4.45	2.8	4.20	2.6	3.90	2.2	3.20	1.8	2.60	1.8	2.58	1.7	2.30	-	-
	15	3.8	6.75	3.2	5.60	3.0	4.85	2.8	4.10	2.4	3.45	1.9	2.90	1.9	2.78	1.8	2.50	-	-
	20	4.2	7.45	3.7	6.55	3.4	5.65	3.1	4.75	2.9	3.90	2.6	3.30	2.5	3.38	2.3	3.05	-	-

Veiktspējas dati

Āra iekārta

■ PUZ-SWM120VAA PUZ-SWM120YAA

Ūdens izplūdes temperatūra [°C]		25		35		40		45		50		55		60		65		70	
Apkārtējā temperatūra [°C]		Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP	Jauda	COP
Max	-25	-	-	8.2	1.74	8.1	1.69	8.0	1.60	7.0	1.43	-	-	-	-	-	-	-	-
	-20	-	-	9.2	1.84	8.9	1.79	8.6	1.69	7.3	1.43	-	-	-	-	-	-	-	-
	-15	-	-	10.4	2.14	10.0	1.99	9.5	1.84	8.9	1.63	8.3	1.49	-	-	-	-	-	-
	-10	12.6	2.56	12.0	2.38	11.7	2.20	11.3	2.05	10.9	1.90	10.5	1.75	9.0	1.54	-	-	-	-
	-7	13.0	2.77	12.5	2.51	12.2	2.36	12.1	2.15	11.5	1.95	11.0	1.79	9.7	1.59	8.7	1.34	-	-
	2	13.0	3.22	12.7	2.90	12.6	2.66	12.4	2.40	12.2	2.15	12.1	1.94	10.8	1.74	9.8	1.52	-	-
	7	13.2	5.00	12.9	4.16	12.5	3.67	12.1	3.16	11.7	2.91	11.2	2.58	10.5	2.25	9.7	1.87	-	-
	12	15.0	5.51	14.5	4.64	14.2	4.18	13.8	3.67	13.2	3.17	12.6	2.71	11.7	2.35	10.2	2.01	-	-
	15	15.9	6.02	15.4	5.10	15.1	4.69	14.7	4.23	14.0	3.83	13.3	3.37	12.4	2.71	11.1	2.23	-	-
	20	16.9	6.22	16.4	5.41	16.2	4.95	15.9	4.49	15.2	3.98	14.5	3.47	13.5	3.06	12.1	2.70	-	-
Daļēja slodze	-25	-	-	8.2	1.74	8.1	1.69	8.0	1.60	7.0	1.43	-	-	-	-	-	-	-	-
	-20	-	-	9.2	1.84	8.9	1.79	8.6	1.69	7.3	1.43	-	-	-	-	-	-	-	-
	-15	-	-	10.4	2.14	10.0	1.99	9.5	1.84	8.9	1.63	8.3	1.49	-	-	-	-	-	-
	-10	12.1	2.87	11.0	2.76	11.0	2.46	11.0	2.10	10.9	1.90	10.5	1.75	9.0	1.54	-	-	-	-
	-7	12.1	3.28	12.1	2.74	12.1	2.51	12.1	2.20	11.5	2.00	11.0	1.79	9.7	1.59	8.7	1.34	-	-
	2	12.1	3.63	12.1	3.27	12.1	2.86	12.1	2.45	12.1	2.20	12.1	1.94	10.8	1.74	9.8	1.52	-	-
	7	10.0	5.86	10.0	4.87	10.0	4.13	10.0	3.47	10.0	3.11	7.0	2.70	7.0	2.30	7.0	2.01	-	-
	12	10.0	7.29	10.0	5.92	10.0	5.10	10.0	4.28	10.0	3.73	7.0	3.06	7.0	2.55	7.0	2.05	-	-
	15	10.0	7.60	10.0	6.27	10.0	5.56	10.0	4.84	10.0	4.29	7.0	3.68	7.0	2.96	7.0	2.37	-	-
	20	10.0	8.82	10.0	7.14	10.0	6.32	10.0	5.46	10.0	4.70	7.0	3.88	7.0	3.68	7.0	3.45	-	-
Daļēja slodze2	-25	-	-	6.6	1.84	6.5	1.79	6.4	1.69	5.6	1.53	-	-	-	-	-	-	-	-
	-20	-	-	7.4	2.25	7.2	2.04	6.9	1.79	5.8	1.53	-	-	-	-	-	-	-	-
	-15	-	-	8.3	2.45	8.0	2.25	7.6	2.04	7.1	1.79	6.6	1.63	-	-	-	-	-	-
	-10	9.6	3.54	8.8	3.07	8.8	2.72	8.8	2.36	8.7	2.10	8.4	1.90	7.2	1.59	-	-	-	-
	-7	9.6	3.69	9.6	3.13	9.6	2.82	9.6	2.46	9.2	2.15	8.8	1.95	7.8	1.64	7.0	1.40	-	-
	2	9.6	4.34	9.6	3.56	9.6	3.22	9.6	2.81	9.6	2.50	9.6	2.15	8.6	1.94	7.8	1.71	-	-
	7	8.0	6.02	8.0	5.07	8.0	4.44	8.0	3.72	8.0	3.27	5.6	2.73	5.6	2.35	5.6	2.10	-	-
	12	8.0	7.34	8.0	6.02	8.0	5.20	8.0	4.39	8.0	3.83	5.6	3.17	5.6	2.71	5.6	2.36	-	-
	15	8.0	7.70	8.0	6.32	8.0	5.61	8.0	4.90	8.0	4.34	5.6	3.73	5.6	3.01	5.6	2.47	-	-
	20	8.0	8.87	8.0	7.24	8.0	6.37	8.0	5.51	8.0	4.75	5.6	3.93	5.6	3.83	5.6	3.71	-	-
Min	-25	-	-	4.0	1.60	3.9	1.50	3.8	1.35	3.2	1.35	-	-	-	-	-	-	-	-
	-20	-	-	4.9	2.35	4.8	2.10	4.7	1.80	4.5	1.50	-	-	-	-	-	-	-	-
	-15	-	-	5.6	2.55	5.5	2.30	5.4	2.00	5.3	1.75	5.2	1.55	-	-	-	-	-	-
	-10	3.8	3.60	3.6	2.85	3.5	2.55	3.4	2.20	3.3	1.90	3.1	1.60	3.0	1.60	-	-	-	-
	-7	3.8	3.70	3.5	2.90	3.4	2.60	3.2	2.25	3.1	2.00	2.9	1.70	2.8	1.67	3.0	1.65	-	-
	2	3.5	4.60	3.2	3.60	3.0	3.20	2.7	2.75	2.4	2.05	2.1	1.80	2.0	1.92	2.9	1.80	-	-
	7	2.7	4.80	2.5	3.50	2.4	3.30	2.3	3.05	2.0	2.50	1.7	2.30	1.6	2.27	2.3	2.20	-	-
	12	3.4	5.35	3.1	4.45	2.9	4.20	2.7	3.90	2.3	3.20	1.9	2.60	1.8	2.58	2.5	2.55	-	-
	15	4.0	6.75	3.3	5.60	3.1	4.85	2.9	4.10	2.5	3.45	2.0	2.90	1.9	2.78	2.6	2.62	-	-
	20	4.3	7.45	3.8	6.55	3.5	5.65	3.2	4.75	2.9	3.90	2.6	3.30	2.5	3.38	3.5	3.02	-	-