

Technical Information

Product description:	Pliable conduit for electrical installations
Productname:	Ku-E-LF
Dimensions:	16, 20, 25, 32, 40 and 50 mm
Material:	PVC-U
Length:	Coils of 25 or 50 m
Colour:	light grey
Approval:	DEKRA mark
Product standard:	EN 61386-1:2008/A1:2019 EN 61386-22:2021/A11: 2021
Resistance to compression:	320N
Resistance to impact:	light
Minimum installation temperature:	- 5°C
Maximum installation temperature:	60°C
Resistance to flame propagation:	non flame propagation
Risk analysis:	This product is produced and tested according to the harmonized standards EN 61386-1 and EN 61386-22. All relevant product acceptance tests are carried out. There is no further risk involved in this product. Product and factory inspections are regularly carried out by an accredited certification institute; DEKRA certification.
System certification:	ISO 9001, ISO 14001

Tehniskā informācija

Produkta apraksts:	Elastīga caurule elektriskajām instalācijām
Produkta nosaukums:	Ku-E-LF
Izmēri	16, 20, 25, 32, 40 un 50 mm
Materiāls:	PVC-U
Garums:	25 vai 50 m ruļļi
Krāsa:	gaiši pelēka
Apstiprinājums:	DEKRA marķējums
Produkta standarts:	EN 61386-1:2008/A1:2019 EN 61386-22:2021/A11: 2021
Izturība pret saspiešanu:	320N
Izturība pret triecienu:	viegla
Minimālā uzstādīšanas temperatūra:	- 5°C
Maksimālā uzstādīšanas temperatūra:	60 °C
Izturība pret liesmu izplatīšanos:	neizplatās liesmas
Riska analīze:	Šis produkts ir ražots un testēts saskaņā ar saskaņotajiem standartiem EN 61386-1 un EN 61386-22. Ir veikti visi attiecīgie produkta pieņemšanas testi. Šim produktam nav citu risku. Produkta un rūpnīcas pārbaudes regulāri veic akreditēta sertifikācijas iestāde DEKRA certification.
Sistēmas sertifikācija:	ISO 9001, ISO 14001

TULKOJUMS PAREIZS
SIA "Pipelife Latvia", reģ. nr. 40003318628
Gundars Frīdenbergs
Rīgā, 14.01.2025.

