# Product data sheet
## Characteristics

# IMT33000
## Thorsman - Goliath 250 work lamp - 55 W - contour plug

### Main

| | |
|---|---|
| Range of product | Thorsman |
| Product name | Goliath 250 |
| Product or component type | Work lamp |
| Light source | Compact fluorescent tube 55 W |

### Complementary

| | |
|---|---|
| Type of installation | Outdoor<br>Indoor |
| [Ue] rated operational voltage | 230...240 V |
| Plug pole configuration | 2P |
| Plug standard | European |
| Light source type | Glare-proof<br>Flicker-proof |
| Luminous flux | 4000 lm |
| Bulb lifespan | 8000 h |
| Colour rendering index | $R_a$=82 |
| Colour temperature | 3500 K |
| Illuminance | 3 m : 210 lux<br>1 m : 1890 lux |
| Cable insulation material | Neoprene |
| Housing material | PC + rubber |
| Electrical connection | 5 m H07RN-F2x1.0 feed power cord |
| Electrical insulation class | Class II |
| Marking | F<br>ENEC 14 |
| Height | 316 mm |
| Width | 316 mm |
| Depth | 91 mm |
| Product weight | 2.9 kg |

### Environment

| | |
|---|---|
| Environmental characteristic | Waterproof<br>Dustproof |
| IP degree of protection | IP65 |
| Quality labels | CE<br>ENEC |
| Ambient air temperature for operation | -15...50 °C |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.