

Motion detector

sensIQ S KNX

EAN 4007841004057



Functional description

The reference motion detector for use anywhere on the building is also available in a version for the world's only open standard for home and building control. The sensIQ S KNX is just as perfect in form and functional diversity as all other sensIQ models. But this designer motion detector also provides the benefits of KNX technology. The electronic detector was developed specifically for wall mounting, nestles up against any facade and harmonises perfectly with modern architecture. Thanks to KNX control, its inner values are spectacular too.

Technical specifications

Type	Motion detectors
Type of accessory	Corner adapter
Dimensions (L x W x H)	128 x 74 x 114 mm
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	1360 Schaltzonen
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, detail	Reichweite von 2 - 20 m in 3 Richtungen (je 100 °) einstellbar
Reach, radial	r = 4 m (42 m ²)
Reach, tangential	r = 20 m (1047 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Constant-lighting control	Yes
Basic light level function	Yes
Basic light level function time	1-255 min
KNX functions	Light output 2x, Presence output, Light level, Basic light level function, Photo-cell controller, Close range
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus
With remote control	Yes
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C

<https://www.steinel-professional.de/>

Motion detector

sensIQ S KNX

EAN 4007841004057

Colour	black
Colour, RAL	9005
IDs, certificates	VDE
Manufacturer's Warranty	5 years
Version	black

Motion detector

sensIQ S KNX

EAN 4007841004057

Sensorenerfassungsbereich 1

