

STACK100 Pro

STACK100 Pro is suitable for residential and small commercial and industrial scenarios. Rackless and stackable design is easy to plug and play. It supports 12 clusters in parallel with a maximum capacity of 921kWh and supports 1C charge/discharge.



Flexible Expansion

Up to 12 clusters in parallel,
15kWh--921kWh capacity



Safe&Reliable

Six-layer safety protection,
IP66 high protection rating



Battery Equalization

Free mixing of modules
within three years



Easy Installation

0 wiring, rackless free stacking,
plug-and-play, one cluster
installation in 30min



Unparalleled Silence

Original cooling design with
natural convection for
ultimate silence



1C Rate

Suitable for grid frequency
regulation, charging stations and
other scenarios, cost saving

SPECIFICATION

Model	STACK100 Pro
Battery Type	LiFePO ₄ (LFP)
Nominal Battery Energy	5.12kWh
Usable Battery Energy	4.864kWh
Nominal Capacity	100Ah
Nominal Voltage	51.2V
Module Number per Cluster	3~15 Pcs
Operating Voltage	134.4V~864V
System Energy Range	15.36kWh~76.8kWh
Recommended Charge & Discharge C Rate	0.5C (50A)
Max. Charge & Discharge C Rate	1C (100A)
Peak Discharge Current (25°C)	125A, 2min
Recommended Charging & Discharging Power	2.56kW
Max. Charging & Discharge Power	5.12kW
Depth of Discharge (DOD)	95%
Charging Temp. Range	0°C~55°C/-20°C~55°C (Optional)
Discharging Temp. Range	-20°C~55°C
Net Weight (kg) ^[1]	34.6+55*n
Single Cluster Dimension (W/D/H) ^[2]	657/460/292+169*n
Protection Level	IP66
Communication	CAN/RS485
Cycle Life ^[3]	≥8000 Cycles
User Interface	Built-in WIFI module + APP, LED
Safety Protection	Pressure relief valve, Aerosol fire extinguisher, Temperature probe. Aerogel pad between batteries(Optional), Fireproof protection for the module(Optional), CO detector(Optional)
Cooling method	Natural Cooling
Installation	Cable-free stacking
Expansion	Up to 12 clusters in parallel
Warranty Period ^[4]	10 Years
Country of Manufacture	China
Battery Module Name	S51100 pro
Certification & Safety Standard	CE-EMC/CE-RED/62619/63056/62477/62040/UN38.3/VED2510
Compatible Inverters	Solis/GoodWe/Growatt/DEYE/Solinteg ect.

[1] Net Weight of Expansion Base and Expansion Upper Cover: 18.8kg. "n" stands for the number of battery modules

[2] Height of Expansion Upper Cover: 92mm

[3] Test conditions: 0.2C Charging & Discharging, 25°C, 95% DOD, 70%EOL

[4] Refer to Dyness Warranty Letter

