

Motion detector

IS 345 MX Highbay

EAN 4007841009731



Functional description

High-bay warehouses often have narrow aisles and high ceilings. Too high for most sensors. We have just the right solution: the IS 345 MX Highbay infrared motion detector was specially developed for mounting at heights of up to 14 m and for precision detection between narrow aisles. Perched up there, it gives you surveillance quality at the highest level, literally. So in the future, you can confidently set your sights higher when it comes to sensor systems!

Technical specifications

Type	Motion detectors
Dimensions (L x W x H)	65 x 95 x 95 mm
Mains power supply	16 V
Power supply, detail	DALI bus
Number of DALI users	3
Sensor Technology	passive infrared
Type of installation	Surface wiring
Switching zones	280 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Mounting height	4,00 – 14,00 m
Optimum mounting height	12 m
Detection angle	360 °
Angle of aperture	9 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	30 x 4 m (120 m ²)
Reach, tangential	30 x 4 m (120 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 1000 lx
Time setting	60 s – 60 min
LiveLink values	Light level, Motion detection, Presence detection
Constant-lighting control	Yes
Basic light level function	No
Settings via	LiveLink app
With remote control	No
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	white
Colour, RAL	9003
Manufacturer's Warranty	5 years
Version	LiveLink - surface-mounted, square https://www.steinell-professional.de/

Data sheet



Motion detector

IS 345 MX Highbay

EAN 4007841009731

Model

LiveLink

Motion detector

IS 345 MX Highbay

EAN 4007841009731

Sensorenerfassungsbereich 1

