

Motion detector

IS 140-2 Z-Wave

EAN 4007841029814



Functional description

Are you toying with the idea of fitting a motion detector to your building? The infrared controlled IS 140-2 Z-Wave motion detector gives you all the benefits of a modern detector. Needless to say, we always use the very latest technology for our bestsellers too. For instance, we have given the product in its current generation even more class: larger adjustment angle, even longer reach and even better detection performance. Treat your home to intelligent sensor technology. Smart home included. The optional Smart Friends Box and the free Smart Friends app make it easy to set the motion detector via smart phone or tablet. The light connected can also be switched ON or OFF via app. Other Steinel products can also be interconnected. If you wish, this also works via remote control when you are out. That completes your own smart home building automation system. Along with STEINEL products, Smart Friends solutions from PAULMANN, SCHELLENBERG and ABUS can also be integrated. Smart homes from a brand-name provider.

Technical specifications

Type	Motion detectors
Mains power supply	230 – 240 V , 50 / 50 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Electronic scalability	No
Mechanical scalability	No
Optimum mounting height	2 m
Detection angle	140 °
Angle of aperture	40 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, radial	r = 3 m (11 m ²)
Reach, tangential	r = 14 m (239 m ²)
Twilight setting TEACH	No
Twilight setting	2 – 2000 lx
Time setting	8 s – 35 min
Switching output 1, resistive	1000 W
Switching output 1, number of LEDs / fluorescent lamps	6 stk.
With bus coupling	No
IP rating	IP54
Material	Plastic
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	3 years
Version	white