

## Motion detector

# IS 3360

EAN 4007841033521



### Functional description

Large spaces, multi-storey car parks and production buildings with ceiling heights of up to 4 m rarely provide installation surfaces every metre. These environments call for motion detectors with a long reach. Like the IS 3360. It detects any tangential movement within an all-round distance of 20 metres. Even installed at heights of up to 4 metres. In short: one IS 3360 covers an area of more than 1000 m<sup>2</sup>! STEINEL Infrared technology that keeps its promises.

### Technical specifications

<b>Type</b>	Motion detectors
<b>Dimensions (Ø x H)</b>	124 x 78 mm
<b>Mains power supply</b>	220 – 240 V , 50 / 60 Hz
<b>Sensor Technology</b>	passive infrared
<b>Type of installation</b>	Concealed wiring
<b>Switching zones</b>	1416 Schaltzonen
<b>Electronic scalability</b>	No
<b>Mechanical scalability</b>	No
<b>Mounting height</b>	2,50 – 4,00 m
<b>Optimum mounting height</b>	2,8 m
<b>Detection angle</b>	360 °
<b>Angle of aperture</b>	180 °
<b>Sneak-by guard</b>	Yes
<b>Capability of masking out individual segments</b>	Yes
<b>Reach, tangential</b>	Ø 40 m (1257 m <sup>2</sup> )
<b>Twilight setting TEACH</b>	Yes
<b>Twilight setting</b>	2 – 1000 lx
<b>Time setting</b>	5 s – 15 min
<b>Control output, DALI</b>	Broadcast 1x30 electronic ballasts
<b>Constant-lighting control</b>	Yes
<b>Basic light level function</b>	Yes
<b>Basic light level function in per cent</b>	10 – 50 %
<b>Basic light level function time</b>	1-30 min, all night
<b>With remote control</b>	No
<b>Interconnection</b>	Yes
<b>IP rating</b>	IP20
<b>Material</b>	Plastic
<b>Ambient temperature</b>	-20 – 50 °C
<b>Colour</b>	white
<b>Colour, RAL</b>	9003
<b>Manufacturer's Warranty</b>	5 years
<b>Version</b>	DALI - concealed installation, round

Motion detector

# IS 3360

EAN 4007841033521

## Sensorenerfassungsbereich 1

