

Presence detector

IR Quattro SLIM XS

EAN 4007841033040



Functional description

Due to popular demand. The extra slim IR Quattro SLIM XS presence detector virtually disappears in the wall or ceiling. Thanks to the new and practical concealed box format it forms a remarkably unobtrusive symbiosis with the home environment and can now be installed in any standard concealed box. In short: our slimmest presence detector would seem to be pretending it wasn't even there - and yet is absolutely present when it matters. To be prepared for any situation, a round SLIM XS is also available.

Technical specifications

Type	Presence detector
Dimensions (L x W x H)	80 x 80 x 51 mm
Mains power supply	16 V
Power supply, detail	DALI bus
Number of DALI users	2
Sensor Technology	passive infrared
Application, place	Indoors
Type of installation	Concealed wiring
Switching zones	408 Schaltzonen
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	4 x 4 m (16 m ²)
Reach, tangential	4 x 4 m (16 m ²)
Reach, presence	4 x 4 m (16 m ²)
Twilight setting TEACH	Yes
Twilight setting	10 – 1000 lx
Time setting	60 s – 60 min
LiveLink values	Light level, Motion detection, Presence detection
Constant-lighting control	Yes
Basic light level function	No
Settings via	LiveLink app
With remote control	No
Interconnection	Yes
IP rating	IP20
Material	Plastic
Ambient temperature	0 – 40 °C
Colour	white
Colour, RAL	9010

<https://www.steinell-professional.de/>

Presence detector

IR Quattro SLIM XS

EAN 4007841033040

Manufacturer's Warranty

5 years

Version

LiveLink - square

Model

LiveLink

Presence detector

IR Quattro SLIM XS

EAN 4007841033040

Sensorenerfassungsbereich 1

