

Presence detector

IR Quattro SLIM XS

EAN 4007841033033



Functional description

Due to popular demand. The extra slim IR Quattro SLIM XS presence detector virtually disappears in the wall or ceiling. Thanks to the new and practical concealed box format it forms a remarkably unobtrusive symbiosis with the home environment and can now be installed in any standard concealed box. In short: our slimmest presence detector would seem to be pretending it wasn't even there - and yet is absolutely present when it matters. To be prepared for any situation, a round SLIM XS is also available.

Technical specifications

Type	Presence detector
Power supply, detail	KNX bus
Sensor Technology	passive infrared
Application, place	Indoors
Type of installation	Concealed wiring
Electronic scalability	No
Mechanical scalability	No
Mounting height	2,50 – 4,00 m
Optimum mounting height	2,8 m
Detection angle	360 °
Angle of aperture	160 °
Sneak-by guard	Yes
Capability of masking out individual segments	No
Reach, detail	Retina lens and hexagonal Fresnel structure
Reach, radial	4 x 4 m (16 m ²)
Reach, tangential	4 x 4 m (16 m ²)
Reach, presence	4 x 4 m (16 m ²)
Twilight setting TEACH	Yes
Time setting	60 s – 60 min
Basic light level function in per cent	10 – 50 %
Basic light level function time	Permanently ON, 1-255 min, all night
KNX functions	Light output 4x, Presence output, Light level, Constant-lighting control, Basic light level function, HVAC output
With bus coupling	Yes
Settings via	ETS software, Remote control, Bus
Interconnection	Yes
Type of interconnection	Master/slave, Master/master
IP rating	IP20
Material	Plastic
Colour	white
Colour, RAL	9010
Manufacturer's Warranty	5 years
Version	KNX - square

Data sheet



Presence detector

IR Quattro SLIM XS

EAN 4007841033033

Model

KNX

Presence detector

IR Quattro SLIM XS

EAN 4007841033033

Sensorenerfassungsbereich 1

