

Motion detector

sensIQ

EAN 4007841029586

**Functional description**

Most motion detectors sit around inconspicuously on a wall or ceiling. The sensIQ is different. Its design is so spectacular that it's a stylish signature on any facade, automatically attracting admiring glances. Behind its internationally acclaimed form is intelligent technology that puts virtually everything else in the shade. Unmatched, the detection reach of the four pyro sensors can easily be scaled in three directions via control dials – instead of shrouds of the type normally used on most other motion detectors. The floating module permits further functions, and you can use the newly available eNet version to integrate the sensor into existing eNet wireless networks.

Technical specifications

Type	Motion detectors
Type of accessory	Corner adapter
Dimensions (L x W x H)	144 x 113 x 172 mm
Mains power supply	220 – 240 V , 50 / 60 Hz
Sensor Technology	passive infrared
Application, place	Indoors, outdoors
Type of installation	Surface wiring
Switching zones	1360 Schaltzonen
Electronic scalability	No
Mechanical scalability	Yes
Mounting height	2,00 – 5,00 m
Optimum mounting height	2 m
Detection angle	300 °
Angle of aperture	90 °
Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Reach, detail	Reichweite von 2 - 20 m in 3 Richtungen (je 100 °) einstellbar
Reach, radial	r = 4 m (42 m ²)
Reach, tangential	r = 20 m (1047 m ²)
Twilight setting TEACH	Yes
Twilight setting	2 – 2000 lx
Time setting	5 s – 15 min
Switching output 1, resistive	2500 W
Switching output 1, number of LEDs / fluorescent lamps	8 stk.
Constant-lighting control	No
Basic light level function	No
With remote control	Yes
Interconnection	Yes
IP rating	IP54
Material	Plastic
Ambient temperature	-20 – 50 °C
Colour	Stainless steel
IDs, certificates	VDE

<https://www.steinell-professional.de/>

Data sheet



Motion detector

sensIQ

EAN 4007841029586

Manufacturer's Warranty

5 years

Version

inox
